

**ATTACHMENT C-1 – VISUAL MONITORING REPORT**

Visual monitoring shall occur within and adjacent to the firing range, and at the shoreline most likely to accumulate fireworks debris based on the prevailing wind, current, and tides. When practical and feasible, the Discharger shall conduct visual monitoring within one hour following the end of the fireworks event. The Discharger must conduct visual monitoring in the morning of the day immediately following the fireworks event.

The Discharger shall complete and electronically submit this form no later than 30 days following the end of the month in which the display of fireworks event occurred and with the Annual Report (due August 30 each year) using the State Water Board’s California Integrated Water Quality System (CIWQS) Program website ([https://www.waterboards.ca.gov/water\\_issues/programs/ciwqs](https://www.waterboards.ca.gov/water_issues/programs/ciwqs)).

<b>Date of the Visual Monitoring:</b>		<b>Time:</b>	AM/PM
<b>Surface Water Conditions</b>			
Describe floatable fireworks debris (if any):			
<b>Weather:</b> <input type="checkbox"/> Cloudy <input type="checkbox"/> Sunny <input type="checkbox"/> Rainy			
<b>Wind direction:</b>		<b>Wind Speed:</b>	
<b>Tide Direction:</b>		<b>Tidal Conditions:</b> High <input type="checkbox"/> Low	
<b>Presence of:</b> <input type="checkbox"/> Discoloration <input type="checkbox"/> Oil and Grease <input type="checkbox"/> Turbidity <input type="checkbox"/> Odor <input type="checkbox"/> Other			
(if any of the above is marked, please describe):			