

ATTACHMENT A

Non-Regulatory Amendments to the *Water Quality Control Plan for the Los Angeles Region* to Administratively Update Chapter 3 “Water Quality Objectives” by Incorporating Previously Adopted Amendments and Updated Tables

Amendments:

In “Chapter 3: Water Quality Objectives” of the Basin Plan, under the section “Regional Objectives for Inland Surface Waters”, delete the existing language under “Ammonia” (on page 3-3) and the corresponding Tables 3-1, 3-2, 3-3, and 3-4 (on pages 3-4, 3-5, 3-6, and 3-7, respectively), and replace with the following language and tables as directed in attachments to Regional Board Resolution Nos. R02-011, R04-022, R05-014, and R07-005.

Ammonia is a pollutant routinely found in the wastewater effluent of Publicly Owned Treatment Works (POTWs), in landfill-leachate, as well as in run-off from agricultural fields where commercial fertilizers and animal manure are applied. Ammonia exists in two forms – un-ionized ammonia (NH₃) and the ammonium ion (NH₄⁺). They are both toxic, but the neutral, un-ionized ammonia species (NH₃) is highly toxic to fish and other aquatic life. The ratio of toxic NH₃ to total ammonia (NH₄⁺ + NH₃) is primarily a function of pH, but it is also affected by temperature and other factors. Additional impacts can also occur as the oxidation of ammonia lowers the dissolved oxygen content of the water, further stressing aquatic organisms. Ammonia also combines with chlorine (often both are present) to form chloramines – persistent toxic compounds that extend the effects of ammonia and chlorine downstream.

Oxidation of ammonia to nitrate may lead to groundwater impacts in areas of recharge.

The freshwater one-hour average objective is dependent on pH and fish species (salmonids present or absent), but not temperature. It is assumed that salmonids may be present in waters designated in the Basin Plan as “COLD” or “MIGR” and that salmonids are absent in waters not designated in the Basin Plan as “COLD” or “MIGR,” in the absence of additional information to the contrary. The freshwater 30-day average objective is dependent on pH, temperature and the presence or absence of early life stages of fish (ELS). Implementation of the ELS Provision is described under “Implementation”, subparagraph 3. The freshwater four-day average objective is 2.5 times the 30-day average objective.

The objectives for inland surface waters not characteristic of freshwater are based on US EPA Ambient Water Quality Criteria for Ammonia (Saltwater) -1989. Both the one-hour average and 4-day average objectives are fixed concentrations for un-ionized ammonia, independent of pH, temperature, or salinity.

In order to protect aquatic life, ammonia concentrations in inland surface waters characteristic of freshwater (“freshwater” as determined by the provisions described herein under “IMPLEMENTATION,” 1. Determination of Freshwater, Brackish Water, or Saltwater Conditions) shall not exceed the values calculated for the appropriate instream conditions shown in Tables 3-1 to 3-3 (per U.S. EPA’s most recent criteria guidance document, “1999 Update of Ambient Water Quality Criteria for Ammonia”).

Resolution No. R13-0XX

For inland surface waters not characteristic of freshwater (as determined by the procedures in paragraph 1 of the Implementation Provisions below), the four-day average concentration of un-ionized ammonia shall not exceed 0.035 mg/L and the one-hour average concentration shall not exceed 0.233 mg/L.

The water quality objectives for ammonia in freshwater may be revised to reflect local waterbody characteristics using one or more of US EPA's procedures for deriving site-specific objectives (SSOs), which include the water-effect ratio (WER) procedure, recalculation procedure, and resident species procedure. In order to establish SSOs for a waterbody, a study must be conducted that is consistent with US EPA guidelines on deriving aquatic life criteria and SSOs, and the resultant SSOs must be fully approved through the Basin Plan amendment process.

In order to protect underlying groundwater basins, ammonia shall not be present at levels that when oxidized to nitrate, pose a threat to groundwater quality.

Table 3-1. One-hour Average Objective for Ammonia-N for Freshwaters (mg N/L)¹

pH	Waters Designated COLD and/or MIGR	Waters Not Designated COLD and/or MIGR
6.5	32.6	48.8
6.6	31.3	46.8
6.7	29.8	44.6
6.8	28.1	42.0
6.9	26.2	39.1
7.0	24.1	36.1
7.1	22.0	32.8
7.2	19.7	29.5
7.3	17.5	26.2
7.4	15.4	23.0
7.5	13.3	19.9
7.6	11.4	17.0
7.7	9.65	14.4

¹ For freshwaters, the one-hour average concentration of total ammonia as nitrogen (in mg N/L) shall not exceed the values described by the following equations.

For waters designated COLD and/or MIGR:

$$\text{One-hour Average Concentration} = \frac{0.275}{1+10^{7.204-pH}} + \frac{39.0}{1+10^{pH-7.204}}$$

Or for waters not designated COLD and/or MIGR:

$$\text{One-hour Average Concentration} = \frac{0.411}{1+10^{7.204-pH}} + \frac{58.4}{1+10^{pH-7.204}}$$

Resolution No. R13-0XX

pH	Waters Designated COLD and/or MIGR	Waters Not Designated COLD and/or MIGR
7.8	8.11	12.1
7.9	6.77	10.1
8.0	5.62	8.40
8.1	4.64	6.95
8.2	3.83	5.72
8.3	3.15	4.71
8.4	2.59	3.88
8.5	2.14	3.20
8.6	1.77	2.65
8.7	1.47	2.20
8.8	1.23	1.84
8.9	1.04	1.56
9.0	0.885	1.32

Reference: U.S. EPA 1999 Update of Ambient Water Quality Criteria for Ammonia

Table 3-2. 30-day Average Objective for Ammonia-N for Freshwaters Applicable to Waters Subject to the “Early Life Stage Present” Condition (mg N/L)

pH	Temperature, °C																
	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
6.5	6.67	6.46	6.06	5.68	5.33	4.99	4.68	4.39	4.12	3.86	3.62	3.39	3.18	2.98	2.80	2.62	2.46
6.6	6.57	6.36	5.97	5.59	5.25	4.92	4.61	4.32	4.05	3.80	3.56	3.34	3.13	2.94	2.75	2.58	2.42
6.7	6.44	6.25	5.86	5.49	5.15	4.83	4.52	4.24	3.98	3.73	3.50	3.28	3.07	2.88	2.70	2.53	2.37
6.8	6.29	6.10	5.72	5.36	5.03	4.72	4.42	4.14	3.89	3.64	3.42	3.20	3.00	2.82	2.64	2.47	2.32
6.9	6.12	5.93	5.56	5.21	4.89	4.58	4.30	4.03	3.78	3.54	3.32	3.11	2.92	2.74	2.57	2.41	2.25
7.0	5.91	5.73	5.37	5.04	4.72	4.43	4.15	3.89	3.65	3.42	3.21	3.01	2.82	2.64	2.48	2.32	2.18
7.1	5.67	5.49	5.15	4.83	4.53	4.25	3.98	3.73	3.50	3.28	3.08	2.88	2.70	2.53	2.38	2.23	2.09
7.2	5.39	5.22	4.90	4.59	4.31	4.04	3.78	3.55	3.33	3.12	2.92	2.74	2.57	2.41	2.26	2.12	1.99
7.3	5.08	4.92	4.61	4.33	4.06	3.80	3.57	3.34	3.13	2.94	2.76	2.58	2.42	2.27	2.13	2.00	1.87
7.4	4.73	4.59	4.30	4.03	3.78	3.55	3.32	3.12	2.92	2.74	2.57	2.41	2.26	2.12	1.98	1.86	1.74
7.5	4.36	4.23	3.97	3.72	3.49	3.27	3.06	2.87	2.69	2.53	2.37	2.22	2.08	1.95	1.83	1.72	1.61
7.6	3.98	3.85	3.61	3.39	3.18	2.98	2.79	2.62	2.45	2.30	2.16	2.02	1.90	1.78	1.67	1.56	1.47
7.7	3.58	3.47	3.25	3.05	2.86	2.68	2.51	2.36	2.21	2.07	1.94	1.82	1.71	1.60	1.50	1.41	1.32
7.8	3.18	3.09	2.89	2.71	2.54	2.38	2.23	2.10	1.96	1.84	1.73	1.62	1.52	1.42	1.33	1.25	1.17
7.9	2.80	2.71	2.54	2.38	2.24	2.10	1.96	1.84	1.73	1.62	1.52	1.42	1.33	1.25	1.17	1.10	1.03
8.0	2.43	2.36	2.21	2.07	1.94	1.82	1.71	1.60	1.50	1.41	1.32	1.24	1.16	1.09	1.02	0.957	0.897
8.1	2.10	2.03	1.91	1.79	1.68	1.57	1.47	1.38	1.29	1.21	1.14	1.07	1.00	0.938	0.879	0.824	0.773
8.2	1.79	1.74	1.63	1.53	1.43	1.34	1.26	1.18	1.11	1.04	0.973	0.912	0.855	0.802	0.752	0.705	0.661
8.3	1.52	1.48	1.39	1.30	1.22	1.14	1.07	1.00	0.941	0.882	0.827	0.775	0.727	0.682	0.639	0.599	0.562
8.4	1.29	1.25	1.17	1.10	1.03	0.966	0.906	0.849	0.796	0.747	0.700	0.656	0.615	0.577	0.541	0.507	0.475
8.5	1.09	1.06	0.990	0.928	0.870	0.816	0.765	0.717	0.672	0.630	0.591	0.554	0.520	0.487	0.457	0.428	0.401
8.6	0.920	0.892	0.836	0.784	0.735	0.689	0.646	0.606	0.568	0.532	0.499	0.468	0.439	0.411	0.386	0.362	0.339
8.7	0.778	0.754	0.707	0.663	0.622	0.583	0.547	0.512	0.480	0.450	0.422	0.396	0.371	0.348	0.326	0.306	0.287
8.8	0.661	0.641	0.601	0.563	0.528	0.495	0.464	0.435	0.408	0.383	0.359	0.336	0.315	0.296	0.277	0.260	0.244
8.9	0.565	0.548	0.513	0.481	0.451	0.423	0.397	0.372	0.349	0.327	0.306	0.287	0.269	0.253	0.237	0.222	0.208
9.0	0.486	0.471	0.442	0.414	0.389	0.364	0.342	0.320	0.300	0.281	0.264	0.247	0.232	0.217	0.204	0.191	0.179

* At temperatures below 14 °C, the objective is the same as that shown for 14 °C.

Reference: U.S. EPA 1999 Update of Ambient Water Quality Criteria for Ammonia²

² For freshwaters subject to the “Early Life Stage Present” condition, the thirty-day average concentration of total ammonia as nitrogen (in mg N/L) shall not exceed the values described by the following equation.

Resolution No. R13-0XX

$$\text{30-day Average Concentration} = \left(\frac{0.0577}{1+10^{7.688-pH}} + \frac{2.487}{1+10^{pH-7.688}} \right) * \text{MIN } 2.85, 1.45 * 10^{0.028 * 25 - T}$$

Where T = temperature expressed in °C.

In addition, for freshwaters, the highest four-day average within the 30-day period shall not exceed 2.5 times the 30-day average objective as calculated above.

Table 3-3. 30-day Average Objective for Ammonia-N for Freshwaters Applicable to Waters Subject to the “Early Life Stage Absent” Condition (mg N/L)

pH	Temperature, °C								
	0-7	8	9	10	11	12	13	14	15*
6.5	10.8	10.1	9.51	8.92	8.36	7.84	7.35	6.89	6.46
6.6	10.7	9.99	9.37	8.79	8.24	7.72	7.24	6.79	6.36
6.7	10.5	9.81	9.20	8.62	8.08	7.58	7.11	6.66	6.25
6.8	10.2	9.58	8.98	8.42	7.90	7.40	6.94	6.51	6.10
6.9	9.93	9.31	8.73	8.19	7.68	7.20	6.75	6.33	5.93
7.0	9.60	9.00	8.43	7.91	7.41	6.95	6.52	6.11	5.73
7.1	9.20	8.63	8.09	7.58	7.11	6.67	6.25	5.86	5.49
7.2	8.75	8.20	7.69	7.21	6.76	6.34	5.94	5.57	5.22
7.3	8.24	7.73	7.25	6.79	6.37	5.97	5.60	5.25	4.92
7.4	7.69	7.21	6.76	6.33	5.94	5.57	5.22	4.89	4.59
7.5	7.09	6.64	6.23	5.84	5.48	5.13	4.81	4.51	4.23
7.6	6.46	6.05	5.67	5.32	4.99	4.68	4.38	4.11	3.85
7.7	5.81	5.45	5.11	4.79	4.49	4.21	3.95	3.70	3.47
7.8	5.17	4.84	4.54	4.26	3.99	3.74	3.51	3.29	3.09
7.9	4.54	4.26	3.99	3.74	3.51	3.29	3.09	2.89	2.71
8.0	3.95	3.70	3.47	3.26	3.05	2.86	2.68	2.52	2.36
8.1	3.41	3.19	2.99	2.81	2.63	2.47	2.31	2.17	2.03
8.2	2.91	2.73	2.56	2.40	2.25	2.11	1.98	1.85	1.74
8.3	2.47	2.32	2.18	2.04	1.91	1.79	1.68	1.58	1.48
8.4	2.09	1.96	1.84	1.73	1.62	1.52	1.42	1.33	1.25
8.5	1.77	1.66	1.55	1.46	1.37	1.28	1.20	1.13	1.06
8.6	1.49	1.40	1.31	1.23	1.15	1.08	1.01	0.951	0.892
8.7	1.26	1.18	1.11	1.04	0.976	0.915	0.858	0.805	0.754
8.8	1.07	1.01	0.944	0.885	0.829	0.778	0.729	0.684	0.641
8.9	0.917	0.86	0.806	0.756	0.709	0.664	0.623	0.584	0.548
9.0	0.790	0.740	0.694	0.651	0.610	0.572	0.536	0.503	0.471

* At 15 °C and above, the regional 30-day average objective for waters subject to the “Early Life Stage Absent” condition is the same as that for waters subject to the “Early Life Stage Present” condition.

Reference: U.S. EPA 1999 Update of Ambient Water Quality Criteria for Ammonia³

³ For freshwaters subject to the “Early Life Stage Absent” condition, the thirty-day average concentration of total ammonia as nitrogen (in mg N/L) shall not exceed the values described by the following equation.

Resolution No. R13-0XX

$$\text{30-day Average Concentration} = \left(\frac{0.0577}{1 + 10^{7.688 - pH}} + \frac{2.487}{1 + 10^{pH - 7.688}} \right) * 1.45 * 10^{0.028 * 25 - MAX T, 7}$$

Where T = temperature expressed in °C.

In addition, for freshwaters, the highest four-day average within the 30-day period shall not exceed 2.5 times the 30-day average objective as calculated above.

Resolution No. R13-0XX

For the following waterbodies, the 30-day average water quality objective for ammonia shall be calculated as set forth below. In addition, the highest four-day average within the 30-day period shall not exceed 2.5 times the 30-day average objective shown in Table 3-4 "Site-specific 30-day Average Objectives for Ammonia by Waterbody Reach". The regional one-hour average objective for ammonia-N for freshwaters, specified in Table 3-1, remains the applicable one-hour objective for these waterbodies.

Notwithstanding the provisions below, regulatory actions, including but not limited to TMDLs and Waste Discharge Requirements, to achieve applicable site-specific objectives must ensure that downstream standards will also be achieved and downstream beneficial uses will also be protected as far as the discharges' impacts may be experienced.

As described in "Implementation", "3. Selection of 30-day Average Objective – Early Life Stage Provision", below, these waterbodies are subject to site-specific ELS provisions as set forth in Table 3-4 "Site-specific 30-day Average Objectives for Ammonia by Waterbody Reach", which incorporate seasonality of early life stages of fish.

Where deemed necessary, additional receiving water monitoring shall be required of dischargers subject to SSOs to ensure that the SSOs are as protective of beneficial uses as the regional objectives are intended to be and downstream standards are achieved. This additional monitoring shall be required through the discharger's NPDES permit monitoring and reporting program or other Board required monitoring programs. If monitoring indicates toxicity due to ammonia or a change in the waterbody that could impact the calculation or application of the SSOs, including either its chemical characteristics or the aquatic species present, including early life stages of fish, the Regional Board may reconsider the SSOs.

Table 3-4. Site-Specific 30-day Average Objectives for Ammonia by Waterbody Reach

WATERBODY	30-DAY AVERAGE OBJECTIVE
Los Angeles River, Reach 5 (Sepulveda Basin)	ELS Present (from April 1 – September 30) $CCC = \left(\frac{0.0676}{1 + 10^{7.688 - pH}} + \frac{2.912}{1 + 10^{pH - 7.688}} \right) * 0.854 * \text{MIN}(2.85, 2.85 * 10^{0.028 * (25 - T)})$
	ELS Absent (from October 1 – March 31) $CCC = \left(\frac{0.0676}{1 + 10^{7.688 - pH}} + \frac{2.912}{1 + 10^{pH - 7.688}} \right) * 0.854 * 2.85 * 10^{0.028 * (25 - \text{Max}(T, 7))}$
Los Angeles River, Reach 4 (Sepulveda Dam to Riverside Drive)	ELS Absent (year round) $CCC = \left(\frac{0.0676}{1 + 10^{7.688 - pH}} + \frac{2.912}{1 + 10^{pH - 7.688}} \right) * 0.854 * 2.85 * 10^{0.028 * (25 - \text{Max}(T, 7))}$
Los Angeles River, Reach 3 (Riverside Drive to Figueroa Street)	ELS Present (from April 1 – September 30) $CCC = \left(\frac{0.0676}{1 + 10^{7.688 - pH}} + \frac{2.912}{1 + 10^{pH - 7.688}} \right) * 0.854 * \text{MIN}(2.85, 2.85 * 10^{0.028 * (25 - T)})$
	ELS Absent (from October 1 – March 31) $CCC = \left(\frac{0.0676}{1 + 10^{7.688 - pH}} + \frac{2.912}{1 + 10^{pH - 7.688}} \right) * 0.854 * 2.85 * 10^{0.028 * (25 - \text{Max}(T, 7))}$
Burbank Western Wash (Burbank Water Reclamation Plant to confluence with LA River)	ELS Absent (year round) $CCC = \left(\frac{0.0676}{1 + 10^{7.688 - pH}} + \frac{2.912}{1 + 10^{pH - 7.688}} \right) * 0.92 * 2.03 * 10^{0.028 * (25 - \text{Max}(T, 7))}$
San Gabriel River, Reaches 2 and 3 (Confluence with San Jose Creek to Firestone Blvd.) (including all San Jose Creek WRP discharges)	ELS Present (from April 1 – September 30) $CCC = \left(\frac{0.0676}{1 + 10^{7.688 - pH}} + \frac{2.912}{1 + 10^{pH - 7.688}} \right) * 0.89 * \text{MIN}(2.85, 2.37 * 10^{0.028 * (25 - T)})$
	ELS Absent (from October 1 – March 31) $CCC = \left(\frac{0.0676}{1 + 10^{7.688 - pH}} + \frac{2.912}{1 + 10^{pH - 7.688}} \right) * 0.89 * 2.37 * 10^{0.028 * (25 - \text{Max}(T, 7))}$
San Gabriel River, Reach 1 (Firestone Blvd. to Willow St. or start of estuary)	ELS Absent (year round) $CCC = \left(\frac{0.0676}{1 + 10^{7.688 - pH}} + \frac{2.912}{1 + 10^{pH - 7.688}} \right) * 0.854 * 3.34 * 10^{0.028 * (25 - \text{Max}(T, 7))}$

WATERBODY	30-DAY AVERAGE OBJECTIVE
Santa Clara River, Reach 6 (Bouquet Canyon Rd. Bridge to West Pier Hwy 99)	ELS Present (from February 1 – September 30) $CCC = \left(\frac{0.0676}{1 + 10^{7.688 - pH}} + \frac{2.912}{1 + 10^{pH - 7.688}} \right) * 0.854 * \text{MIN}(2.85, 3.24 * 10^{0.028*(25-T)})$
	ELS Absent (from October 1 – January 31) $CCC = \left(\frac{0.0676}{1 + 10^{7.688 - pH}} + \frac{2.912}{1 + 10^{pH - 7.688}} \right) * 0.854 * 3.24 * 10^{0.028*(25 - \text{Max}(T,7))}$
Santa Clara River, Reach 5 (West Pier Hwy 99 to Blue Cut gauging station)	ELS Present (from February 1 – September 30) $CCC = \left(\frac{0.0676}{1 + 10^{7.688 - pH}} + \frac{2.912}{1 + 10^{pH - 7.688}} \right) * 0.854 * \text{MIN}(2.85, 3.20 * 10^{0.028*(25-T)})$
	ELS Absent (from October 1 – January 31) $CCC = \left(\frac{0.0676}{1 + 10^{7.688 - pH}} + \frac{2.912}{1 + 10^{pH - 7.688}} \right) * 0.854 * 3.20 * 10^{0.028*(25 - \text{Max}(T,7))}$
San Jose Creek (Pomona WRP to confluence with San Gabriel River)	ELS Present (from April 1 – September 30) $CCC = \left(\frac{0.0676}{1 + 10^{7.688 - pH}} + \frac{2.912}{1 + 10^{pH - 7.688}} \right) * 0.92 * \text{MIN}(2.85, 2.02 * 10^{0.028*(25-T)})$
	ELS Absent (from October 1 – March 31) $CCC = \left(\frac{0.0676}{1 + 10^{7.688 - pH}} + \frac{2.912}{1 + 10^{pH - 7.688}} \right) * 0.92 * 2.02 * 10^{0.028*(25 - \text{Max}(T,7))}$
Rio Hondo (Upstream of Whittier Narrows Dam)	ELS Present (from April 1 – September 30) $CCC = \left(\frac{0.0676}{1 + 10^{7.688 - pH}} + \frac{2.912}{1 + 10^{pH - 7.688}} \right) * 0.854 * \text{MIN}(2.85, 3.04 * 10^{0.028*(25-T)})$
	ELS Absent (from October 1 – March 31) $CCC = \left(\frac{0.0676}{1 + 10^{7.688 - pH}} + \frac{2.912}{1 + 10^{pH - 7.688}} \right) * 0.854 * 3.04 * 10^{0.028*(25 - \text{Max}(T,7))}$
Coyote Creek (Long Beach WRP to confluence with San Gabriel River)	ELS Absent (year round) $CCC = \left(\frac{0.0676}{1 + 10^{7.688 - pH}} + \frac{2.912}{1 + 10^{pH - 7.688}} \right) * 0.854 * 2.96 * 10^{0.028*(25 - \text{Max}(T,7))}$

IMPLEMENTATION

Implementation Provisions for the Application of Ammonia Objectives to Inland Surface Waters in the Los Angeles Region

1. Determination of Freshwater, Brackish Water or Saltwater Conditions⁴

(1) For inland surface waters in which the salinity is equal to or less than 1 part per thousand 95% or more of the time, the applicable objectives are the freshwater objectives, based on the US EPA "1999 Update of Ambient Water Quality Criteria for Ammonia." (2) For waters in which the salinity is equal to or greater than 10 parts per thousand 95% or more of the time, the applicable objectives are a 4-day average concentration of 0.035 mg un-ionized NH₃/L and a one-hour average concentration of 0.233 mg un-ionized NH₃/L. (3) For waters in which the salinity is between 1 and 10 parts per thousand, the applicable objectives are the more stringent of the freshwater or saltwater objectives. (a) However, the Regional Board may by adoption of a resolution approve the use of either freshwater or saltwater objectives for an enclosed bay, wetland or estuary with findings that scientifically defensible information and data demonstrate that on a site-specific basis the biology of the water body is dominated by freshwater aquatic life and that freshwater objectives are more appropriate; or conversely, the biology of the water body is dominated by saltwater aquatic life and that saltwater objectives are more appropriate. When determining the biotic dominance of a water body, the following factors shall be considered: the nature of the conditions causing the dominance (e.g., natural vs. anthropogenic), the historical conditions of the water body, and the reversibility of the existing conditions.

2. Selection of One-hour Average Objective – Salmonids Present vs. Salmonids Absent

It is assumed that salmonids may be present in waters designated in the Basin Plan as "COLD" or "MIGR" and that salmonids are absent in waters not designated in the Basin Plan as "COLD" or "MIGR," in the absence of additional information to the contrary.

3. Selection of 30-day Average Objective – Early Life Stage (ELS) Provision

Early life stages of fish are presumptively present and must be protected at all times of the year unless the water body is listed in Table 3-5 or unless a site-specific study is conducted, which justifies applying the ELS absent condition or a seasonal ELS present condition. Any change in the implementation provision for the ELS present/absent condition, including the assignment of water bodies, must be approved through the Basin Plan Amendment process.

If recent data and information are submitted to the Regional Board that provide substantial evidence that the physical conditions of a water body listed in Table 3-5 have changed due to restoration efforts such that there is habitat suitable for Early Life Stages of fish and one or more fish species that reproduce below 15 degrees Celsius is known to be present, in that or the adjacent water bodies, the Regional Board shall reconsider this implementation provision to ensure protection of Early Life Stages of fish in the water body.

⁴ The procedure described in this section to determine which objectives should be applied is the same method employed in the California Toxics Rule (Title 40, Code of Federal Regulations, § 131.38(c)(3)).

Resolution No. R13-0XX

To justify the ELS absent provision, information regarding fish species distributions, spawning periods, nursery periods and the duration of early life stages found in the water body must be presented. Expert opinions from fisheries biologists and other scientists will be considered. Where it can be obtained, a consensus opinion from a diverse body of experts would carry significant weight in determining the presence or absence of the ELS. Information on water body temperature, including spatial, seasonal and inter-annual variability will also be considered. The determination of the time frame during the year when early life stages are most likely not to be present in numbers that, if chronic toxicity did occur, would affect the long-term success of the fish populations, should include adequate scientific justification. The Regional Board will use the record supporting a Basin Plan amendment as the basis upon which to approve or disapprove changes to these implementation provisions for the 30-day average ammonia objective. The record should clearly explain all the factors and information considered in arriving at the determination. The Regional Board will consider and weigh the breadth and depth of scientific evidence in determining whether to remove the early life stage specification of a water body.

Where there is a site-specific ammonia objective for the water body, and the water body is not identified as ELS absent due to physical characteristics of the water body, separate implementation provisions to protect Early Life Stages of fish may apply, since the temperature threshold at which ELS are more sensitive than invertebrates may change based on these site-specific conditions. The potential for seasonality for all ELS present water bodies will be considered before the ELS provision is applied to water bodies with a site-specific objective.

Notwithstanding anything to the contrary herein, a watershed may have some reaches and tributaries with ELS present conditions and others with ELS absent conditions. Implementation actions to achieve applicable ammonia objectives must implement downstream objectives.

Table 3-5. Water Bodies Subject to 30-day Average Objective Applicable to “ELS Absent” Condition

Hydro Unit HUC 12 No.	Waterbody
CALLEGUAS-CONEJO CREEK WATERSHED	
180701030107	Calleguas Creek Reach 2 (Estuary to Potrero Rd)
180701030106	Revolon Slough (Calleguas Creek Rch 2 to Pleasant Valley Rd.)
180701030107	Revolon Slough (Pleasant Valley Rd. to Central Ave.)
180701030106	Beardsley Wash Reach 5 – Beardsley Channel (above Central Ave.)
180701030105	Conejo Creek
180701030107	Arroyo Conejo (Conejo Creek to North Fork Arroyo Conejo)
180701030104	Arroyo Conejo (above confl. with North Fork Arroyo Conejo)
180701030105	Arroyo Las Posas (Calleguas Creek Rch 3 to Long Canyon)
180701030103	Arroyo Las Posas (Long Canyon to Hitch Rd.)
180701030103	Arroyo Simi (Hitch Rd. to Happy Camp Canyon)
180701030102	Arroyo Simi (Happy Camp Canyon to Alamos Canyon)
180701030102	Arroyo Simi (Alamos Canyon to Tapo Canyon Creek)

Resolution No. R13-0XX

Hydro Unit HUC 12 No.	Waterbody
180701030101	Arroyo Simi (above Tapo Canyon Creek)
MALIBU CREEK WATERSHED	
180701040104	Cold Creek
180701040102	Medea Creek Reach 1 (Malibou Lake to Lindero Creek Reach 1)
180701040102	Medea Creek Reach 2 (above Lindero Creek Reach 1)
180701040104	Triunfo Creek Reach 1 (Malibou Lake to Lobo Canyon)
180701040101	Triunfo Creek Reach 2 (Lobo Canyon to Westlake Lake)
BALLONA CREEK WATERSHED	
180701040300	Ballona Creek Reach 2 (Estuary to National Blvd.)
180701040300	Ballona Creek Reach 1 (above National Blvd.)
DOMINGUEZ CHANNEL WATERSHED	
180701060102	Dominguez Channel (Estuary to 135th St.)
180701060101	Dominguez Channel (above 135th St)
LOS ANGELES RIVER WATERSHED	
180701050402	Los Angeles River Reach 1 (Estuary to Carson St.)
180701050402	Los Angeles River Reach 2 (Carson St. to Rio Hondo Reach 1)
180701050401	Los Angeles River Reach 2 (Rio Hondo Reach 1 to Figueroa St.)
180701050210	Los Angeles River Reach 3 (Figueroa St. to Riverside Dr.)
180701050208	Los Angeles River Reach 4 (Riverside Dr. to Sepulveda Dam)
180701050208	Los Angeles River Reach 5 (Sepulveda Dam to Balboa Blvd.)
180701050208	Los Angeles River Reach 6 (above Balboa Blvd.)
180701050402	Los Angeles River Reach 1 (Estuary to Carson St.)
180701050402	Los Angeles River Reach 2 (Carson St. to Rio Hondo Reach 1)
180701050401	Los Angeles River Reach 2 (Rio Hondo Reach 1 to Figueroa St.)
180701050303	Rio Hondo Reach 1 (Los Angeles River Reach 2 to Santa Ana Fwy)
180701050303	Rio Hondo Reach 2 (Santa Ana Fwy to Whittier Narrows Dam)
180701050302	Rio Hondo Reach 3 (except from Whittier Narrows to 4 miles north)
180701050209	Arroyo Seco Reach 3 (above Devils Gate Dam)
180701050208	Tujunga Wash
180701050402	Compton Creek
180701050209	Arroyo Seco Reach 1 (Los Angeles River Reach 2 to Holly St.)
180701050209	Arroyo Seco Reach 2 (Holly St. to Devils Gate Dam)
180701050208	Burbank Western Channel
180701050206	Pacoima Wash
SAN GABRIEL RIVER WATERSHED	
180701060606	San Gabriel River Reach 1 (San Gabriel River Estuary to Firestone Blvd.)
180701060606	San Gabriel River Reach 2 (Firestone Blvd. to Whittier Narrows Dam)
180701060601	San Gabriel River Reach 3 (Whittier Narrows Dam to San Jose Creek)
180701060601	San Gabriel River Reach 3 (San Jose Creek to Ramona Blvd.)
180701060601	San Gabriel River Reach 4 (Ramona Blvd. to Santa Fe Dam)

Hydro Unit HUC 12 No.	Waterbody
180701060601	San Gabriel River Reach 5 (Santa Fe Dam to Huntington Dr.)
180701060601	San Gabriel River Reach 5 (Huntington Dr. to Van Tassel Canyon)
180701060506	Coyote Creek (San Gabriel River Estuary to La Cañada Verde Creek)
180701060603	Coyote Creek (above La Cañada Verde Creek)
180701060502	San Jose Creek Reach 1 (San Gabriel River Reach 3 to Temple Ave.)
180701060501	San Jose Creek Reach 2 (Temple Ave. to Thompson Wash)

*Notes:

- 1) All wetlands/estuaries and lagoons are assumed to have ELS.
- 2) Whittier Narrows flood control basin is listed separately in the Basin Plan
- 3) Based on published literature and expert opinion, fish species known to reproduce in significant numbers below 15 degrees Celsius are absent in these water bodies, or the water bodies are known to have physical conditions that preclude reproduction and early development of these species in significant numbers. These species include: steelhead/rainbow trout, three-spine stickleback, brown trout, prickly sculpin, staghorn sculpin, striped mullet, starry flounder, arrow goby, and Pacific lamprey.

4. Existence of Threatened or Endangered Species

Where the Regional Board determines that endangered or threatened species in the Los Angeles Region are more sensitive to a pollutant than the species upon which the objectives are based, more stringent, site-specific modifications of the objectives shall be performed using U.S. EPA approved methods.⁵ Temperature and pH must be adjusted to match the conditions used to calculate the objectives. Tests to determine site-specific objectives for threatened and endangered species can be conducted in site water or laboratory water.

5. Translation of Objectives into Effluent Limits⁶

If the Regional Board determines that water quality based effluent limitations are necessary to control ammonia in a discharge, the permit shall contain effluent limitations for ammonia using one of the following methods:

1. Use the following procedure based on a steady-state model:

Step 1: Identify the applicable water quality objectives for ammonia for the receiving water immediately downstream of the discharge.

Step 2a: For each water quality objective, calculate the effluent concentration allowance (ECA) using the following steady-state mass balance model:

⁵ U.S. EPA. 1985. "Guidance for Deriving Numerical National Water Quality Criteria for the Protection of Aquatic Organisms and their Uses". U.S. EPA. 1994. "Water Quality Standards Handbook, Second Edition", Chapter 3, Section 3.7.4 "The Recalculation Procedure".

⁶ The method whereby objectives are translated to effluent limits is similar to the method contained in the "Policy for Implementation of Toxics Standards for Inland Surface Waters, Enclosed Bays, and Estuaries of California" (2000). The method is also consistent with that outlined in the U.S. EPA "Technical Support Document for Water Quality-based Toxics Control (1991).

Resolution No. R13-0XX

If a mixing zone has not been authorized by the Regional Board, or when $WQO \leq B$:

$$ECA = WQO$$

If a mixing zone has been authorized by the Regional Board:⁷

$$ECA = WQO + D (WQO - B) \text{ when } WQO > B$$

Where: WQO = water quality objective (adjusted as described in Step 2b, if necessary, for temperature, pH, and salinity.)

D = dilution credit

B = ambient background concentration

The dilution credit (D) shall be derived taking into account water body characteristics and the type of discharge (i.e. completely-mixed or incompletely-mixed with the receiving water), using established procedures in the "Policy for Implementation of Toxics Standards for Inland Surface Waters, Enclosed Bays, and Estuaries of California" (2000) or other appropriate U.S. EPA approved methodologies. The resulting dilution credit must be approved by the Executive Officer.

The ambient background concentration shall be the observed maximum as determined in accordance with procedures in the "Policy for Implementation of Toxics Standards for Inland Surface Waters, Enclosed Bays, and Estuaries of California" (2000) or other appropriate U.S. EPA approved methodologies. The resulting ambient background concentration must be approved by the Executive Officer.

Step 2b: In order to adjust the un-ionized saltwater ammonia objective to an ECA expressed as total ammonia, the following equation shall be used:

$$[NH_4^+] + [NH_3] = [NH_3] + [NH_3] * 10^{(pK_a^s + 0.0324 (298-T) + 0.0415 P/T - pH)}$$

Where: $P = 1 \text{ atm}$

T = temperature ($^{\circ} K$)

$pK_a^s = 0.116 * i + 9.245$, the stoichiometric acid hydrolysis constant of ammonium ions in saltwater based on i

$i = 19.9273 S (1000 - 1.005109 S)^{-1}$, the molal ionic strength of saltwater based on S

S = salinity

(Per U.S. EPA Ambient Water Quality Criteria for Ammonia (Saltwater)-1989)

Step 3: For each ECA calculated in Step 2, determine the long-term average discharge condition (LTA) by multiplying the ECA with a factor (multiplier) that adjusts for effluent variability. The multiplier shall be calculated as described below, or shall be found in Table 3-6. To use Table 3-6, the

⁷ Mixing zones may be authorized on a discharge-by-discharge basis per the mixing zone provision in Chapter 4 of the Basin Plan.

Formatted: Indent: Left: 2"

Formatted: Indent: Left: 1.5"

coefficient of variation (CV)⁸ for the effluent ammonia concentration must first be calculated. If (a) the number of effluent data points is less than 10, or (b) at least 80 percent of the effluent data are reported as not detected, then the CV shall be set equal to 0.6. When calculating the CV in this procedure, if a data point is below the detection limit in an effluent sample, one-half the detection limit shall be used as the value in the calculation. Multipliers for one-hour average, four-day average, and 30-day average objectives for ammonia that correspond to the CV can be found in Table 3-6.

ECA Multipliers:

$$ECA \text{ multiplier}_{1\text{-hour}99} = e^{0.5s^2 - zs}$$

$$ECA \text{ multiplier}_{4\text{-day}99} = e^{0.5s_4^2 - zs_4}$$

$$ECA \text{ multiplier}_{30\text{-day}99} = e^{0.5s_{30}^2 - zs_{30}}$$

Where s = standard deviation

$$s = \left[\ln CV^2 + 1 \right]^{0.5}$$

$$s^2 = \ln CV^2 + 1$$

$$s_4 = \left[\ln CV^2 / 4 + 1 \right]^{0.5}$$

$$s_4^2 = \ln CV^2 / 4 + 1$$

$$s_{30} = \left[\ln CV^2 / 30 + 1 \right]^{0.5}$$

$$s_{30}^2 = \ln CV^2 / 30 + 1$$

$z = 2.326$ for 99th percentile probability basis

LTA Equations:

$$LTA_{1\text{-hour}99} = ECA_{1\text{-hour}} * ECA \text{ multiplier}_{1\text{-hour}99}$$

$$LTA_{4\text{-day}99} = ECA_{4\text{-day}} * ECA \text{ multiplier}_{4\text{-day}99}$$

$$LTA_{30\text{-day}99} = ECA_{30\text{-day}} * ECA \text{ multiplier}_{30\text{-day}99}$$

Step 4: Select the lowest (most limiting) of the LTAs derived in Step 3 (LTA_{min}).

Step 5: Calculate water quality based effluent limitations (a maximum daily effluent limitation, MDEL, and an average monthly effluent limitation, AMEL) by multiplying LTA_{min} (as selected in Step 4) with a factor (multiplier) that adjusts the

⁸ The coefficient of variation (CV) is a measure of the data variability and is calculated as the estimated standard deviation divided by the arithmetic mean of the observed values.

Resolution No. R13-0XX

averaging period and exceedance frequency of the objective, and the effluent monitoring frequency, as follows:

MDEL and AMEL Equations:

$$MDEL = LTA_{min} * MDEL \text{ multiplier}_{99}$$

$$AMEL = LTA_{min} * AMEL \text{ multiplier}_{95}$$

The MDEL and AMEL multipliers shall be calculated as described below, or shall be found in Table 3-7 using the previously calculated CV and monthly sampling frequency (n) of ammonia in the effluent. If the LTA_{min} selected in Step 4 is $LTA_{4\text{-day}99}$ and the sampling frequency is four times per month or less, then n shall be set equal to 4. If the LTA_{min} selected in Step 4 is $LTA_{30\text{-day}99}$ and the sampling frequency is 30 times per month or less, then n shall be set equal to 30.

MDEL and AMEL Multipliers:

$$MDEL \text{ multiplier}_{99} = e^{zs - 0.5s^2}$$

Where $z = 2.326$ for 99th percentile probability basis

$$s = \left[\ln CV^2 + 1 \right]^{0.5}$$

$$s^2 = \ln CV^2 + 1$$

$$AMEL \text{ multiplier}_{95} = e^{zs_n - 0.5s_n^2}$$

Where $z = 1.645$ for 95th percentile probability basis

$$s_n = \left[\ln CV^2 / n + 1 \right]^{0.5}$$

$$s_n^2 = \ln CV^2 / n + 1$$

$n =$ number of samples per month

2. Apply a dynamic model approved by the Regional Board.
3. If a Total Maximum Daily Load (TMDL) for ammonia is in effect, the permit shall contain effluent limitations for ammonia that are based on the waste load allocation for ammonia in the TMDL.

Resolution No. R13-0XX

Table 3-6 - Effluent Concentration Allowance (ECA)
Multipliers for Calculating Long-Term Averages (LTAs)

Coefficient of Variation (CV)	One-hour Multiplier	4-day Multiplier	30-day Multiplier
	99th Percentile Occurrence Probability	99th Percentile Occurrence Probability 4 day	99th Percentile Occurrence Probability 30 day
0.1	0.797	0.891	0.959
0.2	0.643	0.797	0.919
0.3	0.527	0.715	0.882
0.4	0.440	0.643	0.846
0.5	0.373	0.581	0.812
0.6	0.321	0.527	0.78
0.7	0.281	0.481	0.75
0.8	0.249	0.440	0.721
0.9	0.224	0.404	0.693
1.0	0.204	0.373	0.667
1.1	0.187	0.345	0.642
1.2	0.174	0.321	0.619
1.3	0.162	0.300	0.596
1.4	0.153	0.281	0.575
1.5	0.144	0.264	0.555
1.6	0.137	0.249	0.535
1.7	0.131	0.236	0.517
1.8	0.126	0.224	0.5
1.9	0.121	0.214	0.483
2.0	0.117	0.204	0.468
2.1	0.113	0.195	0.453
2.2	0.110	0.187	0.438
2.3	0.107	0.180	0.425
2.4	0.104	0.174	0.412
2.5	0.102	0.168	0.4
2.6	0.100	0.162	0.388
2.7	0.098	0.157	0.377
2.8	0.096	0.153	0.366
2.9	0.094	0.148	0.356
3.0	0.093	0.144	0.346
3.1	0.091	0.141	0.337
3.2	0.090	0.137	0.328
3.3	0.089	0.134	0.32
3.4	0.088	0.131	0.312
3.5	0.087	0.128	0.304
3.6	0.086	0.126	0.297
3.7	0.085	0.123	0.29
3.8	0.084	0.121	0.283
3.9	0.083	0.119	0.277
4.0	0.082	0.117	0.271

Table 3-7 - Long-Term Average (LTA) Multipliers for Calculating Effluent Limitations

Coefficient of Variation	MDEL Multiplier	AMEL Multiplier		
	99th Percentile Occurrence Probability	95th Percentile Occurrence Probability		
(CV)		n=4	n=8	n=30
0.1	1.25	1.08	1.06	1.03
0.2	1.55	1.17	1.12	1.06
0.3	1.90	1.26	1.18	1.09
0.4	2.27	1.36	1.25	1.12
0.5	2.68	1.45	1.31	1.16
0.6	3.11	1.55	1.38	1.19
0.7	3.56	1.65	1.45	1.22
0.8	4.01	1.75	1.52	1.26
0.9	4.46	1.85	1.59	1.29
1.0	4.90	1.95	1.66	1.33
1.1	5.34	2.04	1.73	1.36
1.2	5.76	2.13	1.80	1.39
1.3	6.17	2.23	1.87	1.43
1.4	6.56	2.31	1.94	1.47
1.5	6.93	2.40	2.00	1.50
1.6	7.29	2.48	2.07	1.54
1.7	7.63	2.56	2.14	1.57
1.8	7.95	2.64	2.20	1.61
1.9	8.26	2.71	2.27	1.64
2.0	8.55	2.78	2.33	1.68

6. Receiving Water Compliance Determination

Per Implementation Provision No. 1, the following methods for determining compliance with proposed objectives shall be used:

If salinity sampled at a particular receiving water station indicates saline conditions (equal to or greater than 10 ppt), then saltwater objectives shall apply.

If salinity sampled at a particular receiving water station indicates freshwater conditions (equal to or less than 1 ppt), then freshwater objectives shall apply.

If salinity sampled at a particular receiving water station indicates brackish conditions (greater than 1 but less than 10 ppt), then the more stringent of the freshwater or saltwater objectives shall apply except where the Regional Board, by adoption of a resolution, approves the use of either freshwater or saltwater objectives per Implementation Provision 1(3)(a).

Resolution No. R13-0XX

In “Chapter 3: Water Quality Objectives” of the Basin Plan, under the section “Regional Objectives for Inland Surface Waters”, replace paragraph 2 under “Bacteria, Coliform” on page 3-3 with the following language as directed in attachments to Regional Board Resolution Nos. R01-0018, R02-022, and R10-005, and State Board Resolution No. 2005-0015.

In Marine Waters Designated for Water Contact Recreation (REC-1)

1. Geometric Mean Limits

- a. *Total coliform density shall not exceed 1,000/100 ml.*
- b. *Fecal coliform density shall not exceed 200/100 ml.*
- c. *Enterococcus density shall not exceed 35/100 ml.*

2. Single Sample Limits

- a. *Total coliform density shall not exceed 10,000/100 ml.*
- b. *Fecal coliform density shall not exceed 400/100 ml.*
- c. *Enterococcus density shall not exceed 104/100 ml.*
- d. *Total coliform density shall not exceed 1,000/100 ml, if the ratio of fecal-to-total coliform exceeds 0.1.*

In Fresh Waters Designated for Water Contact Recreation (REC-1)

1. Geometric Mean Limits

- a. *E. coli density shall not exceed 126/100 ml.*

2. Single Sample Limits

- a. *E. coli density shall not exceed 235/100 ml.*

In Fresh Waters Designated for Limited Water Contact Recreation (LREC-1)

1. Geometric Mean Limits

- a. *E. coli density shall not exceed 126/100 ml.*

2. Single Sample Limits

- a. *E. coli density shall not exceed 576/100 ml.*

The single sample limit for *E. coli* is based on EPA's determination of the most appropriate single sample maximum density for water bodies infrequently used for full-body contact recreation.⁹

Implementation Provisions for Water Contact Recreation Bacteria Objectives

The geometric mean values should be calculated based on a statistically sufficient number of samples (generally not less than 5 samples equally spaced over a 30-day period).

⁹ U.S. EPA. 1986. Ambient Water Quality Criteria for Bacteria – 1986. Report No. EPA 330/5-84-002. January 1986.

Resolution No. R13-0XX

If any of the single sample limits are exceeded, the Regional Board may require repeat sampling on a daily basis until the sample falls below the single sample limit in order to determine the persistence of the exceedance.

When repeat sampling is required because of an exceedance of any one single sample limit, values from all samples collected during that 30-day period shall be used to calculate the geometric mean.

The single sample bacteriological objectives shall be strictly applied except when provided for in a Total Maximum Daily Load (TMDL). In all circumstances, including in the context of a TMDL, the geometric mean objectives shall be strictly applied. In the context of a TMDL, the Regional Board may implement the single sample objectives in fresh and marine waters by using a 'reference system/antidegradation approach' or 'natural sources exclusion approach' as discussed below. A reference system is defined as an area and associated monitoring point that is not impacted by human activities that potentially affect bacteria densities in the receiving water body.

These approaches recognize that there are natural sources of bacteria, which may cause or contribute to exceedances of the single sample objectives for bacterial indicators. They also acknowledge that it is not the intent of the Regional Board to require treatment or diversion of natural water bodies or to require treatment of natural sources of bacteria from undeveloped areas. Such requirements, if imposed by the Regional Board, could adversely affect valuable aquatic life and wildlife beneficial uses supported by natural water bodies in the Region.

Under the reference system/antidegradation implementation procedure, a certain frequency of exceedance of the single sample objectives above shall be permitted on the basis of the observed exceedance frequency in the selected reference system or the targeted water body, whichever is less. The reference system/anti-degradation approach ensures that bacteriological water quality is at least as good as that of a reference system and that no degradation of existing bacteriological water quality is permitted where existing bacteriological water quality is better than that of the selected reference system.

Under the natural sources exclusion implementation procedure, after all anthropogenic sources of bacteria have been controlled such that they do not cause or contribute to an exceedance of the single sample objectives and natural sources have been identified and quantified, a certain frequency of exceedance of the single sample objectives shall be permitted based on the residual exceedance frequency in the specific water body. The residual exceedance frequency shall define the background level of exceedance due to natural sources. The 'natural sources exclusion' approach may be used if an appropriate reference system cannot be identified due to unique characteristics of the target water body. These approaches are consistent with the State Antidegradation Policy (State Board Resolution No. 68-16) and with federal antidegradation requirements (40 CFR 131.12).

The appropriateness of these approaches and the specific exceedance frequencies to be permitted under each will be evaluated within the context of TMDL development for a specific water body, at which time the Regional Board may select one of these approaches, if appropriate.

Resolution No. R13-0XX

These implementation procedures may only be implemented within the context of a TMDL addressing municipal storm water (i.e. MS4), including the MS4 municipal storm water requirements of the Statewide Permit for Storm Water Discharges from the State of California Department of Transportation (Caltrans), and non-point sources discharges. These implementation provisions do not apply to NPDES discharges other than MS4 discharges¹⁰

In “Chapter 3: Water Quality Objectives” of the Basin Plan, under the section “Regional Objectives for Inland Surface Waters”, modify the language in paragraph 3 under “Chemical Constituents” on page 3-8 as indicated by underline and ~~strike through~~ text to reflect changes to provisions of Title 22 of the California Code of Regulations, which are incorporated by reference into the Basin Plan.

Water designated for use as Domestic or Municipal Supply (MUN) shall not contain concentrations of chemical constituents in excess of the limits specified in the following provisions of Title 22 of the California Code of Regulations which are incorporated by reference into this plan: Table 64431-A of Section 64431 (Inorganic Chemicals), ~~Table 64431-B of Section 64431 (Fluoride)~~, and Table 64444-A of Section 64444 (Organic Chemicals). This incorporation by reference is prospective including future changes to the incorporated provisions as the changes take effect. (See Tables 3-8 and 3-9 ~~3-5, 3-6, and 3-7~~)

In “Chapter 3: Water Quality Objectives” of the Basin Plan, under the section “Regional Objectives for Inland Surface Waters,” replace Tables 3-5 and 3-7 under “Chemical Constituents” on pages 3-8 and 3-10, respectively, with updated versions to reflect the current maximum contaminant levels in Title 22 of the California Code of Regulations that became effective since the last Basin Plan update in 1994. Table 3-5 and 3-7 in the 1994 Basin Plan will be renumbered to Tables 3-8 and 3-9, respectively, as a result of the additional table for the new ammonia objectives. Table 3-6 in the 1994 Basin Plan on page 3-9 will be deleted as the fluoride objective(s) has been incorporated into the updated Table 3-8.

Table 3-8. The Maximum Contaminant Levels: Inorganic Chemicals (for MUN beneficial use) specified in Table 64431-A of Section 64431 of Title 22 of the California Code of Regulations as of February 2013

Constituent	Maximum Contaminant Level (mg/L)
Aluminum	1
Antimony	0.006
Antimony	--

¹⁰ *Municipal storm water discharges in the Los Angeles Region are those with permits under the Municipal Separate Sewer System (MS4) NPDES Program. For example, the MS4 permits at the time of this amendment are the Los Angeles County Municipal Storm Water NPDES Permit, Ventura County Municipal Storm Water NPDES Permit, City of Long Beach Municipal Storm Water NPDES Permit, and elements of the statewide storm water permit for the California Department of Transportation (Caltrans).*

Resolution No. R13-0XX

Constituent	Maximum Contaminant Level (mg/L)
Arsenic	0.010
Asbestos	7 MFL
Barium	1 ₂
Beryllium	0.004
Cadmium	0.005
Chromium	0.05
Cyanide	0.15
Fluoride	2 ₀
Mercury	0.002
Nickel	0.1
Nitrate (as NO ₃)	45 ₂
Nitrate + Nitrite (sum as nitrogen)	10 ₂
Nitrite (as Nitrogen <u>nitrogen</u>)	1 ₂
Perchlorate	0.006
Selenium	0.05
Thallium	0.002

(MFL = million fibers per liter; MCL for fibers >10 microns long)

Table 3-9. The Maximum Contaminant Levels: Organic Chemicals (for MUN beneficial use) specified in Table 64444-A of Section 64444 of Title 22 of the California Code of Regulations as of February 2013

Constituent	Maximum Contaminant Level (mg/L)
(a) Volatile Organic Chemicals (VOCs)	
Benzene	0.001
Carbon Tetrachloride	0.0005
1,2-Dichlorobenzene	0.6
1,4-Dichlorobenzene	0.005
1,1-Dichloroethane	0.005
1,2-Dichloroethane	0.0005
1,1-Dichloroethylene	0.006
cis-1,2-Dichloroethylene	0.006
trans-1,2-Dichloroethylene	0.01
Dichloromethane	0.005
1,2-Dichloropropane	0.005
1,3-Dichloropropene	0.0005
Ethylbenzene	0.3
Methyl-tert-butyl ether	0.013
Monochlorobenzene	0.07
Styrene	0.1
1,1,2,2-Tetrachloroethane	0.001
Tetrachloroethylene	0.005
Toluene	0.15
1,2,4-Trichlorobenzene	0.005
1,1,1-Trichloroethane	0.200
1,1,2-Trichloroethane	0.005
Trichloroethylene	0.005
Trichlorofluoromethane	0.15

Resolution No. R13-0XX

Constituent	Maximum Contaminant Level (mg/L)
1,1,2-Trichloro-1,2,2-Trifluoroethane	1.2
Vinyl Chloride	0.0005
Xylenes	1.750*
(b) Non-Volatile Synthetic Organic Chemicals (SOCs)	
Alachlor	0.002
Atrazine	0.001
Bentazon	0.018
Benzo(a)pyrene	0.0002
Carbofuran	0.018
Chlordane	0.0001
2,4-D	0.07
Dalapon	0.2
Dibromochloropropane	0.0002
Di(2-ethylhexyl)adipate	0.4
Di(2-ethylhexyl)phthalate	0.004
Dinoseb	0.007
Diquat	0.02
Endothall	0.1
Endrin	0.002
Ethylene Dibromide	0.00005
Glyphosate	0.7
Heptachlor	0.00001
Heptachlor Epoxide	0.00001
Hexachlorobenzene	0.001
Hexachlorocyclopentadiene	0.05
Lindane	0.0002
Methoxychlor	0.03
Molinate	0.02
Oxamyl	0.05
Pentachlorophenol	0.001
Picloram	0.5
Polychlorinated Biphenyls	0.0005
Simazine	0.004
Thiobencarb	0.07
Toxaphene	0.003
2,3,7,8-TCDD (Dioxin)	3x10 ⁻⁸
2,4,5-TP (Silvex)	0.05

*MCL is for either a single isomer or the sum of the isomers.

In “Chapter 3: Water Quality Objectives” of the Basin Plan, under the section “Regional Objectives for Inland Surface Waters”, modify the language in paragraph 3 under “Radioactive Substances” on page 3-15 as indicated by underline and strikethrough text to reflect changes to provisions of Title 22 of the California Code of Regulations, which are incorporated by reference into the Basin Plan.

Waters designated for use as domestic or municipal supply (MUN) shall not contain concentrations of radionuclides in excess of the limits specified in Table ~~46442~~ of Section ~~64443 (Radioactivity)~~ ~~64442 (Gross Alpha Particle Activity, Radium-226,~~

Resolution No. R13-0XX

Radium-228, and Uranium)) and Table 64443 of Section 64443 (Beta Particle and Photon Radioactivity) of Title 22 of the California Code of Regulations which is incorporated by reference into this plan. This incorporation by reference is prospective including future changes to the incorporated provisions as the changes take effect. (See Table 3-12a and 3-12b.)

In “Chapter 3: Water Quality Objectives” of the Basin Plan, under the section “Regional Objectives for Inland Surface Waters,” replace Table 3-9 under “Radioactive Substances” with Tables 3-12a and 3-12b to reflect the current maximum contaminant levels in Title 22 of the California Code of Regulations that became effective since the last Basin Plan update in 1994.

Table: 3-12a. The Maximum Contaminant Levels (MCLs) and Detection Levels for Purposes of Reporting (DLRs): Gross Alpha Particle Activity, Radium-226, Radium-228, and Uranium (for MUN beneficial use) specified in Table 64442 of Section 64442 of Title 22 of the California Code of Regulations as of February 2013

Radionuclide	MCL (pCi/L)	DLR (pCi/L)
Radium-226 Radium-228	5 (combined radium-226 & -228)	1 1
Gross Alpha particle activity (excluding radon and uranium)	15	3
Uranium	20	1

Table: 3-12b. The Maximum Contaminant Levels (MCLs) and Detection Levels for Purposes of Reporting (DLRs): Beta particles and Photon Radioactivity (for MUN beneficial use) specified in Table 64443 of Section 64443 of Title 22 of the California Code of Regulations as of February 2013

Radionuclide	MCL	DLR (pCi/L)
Beta/photon emitters	4 millirem/year annual dose equivalent to the total body or any internal organ	Gross Beta particle activity: 4pCi/L
Strontium - 90	8 pCi/L (= 4 millirem/yr dose to bone marrow)	2 pCi/L
Tritium	20,000 pCi/L (= 4 millirem/yr dose to total body)	1,000 pCi/L

In “Chapter 3: Water Quality Objectives” of the Basin Plan, under the section “Regional Objectives for Inland Surface Waters”, add the following language after the second paragraph under “Floating Material” on page 3-9 referencing specific guidelines for the trash TMDLs, as directed in Regional Board Resolution Nos. R99-015, R01-014, R07-012.

See additional regulatory guidelines described under the San Gabriel River (East Fork) Trash Total Maximum Daily Load (Chapter 7).

Resolution No. R13-0XX

See additional regulatory guidelines described under the Los Angeles River Trash Total Maximum Daily Load (Chapter 7).

See additional regulatory guidelines described under the Ballona Creek) Trash Total Maximum Daily Load (Chapter 7).

In “Chapter 3: Water Quality Objectives” of the Basin Plan, under the section “Regional Objectives for Inland Surface Waters”, add the following language after the last paragraph under “Mineral Quality” on page 3-11 to reflect the intent of attachments to Regional Board Resolution No. R97-002.

In the late 1980s, many dischargers started to experience compliance problems with chloride limits largely due to chloride levels in supply waters imported into the Region. In order to provide a long-term solution to chloride compliance problems while continuing to protect beneficial uses, the Regional Board adopted Resolution No. 97-002: Policy for Addressing Levels of Chloride in Discharges of Wastewater (Chapter 5). This Chloride Policy revised water quality objectives in selected surface waters based upon chloride levels in supply waters imported into the Region plus a loading factor. The policy also set forth measures to address salinity loading throughout the Region.

Due to concerns expressed about the potential for future adverse impacts to agricultural resources in Ventura County, water quality objectives for chloride in the Santa Clara River and Calleguas Creek watersheds were not revised under the Chloride Policy in 1997. However, the Regional Board granted variances (interim relief) from surface water chloride limits in NPDES permits that are based on existing water quality objectives in the Santa Clara River and Calleguas Creek watersheds. These variances expired in January 2001 and are no longer applicable.

In “Chapter 3: Water Quality Objectives” of the Basin Plan, in Table 3-8 “Water Quality Objectives for Selected Constituents in Inland Surface Waters” starting on page 3-12, modify the following watershed/stream reaches and corresponding mineral objectives (as indicated by ~~strike through~~ and underline font) as directed in attachment to Regional Board Resolution No. R97-002. Table 3-8 in the 1994 Basin Plan will be renumbered to Tables 3-10, as a result of preceding revisions.

WATERSHED/STREAM REACH	TDS (mg/L)	Sulfate (mg/L)	Chloride (mg/L)	Boron ^c (mg/L)	Nitrogen ^d (mg/L)	SAR ^e (mg/L)
Calleguas Creek Watershed:						
Above Potrero Road <u>Arroyo Simi and tributaries-upstream Madera Road</u>	850	250	150	1.0	10	f
<u>Arroyo Simi-downstream Madera Road, Arroyo Las Posas, and tributaries</u>	<u>850</u>	<u>250</u>	<u>150</u>	<u>1.0</u>	<u>10</u>	f

WATERSHED/STREAM REACH	TDS (mg/L)	Sulfate (mg/L)	Chloride (mg/L)	Boron ^c (mg/L)	Nitrogen ^d (mg/L)	SAR ^e (mg/L)
<u>Calleguas Creek and tributaries-between Potrero Road and Arroyo Las Posas. Includes Conejo Creek, Arroyo Conejo, and Arroyo Santa Rosa</u>	850	250	150	1.0	10	f
Los Angeles River Watershed:						
<u>Above Figueroa Street Los Angeles River and tributaries-upstream Sepulveda Flood Control Basin</u>	950	300	150	g	8	g
Los Angeles River-between Sepulveda Flood Control Basin and Figueroa Street. Includes Burbank Western Channel only	950	300 350	190 150	g	8	g
<u>Rio Hondo above Santa Ana Freeway Other tributaries to Los Angeles River-between Sepulveda Flood Control Basin and Figueroa Street</u>	950	300	150	g	8	g
<u>Santa Anita Creek above Santa Anita spreading grounds Los Angeles River-between Figueroa Street and Los Angeles River Estuary (Willow Street). Includes Rio Hondo below Santa Ana Freeway only.</u>	1500	350	190 150	g	8	g
<u>Eaton Canyon Creek above Eaton Dam Other tributaries to Los Angeles River-between Figueroa Street and Los Angeles river Estuary. Includes Arroyo Seco downstream spreading grounds.</u>	1500	350	150	g	8	g
<u>Arroyo Seco above spreading grounds Rio Hondo-between Whittier Narrows Flood Control Basin and Santa Ana Freeway</u>	750	300	180 150	g	8	g
<u>Big Tujunga Creek above Hansen Dam Rio Hondo-upstream Whittier Narrows Flood Control Basin</u>	750	300	150	g	8	g
<u>Pacoima Wash above Pacoima spreading grounds Santa Anita Creek above Santa Anita spreading grounds</u>	250	30	10	g	f	g

Resolution No. R13-0XX

WATERSHED/STREAM REACH	TDS (mg/L)	Sulfate (mg/L)	Chloride (mg/L)	Boron ^c (mg/L)	Nitrogen ^d (mg/L)	SAR ^e (mg/L)
San Gabriel River Watershed:						
<u>San Gabriel River-Above Morris Dam</u>	250	30	10	0.6	2	2
<u>San Gabriel River-Between Morris Dam and Ramona Blvd.</u>	450	100	100	0.5	8	g
<u>San Gabriel River and tributaries-between Ramona Blvd. and Valley Blvd</u>	750	300	150	1.0	8	g
<u>San Gabriel River-between Valley Blvd and Firestone Blvd. Includes Whitter Narrows Flood Control Basin, and San Jose Creek-downstream 71 Freeway only.</u>	<u>750</u>	<u>300</u>	<u>180-150</u>	<u>1.0</u>	<u>8</u>	<u>g</u>
<u>San Jose Creek and tributaries-upstream 71 Freeway.</u>	<u>750</u>	<u>300</u>	<u>150</u>	<u>1.0</u>	<u>8</u>	<u>g</u>
<u>San Gabriel River-Between Firestone Blvd. and San Gabriel River Estuary (downstream from Willow Street) Includes Coyote Creek.</u>	<i>no waterbody specific objectives^f</i>					

In “Chapter 3: Water Quality Objectives” of the Basin Plan, in Table 3-8 “Water Quality Objectives for Selected Constituents in Inland Surface Waters” on page 3-12, replace the 80 mg/L chloride objectives for the area identified as “Between A street, Filmore and Freeman Diversion ‘Dam’ near Saticoy” in the Santa Clara River Watershed with a 100 mg/L chloride objective (see table below) as directed in attachment to Regional Board Resolution No. R03-015. Table 3-8 in the 1994 Basin Plan will be renumbered to Table 3-10, as a result of preceding revisions.

WATERSHED/STREAM REACH	Chloride (mg/L)
Between A street, Filmore and Freeman Diversion “Dam” near Saticoy	80 <u>100</u>

In “Chapter 3: Water Quality Objectives” of the Basin Plan, under the section “Regional Objectives for Inland Surface Waters”, under the subsection titled “Mineral Quality, add

the following table after Table 3-10 (formerly Table 3-8 in the 1994 Basin Plan), as directed in attachments to Regional Board Resolution No. R08-012.

Table 3-10a. Conditional Site Specific Objectives for Santa Clara River Surface Waters

WATERSHED/STREAM REACH	Chloride (mg/L)
Santa Clara River Watershed:	
Between Bouquet Canyon Road Bridge and West Pier Highway 99	150 (12-month average)
Between West Pier Highway 99 and Blue Cut gaging station	150 (12-month average)
Between Blue Cut gaging station and confluence of Piru Creek	117/130 ^a (3-month average) ^b

- a. The conditional site specific objective of 130 mg/L applies only if the following conditions and implementation requirements are met:
 1. Water supply chloride concentrations measured in Castaic Lake are ≥ 80 mg/L.
 2. The Santa Clarita Valley Sanitation District (SCVSD) shall provide supplemental water to salt-sensitive agricultural uses that are irrigated with surface water during periods when Reach 4B (between Blue Cut gaging station and confluence of Piru Creek) surface water exceeds 117 mg/L.
 3. By May 4, 2020, the 10-year cumulative net chloride loading above 117 mg/L ($CNCl_{117}$)ⁱ to Reach 4B of the Santa Clara River (SCR), calculated annually, from the SCVSD Water Reclamation Plants (WRPs) shall be zero or less.

$$^i CNCl_{117} = Cl_{(Above\ 117)} - Cl_{(Below\ 117)} - Cl_{(Export\ Ews)}$$

Where:

$$Cl_{(Above\ 117)} = [WRP\ CI\ Load^1 / Reach\ 4B\ CI\ Load^2] * [Reach\ 4B\ CI\ Load_{>117}^3]$$

$$Cl_{(Below\ 117)} = [WRP\ CI\ Load^1 / Reach\ 4B\ CI\ Load^2] * [Reach\ 4B\ CI\ Load_{\leq 117}^4]$$

$$Cl_{(Export\ EWs)} = CI\ Load\ Removed\ by\ Extraction\ Wells$$

¹ WRP CI Load is determined as the monthly average chloride (Cl) concentration multiplied by the monthly average flow measured at the Valencia WRP.

² Reach 4B CI Load is determined as the monthly average Cl concentration at SCVSD Receiving Water Station RF multiplied by the monthly average flow measured at USGS Gauging Station 11109000 (Las Brisas Bridge).

³ Reach 4B CI Load_{>117} means the calculated Cl load to Reach 4B when monthly average Cl concentration in Reach 4B is above 117 mg/L.

⁴ Reach 4B CI Load_{≤117} means the calculated Cl load to Reach 4B when monthly average Cl concentration in Reach 4B is below or equal to 117 mg/L.

4. The chief engineer of the SCVSD signs under penalty of perjury and submits to the Regional Board a letter documenting the fulfillment of conditions 1, 2, and 3.

- b. The averaging period for the critical condition SSO of 130 mg/L may be reconsidered based on results of chloride trend monitoring after the alternative water resources management (AWRM) system is applied.

The conditional site specific objectives for chloride in the surface water between Bouquet Canyon Road bridge and West Pier Highway 99, between West Pier Highway 99 and

Resolution No. R13-0XX

Blue Cut gaging station, and between Blue Cut gaging station and confluence of Piru Creek shall apply and supersede the existing water quality objectives in Table 3-8 only when chloride load reductions and/or chloride export projects are in operation by the SCVSD according to the implementation section in Table 7-6.1 of Chapter 7.

In “Chapter 3: Water Quality Objectives” of the Basin Plan, under the section “Regional Objectives for Inland Surface Waters”, add another subsection titled “Priority Pollutants” between “Polychlorinated Biphenyls (PCBs)” and “Radioactive Substances” on page 3-15 with the following language and new Table 3-11, as directed in attachments to Regional Board Resolution No. R06-022.

Priority Pollutants

The California Toxics Rule (CTR), located at 40 CFR § 131.38, contains federally promulgated water quality criteria applicable to California waters for 126 priority pollutants for the protection of aquatic life and human health.

Implementation Provisions

The water quality criteria for metals contained in the CTR are expressed as a function of a water-effect ratio (WER).¹¹ In the CTR, the US EPA has provided for the adjustment of these water quality criteria through the application by States of the WER procedure. The WER has a default value of 1.0 unless a site-specific WER is approved by the Regional Board. To use a WER other than the default of 1.0, a study must be conducted, establishing the ratio that represents the difference between toxicity in laboratory test water and toxicity in a specific water body based on ambient conditions. The study must be consistent with US EPA procedures on deriving WERs.

Notwithstanding the provisions below, regulatory actions to achieve applicable criteria, as modified by site-specific WERs, must ensure that downstream standards will also be achieved.

Additional receiving water monitoring shall be required of dischargers subject to site-specific WER(s) to evaluate whether criteria, as modified by the WER(s), are as protective of beneficial uses as the CTR criteria are intended to be. If additional monitoring indicates a change in the chemical characteristics of the water body or toxicity, the Regional Board may reconsider the site-specific WER(s).

Copper

For the following water bodies, the copper water quality criteria contained in the CTR shall be modified using the site-specific WERs set forth below.

Table 3-11 Site-specific Water-Effect Ratios for Copper

¹¹ There are two exceptions where the criteria are not a function of a WER. The freshwater criteria for selenium are not a function of a WER. The freshwater and saltwater criteria for mercury are not a function of a WER.

Resolution No. R13-0XX

Waterbody Name	Reach Name	Description of Reach/Area	Water-Effect Ratio
Mugu Lagoon	Reach 1	Lagoon fed by Calleguas Creek	1.51
Lower Calleguas Creek	Reach 2	Downstream (south) of Potrero Road to the lagoon	3.69

In “Chapter 3: Water Quality Objectives” of the Basin Plan, under the section “Regional Objectives for Inland Surface Waters”, and subsection titled “Solid, Suspended, or Settleable Materials,” add the following language after the second paragraph referencing specific guidelines for trash TMDLs as directed in Regional Board Resolution Nos. R01-14 and R07-012.

See additional regulatory guidelines described under the Los Angeles River Trash Total Maximum Daily Load (Chapter 7).

See additional regulatory guidelines described under the Ballona Creek Trash Total Maximum Daily Load (Chapter 7).

In “Chapter 3: Water Quality Objectives” of the Basin Plan, under the section “Regional Objectives for Ground Waters”, modify the language in the second paragraph under “Chemical Constituents and Radioactivity” (on page 3-18) as indicated in underline and strikethrough text to reflect changes to provisions of Title 22 of the California Code of Regulations, which are incorporated by reference into the Basin Plan:

Ground waters designated for use as domestic or municipal supply (MUN) shall not contain concentrations of chemical constituents and radionuclides in excess of the limits specified in the following provisions of Title 22 of the California Code of Regulations which are incorporated by reference into this plan: Table 64431-A of section 64431 (Inorganic chemicals), ~~Table 64431-B of Section 64431 (Fluoride)~~, Table 64444-A of Section 64444 (Organic Chemicals), and Table 4 of Section 64443 (Radioactivity). This incorporation by reference is prospective including future changes to the incorporated provisions as the changes take effect. (See Tables ~~3-8, 3-9, 3-12a, and 3-12b~~ ~~3-5, 3-6, 3-7 and 3-9.~~)

In “Chapter 3: Water Quality Objectives” of the Basin Plan, under the section “Regional Objectives for Ground Waters”, add the following language after the second paragraph under “Mineral Quality” (on page 3-18), as directed in attachment to Regional Board Resolution No. R06-003.

Coastal Aquifer Variance Provision for Mineral Quality Objectives

In coastal aquifers where elevated concentrations of minerals are caused by natural sources due to an aquifer’s proximity to the ocean, the Regional Board may grant a variance from implementing the mineral quality objectives specified in Table 3-13 when issuing waste discharge requirements (WDRs) or enforcement orders. Any variance

Resolution No. R13-0XX

granted pursuant to this variance provision shall be for no more than five years, and may be extended not more than once for an additional period of up to five years. Any further relief should be in the form of a Basin Plan amendment. A decision to issue or to extend a variance will be based upon the Regional Board's evaluation of the evidence submitted concerning the granting of the variance.

A discharger must submit to the Executive Officer a written request for a variance from compliance with the mineral quality objectives for groundwater. The request must include recent data and analysis that provide clear and convincing evidence that elevated mineral concentrations are natural in origin and result from the aquifer's proximity to the ocean. The discharger's request must include clear and convincing evidence and analysis that:

1. The aquifer's proximity to the ocean leads to one or more of the following:
 - a) seawater intrusion;
 - b) the presence of marine sediments high in mineral content;
 - c) tidal fluctuations that regularly influence the chemistry of the aquifer.
2. The source of the elevated mineral concentrations is natural and not induced by current or past discharge of pollutants.
3. A discharge of minerals in excess of the mineral quality objectives in the coastal aquifer will not degrade adjacent, inland aquifers.
4. The discharger has not caused or significantly contributed to the elevated Mineral concentrations from which it seeks relief.

The Regional Board may only grant a variance after a duly noticed public meeting. The Regional Board's decision to grant or to deny a variance shall be based on the record, including the discharger's request, the circumstances leading to the elevated mineral concentrations at the site, and the comments of staff and interested persons. The Regional Board may only grant a variance upon the Regional Board's determination that the request satisfies the conditions specified above and that the variance is in the public interest. In granting a variance, the Regional Board must include appropriate requirements in the WDRs or enforcement order consistent with the State Water Resources Control Board's anti-degradation resolution (SWRCB Res. No. 68-16) and other applicable water quality standards as stipulated in regional and statewide water quality control plans.

In "Chapter 3: Water Quality Objectives" of the Basin Plan, under the section "Regional Objectives for Ground Waters", update the corresponding Table 3-13 (formerly Table 3-10 on pages 3-19, 3-20, and 3-21), to include a footnote "m" in the objectives column with the following language, as directed in attachment to Regional Board Resolution No. R06-003.

DWR Basin No. ^b	BASIN	OBJECTIVES (mg/L) ^m
----------------------------------	-------	--------------------------------

^m The Regional Board may grant, at its sole discretion, individual dischargers a variance from the numeric mineral quality objectives for groundwater specified in Table 3-13 under the conditions and procedures specified in "Coastal Aquifer Variance Provision for Mineral Quality Objectives" set forth in the Regional Objectives for Ground Waters.

Resolution No. R13-0XX

In “Chapter 3: Water Quality Objectives” of the Basin Plan, update Table 3-10 (on pages 3-19, 3-20, and 3-21), to reflect the updated groundwater basins and basin numbers, which were included in the attachment to Regional Board Resolution No. R11-011. Table 3-10 will be renumbered to Table 3-13 as a result of preceding changes.

Table 3-13: Water Quality Objectives for Selected Constituents in Regional Ground Waters^a

BASINS			Objectives (mg/l) ^m				
Basin	Basin No ^b	1994 Basin Name	1994 Basin No	TDS	Sulfate	Chloride	Boron
Pitas Point Area^c		Pitas Point Area		None specified			
Upper Ojai Valley	4-1	Ojai Valley	4-1				
Upper Ojai Valley	4-1	Upper Ojai Valley	4-1				
Upper Ojai Valley	4-1	West of Sulfur Mountain Road	4-1	1000	300	200	1.0
Upper Ojai Valley	4-1	Central Area	4-1	700	50	100	1.0
Upper Ojai Valley	4-1	Sisar Area	4-1	700	250	100	0.5
Ojai Valley	4-2	Lower Ojai Valley	4-2				0.5
Ojai Valley	4-2	West of San Antonio-Senior Canyon	4-2	1000	300	200	0.5
Ojai Valley	4-2	East of San Antonio-Senior Canyon	4-2	700	200	50	
Ventura River Valley	4-3	Ventura River Valley	4-3				
Upper Ventura River	4-3.01	Upper Ventura	4-3	800	300	100	0.5
Upper Ventura River	4-3.01	San Antonio Creek Area	4-3	1000	300	100	1.0
Lower Ventura River	4-3.02	Lower Ventura	4-3	1500	500	30	1.5
Santa Clara River Valley^d	4-4	Ventura Central	4-4				
Piru	4-4.06	Santa Clara-Piru Creek Area	4-4				
Piru	4-4.06	Upper Area (above Lake Piru)	4-4	1100	400	200	2.0
Piru	4-4.06	Lower Area East of Piru Creek	4-4	2500	1200	200	1.5
Piru	4-4.06	Lower Area West of Piru Creek	4-4	1200	600	100	1.5
Fillmore	4-4.05	Santa Clara-Sespe Creek Area	4-4				
Fillmore	4-4.05	Topa Topa (upper Sespe) Area	4-4	900	350	30	2.0
Fillmore	4-4.05	Fillmore Area	4-4				

BASINS			Objectives (mg/l) ^m				
Basin	Basin No ^b	1994 Basin Name	1994 Basin No	TDS	Sulfate	Chloride	Boron
Fillmore	4-4.05	Pole Creek Fan Area	4-4	2000	800	100	1.0
Fillmore	4-4.05	South Side of Santa Clara River	4-4	1500	800	100	1.1
Fillmore	4-4.05	Remaining Fillmore Area	4-4	1000	400	50	0.7
Santa Paula	4-4.04	Santa Clara-Santa Paula Area	4-4				
Santa Paula	4-4.04	East of Peck Road	4-4	1200	600	100	1.0
Santa Paula	4-4.04	West of Peck Road	4-4	2000	800	110	1.0
Oxnard	4-4.02	Oxnard Plain	4-4				
Mound	4-4.03	Oxnard Plain	4-4				
Oxnard	4-4.02	Oxnard Forebay	4-4	1200	600	150	1.0
Oxnard	4-4.02	Confined Aquifers	4-4	1200	600	150	1.0
Oxnard	4-4.02	Unconfined & Perched Aquifers	4-4	3000	1000	500	
Pleasant Valley^e	4-6	Pleasant Valley	4-6				
Pleasant Valley	4-6	Confined Aquifers	4-6	700	300	150	1.0
Pleasant Valley	4-6	Unconfined & Perched Aquifers	4-6				
Arroyo Santa Rosa Valley^e	4-7	Arroyo Santa Rosa	4-7	900	300	150	1.0
Las Posas Valley^e	4-8	Las Posas Valley	4-8				
Las Posas Valley	4-8	South Las Posas Area	4-8				
Las Posas Valley	4-8	NW of Grimes Cyn Rd. & LA Ave. & Somis Rd.	4-8	700	300	100	0.5
Las Posas Valley	4-8	E of Grimes Cyn Rd & Hitch Blvd.	4-8	2500	1200	400	3.0
Las Posas Valley	4-8	S of LA Ave Between Somis Rd & Hitch Blvd.	4-8	1500	700	250	1.0
Las Posas Valley	4-8	Grimes Canyon Rd. &	4-8	250	30	30	0.2

BASINS			Objectives (mg/l) ^m				
Basin	Basin No ^b	1994 Basin Name	1994 Basin No	TDS	Sulfate	Chloride	Boron
		Broadway Area					
Las Posas Valley	4-8	North Las Posas Area	4-8	500	250	150	1.0
Acton Valley^f	4-5	Upper Santa Clara	4-5				
Acton Valley	4-5	Acton Valley	4-5	550	150	100	1.0
Acton Valley	4-5	Sierra Pelona Valley (Agua Dulce)	4-5	600	100	100	0.5
Acton Valley	4-5	Upper Mint Canyon	4-5	700	150	100	0.5
Acton Valley	4-5	Upper Bouquet Canyon	4-5	400	50	30	0.5
Acton Valley	4-5	Green Valley	4-5	400	50	25	
Acton Valley	4-5	Lake Elizabeth-Lake Hughes Area	4-5	500	100	50	0.5
Santa Clara River Valley East	4-4.07	Eastern Santa Clara	4-4.07				
Santa Clara River Valley East	4-4.07	Santa Clara-Mint Canyon	4-4.07	800	150	150	1.0
Santa Clara River Valley East	4-4.07	South Fork	4-4.07	700	200	100	0.5
Santa Clara River Valley East	4-4.07	Placentia Canyon	4-4.07	700	150	100	0.5
Santa Clara River Valley East	4-4.07	Santa Clara-Bouquet & San Fransisquito Canyons	4-4.07	700	250	100	1.0
Santa Clara River Valley East	4-4.07	Castaic Valley	4-4.07	1000	350	150	1.0
Santa Clara River Valley East	4-4.07	Saugus Aquifer	4-4.07				
Simi Valley	4-9	Simi Valley	4-9				
Simi Valley	4-9	Simi Valley Basin	4-9				
Simi Valley	4-10	Confined Aquifers	4-9	1200	600	150	1.0
Simi Valley	4-11	Unconfined & Perched Aquifers	4-9				

BASINS			Objectives (mg/l) ^m				
Basin	Basin No ^b	1994 Basin Name	1994 Basin No	TDS	Sulfate	Chloride	Boron
Simi Valley	4-12	Gillibrand Basin	4-9	900	350	50	1.0
Conejo Valley	4-10	Conejo Valley	4-10	800	250	150	1.0
Coastal Plain of Los Angeles	4-11	Los Angeles Coastal Plain	4-11				
Central	4-11.04	Central Basin	4-11	700	250	150	1.0
West Coast	4-11.03	West Coast Basin	4-11	800	250	250	1.5
Hollywood	4-11.02	Hollywood Basin	4-11	750	100	100	1.0
Santa Monica	4-11.01	Santa Monica Basin	4-11	1000	250	200	0.5
San Fernando Valley	4-12	San Fernando Valley	4-12				
San Fernando Valley	4-12	Sylmar Basin	4-12	600	150	100	0.5
San Fernando Valley	4-12	Verdugo Basin	4-12	600	150	100	0.5
San Fernando Valley	4-12	San Fernando Basin	4-12				
San Fernando Valley	4-12	West of Highway 405	4-12	800	300	100	1.5
San Fernando Valley	4-12	East of Highway 405 (overall)	4-12	700	300	100	1.5
San Fernando Valley	4-12	Sunland-Tujunga Area	4-12	400	50	50	0.5
San Fernando Valley	4-12	Foothill Area	4-12	400	100	50	1.0
San Fernando Valley	4-12	Area Encompassing RT-Tujunga -Erwin-N. Hollywood-Whithall-LA/Verdugo-Crystal Springs-Headworks-Glendale/Burbank Well Fields	4-12	600	250	100	1.5
San Fernando Valley	4-12	Narrows Area (below confluence of Verdugo Wash with the LA River	4-12	900	300	150	1.5
San Fernando Valley	4-12	Eagle Rock Basin	4-12	800	150	100	0.5
San Gabriel Valley^h/Raymond^h/San Fernando Valley	4-13	San Gabriel Valley	4-13				

BASINS			Objectives (mg/l) ^m				
Basin	Basin No ^b	1994 Basin Name	1994 Basin No	TDS	Sulfate	Chloride	Boron
Raymond	4-23	Raymond Basin	4-13				
San Fernando Valley Raymond	4-124-23	Monk Hill Sub-Basin	4-13	450	100	100	0.5
Raymond	4-23	Santa Anita Area	4-13	450	100	100	0.5
Raymond	4-23	Pasadena Area	4-13	450	100	100	0.5
San Gabriel Valley	4-13	Main San Gabriel Basin	4-13				
San Gabriel Valley	4-13	Western Area ⁹	4-13	450	100	100	0.5
San Gabriel Valley	4-13	Eastern Area ⁹	4-13	600	100	100	0.5
San Gabriel Valley	4-13	Puente Basin	4-13	1000	300	150	1.0
Upper Santa Ana Valley/San Gabriel Valley	8-2.01ⁱ	Upper Santa Ana Valley	4-14				
San Gabriel Valley	4-13	Live Oak Area	8-2	450	150	100	0.5
San Gabriel Valley	4-13	Claremont Heights Area	8-2	450	100	50	
San Gabriel Valley	4-13	Pomona Area	8-2	300	100	50	0.5
Upper Santa Ana Valley/ San Gabriel Valley	8-2.01/4-13	Chino Area	8-2	450	20	15	
San Gabriel Valley	4-13	Spadra Area	8-2	550	200	120	1.0
Tierra Rejada	4-15	Tierra Rejada	4-15	700	250	100	0.5
Hidden Valley	4-16	Hidden Valley	4-16	1000	250	250	1.0
Lockwood Valley	4-17	Lockwood Valley	4-17	1000	300	20	2.0
Hungry Valley	4-18	Hungry Valley & Peace Valley	4-18	500	150	50	1.0
Conejo Valley	4-10	Thousand Oaks Area	4-19	1400	700	150	1.0
Russell Valley	4-20	Russell Valley	4-20				
Russell Valley	4-20	Russell Valley	4-20	1500	500	250	1.0
Thousand Oaks Area	4-19	Triunfo Canyon Area	4-20	2000	500	500	2.0
Thousand Oaks Area	4-20	Lindero Canyon Area	4-20	2000	500	500	2.0
Thousand Oaks Area	4-21	Las Virgenes Canyon Area	4-20	2000	500	500	2.0

BASINS			Objectives (mg/l) ^m				
Basin	Basin No ^b	1994 Basin Name	1994 Basin No	TDS	Sulfate	Chloride	Boron
Conejo-Tierra Rejada Volcanic Area^j	No DWR#	Conejo-Tierra Rejada Volcanic Area	4-21				
Malibu Valley	4-22	Santa Monica Mountains-Southern Slopes^k	4-22				
Malibu Valley	No DWR#	Camarillo Area		1000	250	250	1.0
Malibu Valley	No DWR#	Point Dume Area		1000	250	250	1.0
Malibu Valley	4-22	Malibu Valley	4-22	2000	500	500	2.0
Malibu Valley	No DWR#	Topanga Canyon Area		2000	500	500	2.0
San Pedro Channel Islands^l	No DWR#	San Pedro Channel Islands					
Anacapa Island	No DWR#	Anacapa Island	No DWR#				
San Nicholas Island	No DWR#	San Nicholas Island	No DWR#	1100	150	350	
Santa Catalina Island	No DWR#	Santa Catalina Island	No DWR#	1000	100	250	1.0
San Clemente Island	No DWR#	San Clemente Island	No DWR#				
Santa Barbara	No DWR#	Santa Barbara Island	No DWR#				

- a. Objectives for ground waters outside of the major basins listed on this table and outlined in Figure 1-9 have not been specifically listed. However, ground waters outside of the major basins are, in many cases, significant sources of water. Furthermore, ground waters outside of the major basins are either potential or existing sources of water for downgradient basins and, as such, objectives in the downgradient basins shall apply to these areas.
- b. Basins are numbered according to Bulletin 118-Update 2003 (Department of Water Resources, 2003).
- c. Ground waters in the Pitas Point area (between the lower Ventura River and Rincon Point) are not considered to comprise a major basin, and accordingly have not been designated a basin number by the California Department of Water Resources (DWR) or outlined on Figure 1-9.
- d. The Santa Clara River Valley (4-4) was formerly Ventura Central Basin
- e. Pleasant Valley (4-6), Arroyo Santa Rosa Valley (4-7) and Las Posas Valley (4-8) Ground Water Basins were former sub-basins of the Ventura Central Basin (DWR, 1980).
- f. Acton Valley Basin was formerly Upper Santa Clara Basin (DWR, 1980)
- g. San Gabriel Valley is a combination of what were formerly the Western and Eastern areas of the Main San Gabriel Basin, and the Puente Basin. [All of the](#)

Resolution No. R13-0XX

groundwater in the former Main San Gabriel Basin is covered by the objectives listed under Main San Gabriel Basin – Eastern Area and Western Area. Walnut Creek, Big Dalton Wash, and Little Dalton Wash separate the Eastern Area from the Western Area (see the dashed line on Figure A2-17 in Appendix II). -Any ground water upgradient of these areas is subject to downgradient beneficial uses and objectives, as explained in Footnote a.

- h. Raymond Basin was formerly a sub-basin of the San Gabriel Valley and is now a separate basin.
- i. The border between Regions 4 and 8 crosses the Upper Santa Ana Valley and San Gabriel Valley Ground Water Basins.
- j. Ground water in the Conejo-Tierra Rejada Volcanic Area occurs primarily in fractured volcanic rocks in the western Santa Monica Mountains and Conejo Mountain areas. These areas have not been delineated on Figure 1-9.
- k. With the exception of ground water in Malibu Valley (DWR Basin No. 4-22), ground waters along the southern slopes of the Santa Monica Mountains are not considered to comprise a major basin and accordingly have not been designated a basin number by the California Department of Water Resources (DWR) or outlined on Figure 1-9.
- l. DWR has not designated basins for ground waters on the San Pedro Channel Islands
- m. The Regional Board may grant, at its sole discretion, individual dischargers a variance from the numeric mineral quality objectives for groundwater specified in Table 3-10 under the conditions and procedures specified in “Coastal Aquifer Variance Provision for Mineral Quality Objectives” set forth in the Regional Objectives for Ground Waters.

Resolution No. R13-0XX

In “Chapter 3: Water Quality Objectives” of the Basin Plan, under the subsection titled “Regional Objectives for Ground Waters”, add the following table after Table 3-13 (formerly Table 3-10 in the 1994 Basin Plan), as directed in attachments to Regional Board Resolution No. R08-012:

Table 3-13a. Conditional Site Specific Objectives for Selected Constituents in Regional Groundwaters

DWR Basin No.	BASIN	Chloride (mg/L)
4-4	Santa Clara River Valley Lower area east of Piru Creek ¹	150 (rolling 12-month average)
4-4.07	Santa Clara River Valley East Santa Clara—Bouquet & San Francisquito Canyons Castaic Valley	150 (rolling 12-month average) 150 (rolling 12-month average)

1. This objective only applies to the San Pedro formation. Existing objective of 200 mg/L applies to shallow alluvium layer above San Pedro formation.

The conditional site specific objectives for chloride in the groundwater in Santa Clara--Bouquet & San Francisquito Canyons, Castaic Valley, and the lower area east of Piru Creek (San Pedro Formation) shall apply and supersede the existing regional groundwater quality objectives only when chloride load reductions and/or chloride export projects are in operation by the SCVSD according to the implementation section in Table 7-6.1 of Chapter 7.

In “Chapter 3: Water Quality Objectives” of the Basin Plan, add the following section at the end of the chapter, to address the Compliance Policy adopted through Regional Board Resolution No.R03-001 that has since been superseded by State Board's Compliance Policy which was adopted through State Board Resolution No 2005-0028:

COMPLIANCE WITH WATER QUALITY OBJECTIVES

On January 30, 2003, the Regional Board adopted Resolution No. 2003-001 amending this Basin Plan to incorporate language authorizing compliance schedules in NPDES permits. Resolution No. 2003-001 was subsequently approved by the State Water Resources Control Board, Office of Administrative Law, and the U.S. Environmental Protection Agency. On April 15, 2008, the State Water Resources Control Board adopted Resolution No. 2008-0025, which established a state-wide *Policy for Compliance Schedules in National Pollutant Discharge Elimination System Permits*. State Water Resources Control Board Resolution No. 2008-0025 superseded all existing provisions authorizing compliance schedules in Basin Plans, including Regional Board Resolution No. 2003-001, except for existing compliance schedule provisions in TMDL implementation plans that are in effect as of the effective date of Resolution No. 2008-0025. Further information on

Resolution No. R13-0XX

State Water Resources Control Board Resolution No. 2008-0025 is discussed in Chapter 5, Plans and Policies.

In Appendix 2: "Overlays" of the Basin Plan, and the following figures as part of Item 4: (Groundwater Basin Maps Delineating Sub-basin Boundaries in DWR Bulletin 118-80 and reflected in the June 1994 Basin Plan.):

Figure A2-11: Sub-basin Boundaries for Ojai Valley and Ventura River Valley Groundwater Basins.

Figure A2-12: Sub-basin Boundaries for Ventura Central Groundwater Basins.

Figure A2-13: Sub-basin Boundaries for Upper Santa Clara Groundwater Basins.

Figure A2-14: Sub-basin Boundaries for Upper Santa Clara Groundwater Basins.

Figure A2-15: Sub-basin Boundaries for Los Angeles Coastal Groundwater Basins.

Figure A2-16: Sub-basin Boundaries for San Fernando Valley Groundwater Basins.

Figure A2-17: Sub-basin Boundaries for San Gabriel Valley and Raymond Groundwater Basins.

Figure A2-18: Lockwood Valley, Hungry Valley and Peace Valley Groundwater Basins.