

Ethanol

Manufacturer's Affirmative Statement of Compatibility
(As required by California Code of Regulations section 2631(k))

I declare, to the best of my knowledge and belief, that this affirmative statement of compatibility and the information contained herein is true, correct, and complete.

MARK O'HERRY
Print Name

PRESIDENT
Title

[Signature]
Manufacturer's Authorized Signature

05-04-12
Date



QLWV.MH25059 Flexible Connectors for Flammable Liquids

[Page Bottom](#)

Flexible Connectors for Flammable Liquids

[See General Information for Flexible Connectors for Flammable Liquids](#)

FLEX-ING INC

MH25059

2828 FALLON DR
SHERMAN, TX 75090 USA

Aboveground flexible metallic connectors for flammable liquid tanks for petroleum products, alcohols and alcohol-gasoline mixtures, Models Fireman 3/4, Fireman 1, Fireman 1-1/2, Fireman 2, Fireman 3, Fireman 4, maximum working pressure 50 psi; Fireflex 1, 1-1/4, 1-1/2, 2 and 3 in., maximum working pressure 50 psi.

Flexible metallic connectors in underground sumps for petroleum products, alcohols and alcohol-gasoline mixtures, Models Fireman 3/4, Fireman 1, Fireman 1-1/2, Fireman 2, Fireman 3, Fireman 4, maximum working pressure 50 psi; Fireflex 1, 1-1/4, 1-1/2, 2, 3 and 4 in., maximum working pressure 50 psi; THC 1-1/4, 1-1/2 and 2 in., maximum working pressure 50 psi.

Flexible metallic connectors for underground use for petroleum products, alcohols and alcohol-gasoline mixtures, Models Fireman 3/4, Fireman 1, Fireman 1-1/2, Fireman 2, Fireman 3, Fireman 4, maximum working pressure 50 psi; THC 1-1/4, 1-1/2 and 2 in., maximum working pressure 50 psi.

[Last Updated](#) on 2001-05-10

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

© 2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".