STATE OF CALIFORNIA CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD LOS ANGELES REGION

MONITORING AND REPORTING PROGRAM NO. <u>CI-8739</u> FOR

MARY E. FREDERICK-QUAIL RANCH EROLLMENT UNDER REGIONAL BOARD ORDER NO. 91-94 SERIES NO. 34 (TRACT 50173-01) (FILE NO. 92-16)

I. REPORTING REQUIREMENTS

A. Mary E. Fredrick (the Discharger) shall implement this monitoring program on the effective date of this enrollment (June 2, 2004) under Regional Board Order No. 91-94. The first monitoring report under this Program is due by July 15, 2004.

Monitoring reports shall be received by the dates in the following schedule:

Reporting Period	Report Due
January – March	April 15
April – June	July 15
July – September	October 15
October – December	January 15

- B. If there is no discharge, during any reporting period, the report shall so state.

 Monitoring reports must be addressed to the Regional Board, Attention:

 Information Technology Unit.
- C. By March 1 of each year, the Discharger shall submit an annual summary report to the Regional Board. The report shall contain both tabular and graphical summaries of the monitoring data obtained during the previous calendar year. In addition, the Discharger shall explain the compliance record and the corrective actions taken or planned, which may be needed to bring the discharge into full compliance with the waste discharge requirements (WDRs).
- D. Laboratory analyses all chemical, bacteriological, and toxicity analyses shall be conducted at a laboratory certified for such analyses by the California Department of Health Services Environmental Laboratory Accreditation Program (ELAP). A copy of the laboratory certification shall be provided each time a new and/or renewal is obtained from ELAP.
- E. The method limits (MLs) employed for effluent analyses shall be lower than the permit limits established for a given parameter, unless the Discharger can

June 2, 2004

demonstrate that a particular ML is not attainable and obtains approval for a higher ML from the Regional Board Executive Officer (Executive Officer). At least once a year, the Discharger shall submit a list of the analytical methods employed for each test and the associated laboratory QA/QC procedures.

F. Water/wastewater samples must be analyzed within allowable holding time limits as specified in 40 CFR Part 136.3. All QA/QC samples must be run on the same dates when samples were actually analyzed. The Discharger shall make available for inspection and/or submit the QA/QC documentation upon request by Regional Board staff.

Proper chain of custody procedures must be followed and a copy of the chain of custody shall be submitted with the monitoring report.

- G. Each monitoring report must affirm in writing that "All analyses were conducted at a laboratory certified for such analyses by the California Department of Health Services, and in accordance with current USEPA guideline procedures or as specified in this Monitoring Program."
- H. Each monitoring report shall contain a separate section titled "Summary of Non-Compliance" which discusses the compliance record and the corrective actions taken or planned that may be needed to bring the discharge into full compliance with these WDRs. This section shall be located at the front of the report and shall clearly list all non-compliance with discharge requirements, as well as all excursions of effluent limitations.
- I. The Discharger shall maintain all sampling and analytical results, including strip charts; date; exact place, and time of sampling; dates analyses were performed; analyst's name; analytical techniques used; and results of all analyses. Such records shall be retained for a minimum of three years. This period of retention shall be extended during the course of any unresolved litigation regarding this discharge, or when requested by the Regional Board.
- J. In reporting the monitoring data, the Discharger shall arrange the data tabular form so that the date, the constituents, and the concentrations are readily discernible. The data shall be summarized to demonstrate compliance with the requirements and, where applicable, shall include results of receiving water observations.
- K. Any mitigation/remedial activity including any pre-discharge treatment conducted at the site must be reported in the quarterly monitoring report.

II. SEPTIC TANK AND DISPOSAL SYSTEM MONITORING REQUIREMENTS

The quarterly reports shall contain the following information:

- 1. Average and maximum daily waste flow for each month of the quarter, in gallons per day.
- 2. Estimated population served during each month of the reporting period.
- 3. Results of at least quarterly observations in the disposal area for any over flow or surfacing of wastes.

In addition, the Discharger shall annually submit an operation and maintenance report on the septic systems. The information to be contained in the report shall include, at a minimum, the following:

- 1. The name and address of the person or company responsible for the operation and maintenance of the facility;
- 2. Type of maintenance (preventive or corrective action performed);
- 3. Frequency of maintenance, if preventive;
- 4. Periodic pumping out of each septic tank; and
- 5. Maintenance records of each septic disposal system.

III. GROUNDWATER MONITORING PROGRAM

In lieu of the required groundwater monitoring program the Discharger has the option to install dry lateral sewers from each residence to a public street. If the Discharger chooses this option, a letter of intent must be submitted within 60 days from this enrollment date (June 2, 2004).

Should the Discharger chose to implement a groundwater monitoring program, the groundwater monitoring program shall be designed to detect and evaluate impacts from wastewater discharges from the septic disposal systems. A groundwater monitoring plan must be submitted to this Regional Board within 60 days from the effective date of this Order and is subject to the Executive Officer's approval prior to implementation. The groundwater monitoring wells must be installed in such a way as to fully assess the downgradient groundwater quality of any water zones encountered within 50 feet of the surface. The plan shall include the exact location of the proposed well, depths, construction of well, schedule for the installation and proposed sampling of the well.

Upon obtaining the Executive Officer's approval of an adequate groundwater monitoring network plan, construction and development of the proposed wells shall be completed within 60 days in accordance with the standards in Bulletins 74-81 and 74-90 of California Department of Water Resources. Within 30 days after installation of monitoring wells, a well installation report including a scaled plot plan, soil boring logs, water quality data, well permits and as-built well construction diagrams shall be submitted to this Board. This groundwater monitoring schedule may be subject to revision after completion of the first year of baseline water quality monitoring.

The monitoring program must be prepared under the direction of a California Registered Geologist, or Certified Engineering Geologist, or a California Registered Civil Engineer with appropriate experience in hydrogeology.

The following shall constitute the groundwater monitoring program:

Constituent	<u>Units</u> *	Type of Sample	Minimum Frequency of Analysis ^[1]
Total coliform Fecal coliform Enterococcus Ammonia-N Nitrate-N Nitrite-N Organic nitrogen Total dissolved solids Chloride Sulfate Boron	MPN/100mL MPN/100mL MPN/100mL mg/L mg/L mg/L mg/L mg/L mg/L mg/L mg	grab grab grab grab grab grab grab grab	quarterly quarterly quarterly quarterly quarterly quarterly quarterly quarterly quarterly quarterly

^[1] If any constituent exceeds the baseline water quality data, then the frequency of analyses shall increase to monthly until at least three test results have been obtained and there is no more exceeding constituent, after which the frequency of analyses shall revert to quarterly.

All groundwater monitoring reports must include, at minimum, the following:

- a. Well identification, date and time of sampling;
- b. Sampler identification, and laboratory identification;
- c. Quarterly observation of groundwater levels, recorded to 0.01 feet mean sea level; If no groundwater is found, that fact must be reported.
- d. Groundwater contour map depicting the direction of groundwater flow across the subject tract; and

^{*} MPN/100mL: Most Probable Number per milliliter; mg/L: milligram per liter

File No. 92-15

e. Vertical separation of groundwater levels to bottom of each septic disposal system (leach field and /or seepage pit).

IV. WASTE HAULING REPORTING

In the event that waste sludge, septage, or other wastes are hauled offsite, the name and address of the hauler shall be reported, along with types and quantities hauled during the reporting period and the location of final point of disposal. In the event that no wastes are hauled during the reporting period, a statement to that effect shall be submitted.

V. CERTIFICATION STATEMENT

Each report shall contain the following completed declaration:

"I certify under penalty of law that this document, including all attachments and supplemental information, were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of a fine and imprisonment.

Executed on the day of at .

			(Signature)
			(Title)"
during norma	•	ocuments and shall be made av fice of the California Regional V	
Ordered by:	Dennis A. Dickerson Executive Officer		Date: June 2, 2004