

**STATE OF CALIFORNIA
CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD
LOS ANGELES REGION
320 West 4th Street, Suite 200, Los Angeles, California 90013**

**FACT SHEET
WASTE DISCHARGE REQUIREMENTS
FOR
ULTRAMAR INC.
(VALERO WILMINGTON REFINERY TANK NO. TK11)**

**NPDES NO. CAG674001
CI-8594**

FACILITY ADDRESS

2402 E. Anaheim Street
Wilmington, CA 90744

FACILITY MAILING ADDRESS

2402 E. Anaheim Street
Wilmington, CA 90744

PROJECT DESCRIPTION:

Ultramar Inc. proposes to discharge hydrostatic test water from a newly constructed aboveground storage tank (Tank No. TK11) located at 2402 E. Anaheim Street, Wilmington. The wastewater from the aboveground storage tank will be discharged into the storm drain located along Pier A Street. Potable water supplied by the City of Los Angeles Department of Water and Power will be used for the hydrostatic testing.

VOLUME AND DESCRIPTION OF DISCHARGE:

Approximately 1.0 million gallons per day of hydrostatic test water will be discharged to the storm drain located along Pier A Street (Latitude: 33° 46' 12", Longitude: 118° 13' 48"). From the stormdrain, the discharge flows into the Long Beach Inner Harbor, a water of the United States. The location and site plan are shown in Figures 1 and 2.

FREQUENCY OF DISCHARGE:

The discharge will be intermittent. The Ultramar Inc. anticipates conducting the hydrostatic testing in June 2003.

REUSE OF WATER:

Reuse of water at the facility for irrigation and dust control were evaluated. However, there is no sufficient unpaved areas that will allow percolation of this quantity of water. Therefore, the hydrostatic test water will be discharged into the storm drain.