



San Diego Regional Water Quality Control Board

March 17, 2023

Georgina Gonzalez
LB Twin Lakes
LB Three, LLC
25275 Potrero Valley Rd
Potrero, CA 91963
Sent by email only:
lbtwinlakes@gmail.com

In reply refer to/attn.: 266817:Mlzadmehr

Subject: Tentative Notice of Applicability for Order WQ 2014-0153-DWQ, Waste

Discharge Requirements for the County of San Diego, LB Twin Lakes

Georgina Gonzalez:

This Tentative Notice of Applicability (NOA) is to inform LB Three, LLC (Discharger) that the LB Twin Lakes (Facility) onsite wastewater treatment system (OWTS) is anticipated to be enrolled in State Water Resources Control Board Order WQ 2014-0153-DWQ, General Waste Discharge Requirements for Small Domestic Wastewater Treatment Systems (General Order). The Facility's enrollment in the General Order is effective upon adoption of Tentative Order No. R9-2023-0040, An Order Rescinding Order No. 94-119, Waste Discharge Requirements for Vernon and Jane Shears, Twin Lakes Resort, San Diego County (Tentative Order No. R9-2023-0040) by the California Regional Water Quality Control Board, San Diego Region (San Diego Water Board). Adoption of Tentative Order No. R9-2023-0040 will be considered at the regularly scheduled San Diego Water Board meeting on June 14, 2023.

The San Diego Water Board reviewed Order No. 94-119, *Waste Discharge Requirements for Vernon and Jane Shears, Twin Lakes Resort, San Diego County* (Order No. 94-119) and the record of compliance with Order No. 94-119. Order No. 94-119 is outdated and not as protective of water quality as the requirements specified in the General Order. Implementation of the General Order provides a more appropriate and consistent statewide approach to regulating small domestic wastewater treatment systems. While the Discharger may request to be regulated under individual waste discharge requirements, the Facility's enrollment in the General Order allows the San Diego Water Board to effectively and efficiently regulate discharges from small domestic wastewater treatment systems, while prioritizing the agency's limited resources.

The Facility OWTS discharges less than 100,000 gallons per day and meets the enrollment eligibility criteria included in the General Order. An electronic copy of the General Order is available online at the following website:

CELESTE CANTÚ, CHAIR | DAVID GIBSON, EXECUTIVE OFFICER

https://www.waterboards.ca.gov/board_decisions/adopted_orders/water_quality/2014/wqo2014_0153_dwq.pdf

NOA FINDINGS AND REQUIREMENTS – The Discharger must comply with all applicable requirements in the General Order and any additional requirements included in this NOA, upon the effective date of enrollment in the General Order.

1. FACILITY AND DISCHARGE DESCRIPTION

The Facility is located at 25275 Potrero Valley Rd, Potrero, in San Diego County, within the Long Potrero Hydrologic Subarea of the Tijuana Hydrologic Unit. The Facility's OWTS includes 12 septic tanks and a recreational vehicle (RV) dump station that discharge to a leach field. Domestic wastewater is collected from 150 tenants, 52 permanent mobile homes, 92 RV spaces, two standard restrooms, a restroom with showers, and a laundry room.

2. CALIFORNIA ENVIRONMENTAL QUALITY ACT

The General Order regulates discharges from new and existing small domestic wastewater treatment systems. In accordance with the California Environmental Quality Act (CEQA) and consistent with Finding No. 32.a of the General Order, the action to enroll the Facility is categorically exempt from CEQA pursuant to California Code of Regulations (CCR) title 14, section 15301 (ongoing or existing projects), section 15302 (replacement or reconstruction of existing utility systems), and section 15303 (new construction or conversion of small structures).

3. FACILITY REQUIREMENTS

The Discharger and operator of the Facility must be familiar with the requirements contained in the General Order, this NOA, and the Monitoring and Reporting Program (MRP) in section 4 below.

The Discharger must comply with the prohibitions and specifications contained within the General Order, which are applicable to all wastewater systems. The Discharger also must comply with the following General Order specifications applicable to the Facility's specific treatment and/or disposal system.

- a. <u>Required Technical Reports/Plans.</u> The Discharger must submit the following plans and certificate:
 - A Spill Prevention and Emergency Response Plan consistent with the requirements of General Order Provision E.1.a. The San Diego Water Board must receive the Spill Prevention and Emergency Response Plan by <u>5:00</u> <u>p.m. on September 6, 2023</u>.
 - ii. A Sampling and Analysis Plan consistent with the requirements of General Order Provision E.1.b. The San Diego Water Board must receive the

Sampling and Analysis Plan by 5:00 p.m. on September 6, 2023.

- iii. A Sludge Management Plan consistent with the requirements of General Order Provision E.1.c. The San Diego Water Board must receive the Sludge Management Plan by 5:00 p.m. on September 6, 2023.
- iv. A certificate of compliance with Senate Bill 317.¹ The San Diego Water Board must receive the certificate of compliance by <u>5:00 p.m. on September</u> 6, 2023.

Upon receipt of these plans by the San Diego Water Board, the Discharger must implement the plans.

- b. <u>Prohibitions</u>. The Discharger must comply with all prohibitions listed in section A of the General Order and all applicable requirements in the *Water Quality Control Plan for the San Diego Basin* (Basin Plan).²
- c. <u>Setback Requirements.</u> The Discharger must ensure new discharges maintain the applicable setbacks specified in Table 3 of the General Order.
- d. Additional Applicable Requirements of the General Order. The Discharger must comply with all the requirements listed in sections B.1 (All Wastewater Systems), B.2 (Septic Systems), and B.6 (Subsurface Disposal Systems) of the General Order. Pursuant to B.1.a of the General Order, the Discharger shall not discharge wastewater in excess of the flow limit(s) specified in this NOA. The Discharger is prohibited from discharging in exceedance of a monthly average effluent flow rate of 100,000 gallons per day (gpd), pursuant to Finding 27 of the General Order. The Discharger must further evaluate the discharge to determine if nitrogen effluent limitations are appropriate, if the monthly average effluent flow rate exceeds 20,000 gpd.
- e. <u>RV Holding Chemicals.</u> The Discharger must distribute Attachment B2 of the General Order to all visitors discharging to the OWTS, instructing visitors not to use toxic RV holding chemicals. The Discharger must also post a sign at the RV dump station stating the following:

The State of California prohibits the use of products in RV holding tanks, including deodorizers, that contain bronopol, dowicil, formalin, formaldehyde, glutaraldehyde, paraformaldehyde, para-dichlorobenzene, benzene, toluene, xylene, ethylene glycol, 1,1,1-trichloroethane, trichloroethylene, or perchloroethylene. These chemicals can inhibit biological activity in onsite wastewater treatment systems and threaten groundwater and drinking water

https://leginfo.legislature.ca.gov/faces/billTextClient.xhtml?bill_id=201920200SB317

https://www.waterboards.ca.gov/sandiego/water_issues/programs/basin_plan/

¹ Web link to Senate Bill 317:

² Web link to the Basin Plan:

wells and are strictly forbidden. Please use bacteria- or enzyme-based products.

4. MONITORING AND REPORTING PROGRAM

The Discharger must comply with the monitoring requirements below, which are based on the MRP of the General Order.

a. Reporting Frequency

The Discharger must submit quarterly and annual monitoring reports as described in sections A and B of Attachment C of the General Order. The Discharger's first quarterly report is the July– Sept 2023 Quarterly Report, which must be submitted to the San Diego Water Board by 5:00 p.m. on November 1, 2023. The Discharger's first annual report is the 2023 Annual Report, which must be submitted to the San Diego Water Board by March 1, 2024.

b. Effluent Monitoring

The Discharger must collect a liquid grab sample from at least four septic tanks and combined in equivalent amounts for a single analysis. The Discharger shall implement a schedule for sampling the septic tanks so that all the septic tanks are sampled within a six-year period. The Discharger must collect septic tank effluent samples as close to the outlet pipe as practical. The Discharger must analyze the samples, and report the results as described in Table 1 below:

Table 1. Septic Tank Effluent Monitoring

Tuble 1. Septie Turk Emident Workstring				
Constituent	Units ¹	Sample Type	Sample Frequency ^{2,3}	Reporting Frequency ^{2,3}
Flowrate	gpd	Metered ⁴	Continuous	Annually
Zinc	mg/L	Grab	Quarterly	Quarterly
Phenol	mg/L	Grab	Quarterly	Quarterly
Formaldehyde	mg/L	Grab	Quarterly	Quarterly

Table Notes:

- 1) gpd denotes gallons per day and mg/L denotes milligrams per liter.
- 2) Annually is defined as a period of 12 consecutive calendar months beginning January 1.
- 3) Quarterly is defined as a period of three consecutive calendar months beginning on January 1, April 1, July 1, or October 1.
- 4) The Discharger may meter or estimate the effluent flowrate based on potable water supply meter readings or other approved method.

c. Septic Tank Monitoring and Inspection

Septic tank monitoring and inspecting must include the following:

Table 2. Septic Tank Monitoring and Inspection

Parameter	Units	Measurement Type	Inspection/Reporting Frequency
Sludge depth and scum thickness in each compartment of each tank	Feet	Staff Gauge	Annually
Distance between bottom of scum layer and bottom of outlet device	Inches	Staff Gauge	Annually
Distance between top of sludge layer and bottom of outlet device	Inches	Staff Gauge	Annually

Septic tanks shall be pumped when any one of the following conditions exists:

- i. The combined thickness of sludge and scum exceeds one-third of the tank depth of the first compartment.
- ii. The scum layer is within 3 inches of the outlet device.
- iii. The sludge layer is within 8 inches of the outlet device.

If the Discharger pumps out a septic tank during the year, the Discharger must submit the pumping report with the annual report. At a minimum, the pumping report shall include the date, nature of service, service company name, and service company license number.

d. Subsurface Disposal Monitoring

The Discharger must monitor the subsurface disposal area to determine if the septic system evenly applies wastewater; the discharge is not saturating the disposal area; burrowing animals and/or deep-rooted plants are not present; and odors are not present. The Discharger must self-inspect dosing pump controllers, automatic distribution valves, etc. to maintain optimum treatment in the disposal area (and any sand or media filter if present). Subsurface disposal monitoring must include the following at a minimum:

Table 3. Subsurface Disposal Area Monitoring

Constituent	Inspection Frequency⁵	Inspection/Reporting Frequency⁵	
Pump Controllers, Automatic Valves, etc. ¹	Quarterly	Quarterly	
Nuisance Odor Condition	Quarterly	Quarterly	

Constituent	Inspection Frequency⁵	Inspection/Reporting Frequency⁵
Saturated Soil Conditions ²	Quarterly	Quarterly
Plant Growth ³	Quarterly	Quarterly
Vectors or Animal Burrowing ⁴	Quarterly	Quarterly

Table Notes:

- 1) The Discharger must inspect all pump controllers and automatic distribution valves for proper operation as recommended by the manufacturer.
- 2) The Discharger must inspect the disposal area(s) for saturated conditions.
- 3) Shallow-rooted plants are generally desirable. The Discharger must remove deep-rooted plants such as trees, as necessary.
- 4) The Discharger must investigate evidence of animals burrowing, and control burrowing animal populations, as necessary.
- 5) Quarterly is defined as a period of three consecutive calendar months beginning on January 1, April 1, July 1, or October 1.

5. CHANGE IN OWNERSHIP

When control or ownership changes of the Facility or wastewater disposal areas, the Discharger must notify the succeeding owner or operator of the existence of this General Order by letter, a copy of which must be immediately forwarded to the Executive Officer for the San Diego Water Board.

6. ENFORCEMENT

The Discharger must review and ensure this NOA completely and accurately reflects the Facility's discharge. If the Discharger violates the terms or conditions listed in this NOA or the General Order, the San Diego Water Board may take enforcement action, including assessment of administrative civil liability. Prior to allowing changes to the wastewater strength, generation rate, or method of waste disposal, the Discharger must contact the San Diego Water Board to determine if submittal of a report of waste discharge is required.

The Discharger is responsible for compliance with the General Order and this NOA. Failure to comply with the requirements in the General Order and this NOA could result in an enforcement action as authorized by provisions of the California Water Code. Discharges of wastes other than treated domestic wastewater are prohibited.

7. ANNUAL FEES AND SAN DIEGO WATER BOARD CONTACT INFORMATION

The discharge has a threat to water quality and complexity rating of 3-C. The annual fee corresponding to a threat to water quality and complexity of 3-C can be found using the current fee schedule.³ Pursuant to CCR title 23, section 2200(a), footnote

https://www.waterboards.ca.gov/resources/fees/water_quality/

³ Web link to Fee Schedule:

2, dischargers covered by waste discharge requirements for municipal and domestic discharges with permitted flows of less than 50,000 gallons per day in categories 2-B, 2-C, 3-B, and 3-C will receive a 50 percent fee discount. The fee is due and payable on an annual basis until enrollment in the General Order is terminated by the San Diego Water Board. If the wastewater discharge ceases, the Discharger must provide written notice to enable the San Diego Water Board to terminate enrollment and billing.

Please review the conditions specified in this NOA and applicable sections of the General Order and notify the San Diego Water Board if for any reason the Discharger is not able to comply with any of the conditions specified.

Please submit all future monitoring reports and documents required by this NOA and the General Order to the San Diego Water Board by email. Email submittals must include a signed cover/transmittal letter with the facility name, facility contact information, and reference code **266817:Mlzadmehr**. Monitoring reports, documents, and other email submittals must be sent to sandiego@waterboards.ca.gov. Routine email correspondence may be sent directly to individual San Diego Water Board staff members.

Documents that are 50 megabytes or larger should be transferred to a compact disc (CD) or universal serial bus (USB) drive and mailed to the San Diego Water Board. Board staff may request that specific individual items such as appendices to large/complex technical reports and/or large drawings, grading plans, or maps continue to be provided in paper format. If you have specific questions about email submittal procedures, please contact our Mission Support Services Unit by phone at 619-516-1990, or via email at sandiego@waterboards.ca.gov.

Please contact Dr. Mahsa Izadmehr at (619) 521-8048 or via email at Mahsa.Izadmehr@waterboards.ca.gov if you have any questions or comments.

Respectfully,

TENTATIVE

David W. Gibson Executive Officer

DWG:rnm:as:bn:mi

cc (via email): Heather Buonomo, San Diego County Department of Environmental

Health and Quality, Heather.Buonomo@sdcounty.ca.gov

<u>Tech Staff Info & Use</u> Regulatory Measure IDs: 450945 (NOA) 398403 (WQ 2014-0153-DWQ)

Order No.: WQ 2014-0153-DWQ

Place ID: 266817 Party ID: 634550