CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD SAN FRANCISCO BAY REGION

1515 Clay Street, Suite 1400, Oakland, California 94612 waterboards.ca.gov/sanfranciscobay

ORDER R2-2024-0013 NPDES PERMIT CA0038873

The following dischargers (collectively, Dischargers and, individually, Discharger) are subject to waste discharge requirements (WDRs) set forth in this Order, for the purpose of regulating nutrient discharges to San Francisco Bay¹ and its contiguous bay segments:

Discharger	Facility Name	Facility Address	Minor/ Major
American Canyon, City of	Wastewater Treatment and Reclamation Facility	151 Mezzetta Court American Canyon, CA 94503	Major
Benicia, City of	Benicia Wastewater Treatment Plant	614 East Fifth Street Benicia, CA 94510	Major
Burlingame, City of	Burlingame Wastewater Treatment Plant	1103 Airport Boulevard Burlingame, CA 94010	Major
Central Contra Costa Sanitary District	Central Contra Costa Sanitary District Wastewater Treatment Plant	5019 Imhoff Place Martinez, CA 94553	Major
Central Marin Sanitation Agency	Central Marin Sanitation Agency Wastewater Treatment Plant	1301 Andersen Drive San Rafael, CA 94901	Major
Crockett Community Services District	Port Costa Wastewater Treatment Plant	End of Canyon Lake Drive Port Costa, CA 94569	Minor
Delta Diablo	Delta Diablo Wastewater Treatment Plant	2500 Pittsburg-Antioch Highway Antioch, CA 94509	Major
East Bay Dischargers	EBDA Common Outfall		
Authority (EBDA); Cities of Hayward and San Leandro:	Hayward Water Pollution Control Facility		
Oro Loma Sanitary District; Castro Valley Sanitary	San Leandro Water Pollution Control Plant	EBDA Common Outfall 14150 Monarch Bay Drive	Major
District; Union Sanitary District; East Bay Regional	Oro Loma/Castro Valley Sanitary Districts Water Pollution Control Plant	San Leandro, CA 94577	
Parks District; Livermore- Amador Valley Water	Raymond A. Boege Alvarado Wastewater Treatment Plant		

Table 1. Discharger Information

¹ San Francisco Bay consists of the Sacramento/San Joaquin River Delta, Suisun Bay, Carquinez Strait, San Pablo Bay, Central San Francisco Bay, Richardson Bay, Lower San Francisco Bay, and South San Francisco Bay.

Discharger	Facility Name	Facility Address	Minor/ Major
Management Agency; Dublin Ramon Services District; and City of Livermore	Livermore-Amador Valley Water Management Agency Export and Storage Facilities		
	Dublin San Ramon Services District Wastewater Treatment Plant		
	City of Livermore Water Reclamation Plant		
East Bay Municipal Utility District	East Bay Municipal Utility District, Special District No. 1 Wastewater Treatment Plant	2020 Wake Avenue Oakland, CA 94607	Major
Fairfield-Suisun Sewer District	Fairfield-Suisun Wastewater Treatment Plant	1010 Chadbourne Road Fairfield, CA 94534	Major
Las Gallinas Valley Sanitary District	Las Gallinas Valley Sanitary District Sewage Treatment Plant	300 Smith Ranch Road San Rafael, CA 94903	Major
Marin County (Paradise Cove), Sanitary District No. 5 of	Paradise Cove Treatment Plant	3700 Paradise Drive Tiburon, CA 94920	Minor
Marin County (Tiburon), Sanitary District No. 5 of	Wastewater Treatment Plant	2001 Paradise Drive Tiburon, CA 94920	Minor
Millbrae, City of	Water Pollution Control Plant	400 East Millbrae Avenue Millbrae, CA 94030	Major
Mt. View Sanitary District	Mt. View Sanitary District Wastewater Treatment Plant	3800 Arthur Road Martinez, CA 94553	Major
Napa Sanitation District	Soscol Water Recycling Facility	1515 Soscol Ferry Road Napa, CA 94558	Major
Novato Sanitary District	Novato Sanitary District Wastewater Treatment Plant	500 Davidson Street Novato, CA 94945	Major
Palo Alto, City of	Palo Alto Regional Water Quality Control Plant	2501 Embarcadero Way Palo Alto, CA 94303	Major
Petaluma, City of	Municipal Wastewater Treatment Plant	3890 Cypress Drive Petaluma, CA 94954	Major
Pinole, City of	Pinole-Hercules Water Pollution Control Plant	11 Tennent Avenue Pinole, CA, 94564	Major
Rodeo Sanitary District	Rodeo Sanitary District Water Pollution Control Facility	800 San Pablo Avenue Rodeo, CA 94572	Major
San Francisco (San Francisco International Airport), City and County of	Mel Leong Treatment Plant, Sanitary Plant	Bldg. 924 Clearwater Drive San Francisco, CA 94128	Major
San Francisco (Southeast Plant), City and County of	Southeast Water Pollution Control Plant	750 Phelps Street San Francisco, CA 94124	Major
San Jose and Santa Clara, Cities of	San Jose/Santa Clara Water Pollution Control Plant	700 Los Esteros Road San Jose, CA 95134	Major
San Mateo, City of	City of San Mateo Wastewater Treatment Plant	2050 Detroit Drive San Mateo, CA 94404	Major
Sausalito-Marin City Sanitary District	Sausalito-Marin City Sanitary District Wastewater Treatment Plant	1 East Road Sausalito, CA 94965	Major

Discharger	Facility Name	Facility Address	Minor/ Major
Sewerage Agency of Southern Marin	Sewerage Agency of Southern Marin Wastewater Treatment Plant	450 Sycamore Avenue Mill Valley, CA 94941	Major
Silicon Valley Clean Water	Silicon Valley Clean Water Wastewater Treatment Plant	1400 Radio Road Redwood City, CA 94065	Major
Sonoma Valley County Sanitation District	Municipal Wastewater Treatment Plant	22675 8th Street East Sonoma, CA 95476	Major
South San Francisco and San Bruno, Cities of	South San Francisco and San Bruno Water Quality Control Plant	195 Belle Air Road South San Francisco, CA 94080	Major
Sunnyvale, City of	Sunnyvale Water Pollution Control Plant	1444 Borregas Avenue, Sunnyvale, CA 94089	Major
Treasure Island Development Authority	Treasure Island Wastewater Treatment Plant	1220 Avenue M San Francisco, CA 94130	Major
Vallejo Flood and Wastewater District	Vallejo Flood and Wastewater District Wastewater Treatment Plant	450 Ryder Street Vallejo, CA 94590	Major
West County Agency; West County Wastewater District; City of Richmond; and Richmond Municipal Sewer District	West County Agency Combined Outfall West County Wastewater District Treatment Plant Richmond Municipal Sewer District Water Pollution Control Plant	2910 Hilltop Drive Richmond, CA 94806	Major

Table 2. Discharge Locations

Discharge locations are specified in the individual NPDES permits listed in Attachment B.

This Order was adopted on: This Order shall become effective on: This Order shall expire on: CIWQS regulatory measure number: July 10, 2024 October 1, 2024 September 30, 2029 457777

I hereby certify that this Order with all attachments is a full, true, and correct copy of the Order adopted by the San Francisco Bay Regional Water Quality Control Board (Regional Water Board) on the date indicated above.

Eileen White, Executive Officer

CONTENTS

1.	FACILITY INFORMATION	5
2.	FINDINGS	5
3.	DISCHARGE PROHIBITIONS	8
4.	EFFLUENT LIMITATIONS	8
5.	RECEIVING WATER LIMITATIONS	11
6.	PROVISIONS	11

TABLES

TABLE 1. DISCHARGER INFORMATION	1
TABLE 2. DISCHARGE LOCATIONS	3
TABLE 3. INTERIM EFFLUENT LIMITATIONS	9
TABLE 4. FINAL EFFLUENT LIMITATIONS	10
TABLE 5. COMPLIANCE SCHEDULE MILESTONES	14

ATTACHMENTS

ATTACHMENT A – DEFINITIONS AND ABBREVIATIONS	A-1
ATTACHMENT B – INDIVIDUAL NPDES PERMITS AND ORDER NUMBERS	B-1
ATTACHMENT C – MAP OF MUNICIPAL DISCHARGE LOCATIONS	C-1
ATTACHMENT D – STANDARD PROVISIONS	D-1
ATTACHMENT E – MONITORING AND REPORTING PROGRAM	E-1
ATTACHMENT F – FACT SHEET	F-1

1. FACILITY INFORMATION

Information describing the facilities subject to this Order is summarized in Table 1 and in Fact Sheet (Attachment F) sections 1 and 2.

2. FINDINGS

The Regional Water Board finds the following:

- 2.1. Legal Authorities. This Order serves as WDRs pursuant to California Water Code article 4, chapter 4, division 7 (commencing with § 13260). This Order is also issued pursuant to federal Clean Water Act (CWA) section 402 and implementing regulations adopted by U.S. EPA and Water Code chapter 5.5, division 7 (commencing with § 13370). It shall serve as a National Pollutant Discharge Elimination System (NPDES) permit for point source discharges of nutrients from the Discharger facilities listed in Attachment B to surface waters.
- **2.2. Background and Rationale for Requirements.** San Francisco Bay is the West Coast's largest estuary and home to over seven million people. It has long been recognized as a nutrient-enriched estuary with higher nitrogen and phosphorus concentrations than most estuaries in the world. Too much nitrogen and phosphorous can result in excessive phytoplankton growth, which can be associated with harmful algal blooms and low dissolved oxygen levels. In San Francisco Bay, nitrogen has more influence on phytoplankton growth than phosphorous. During the dry season, the Dischargers account for about 86 percent of the total nitrogen loading to San Francisco Bay.

Despite being nutrient rich, the Bay has historically resisted excessive phytoplankton growth due to its turbidity, which limits the light penetration necessary for phytoplankton growth; strong tidal mixing, which limits periods of stratification necessary for phytoplankton to thrive at the Bay's surface; and filterfeeding clams, which graze on phytoplankton. However, increasing phytoplankton levels in the early 2000s indicated that the Bay's resilience may be weakening, and the Region's population growth could increase nitrogen loads.

The Regional Water Board initiated a Nutrient Management Strategy in 2012 and convened a Steering Committee in 2014, with the participation of U.S. EPA, the Dischargers, scientific researchers, and non-governmental organizations. The Steering Committee oversees a Nutrient Science Program managed by the San Francisco Estuary Institute (SFEI).¹ The Nutrient Science Program includes

¹ SFEI is a premier science organization that has been rigorously monitoring and analyzing San Francisco Bay for pollutants through the Regional Monitoring Program and nutrients through the Nutrients Science Program through coordination with publicly owned treatment works, the Regional Water Board, U.S. EPA, and non-governmental organizations.

monitoring, modeling, and special studies to better understand and respond to the possibility that the Bay could be losing its resilience to high nutrient levels, to evaluate nutrient reduction alternatives to prevent or resolve adverse impacts to the Bay, and to establish a scientific basis for regulatory actions.

In 2014, the Regional Water Board issued the first Nutrients Watershed Permit to provide a consistent approach for regulating municipal wastewater treatment plants within the San Francisco Bay watershed. The permit required the Dischargers to (1) contribute \$880,000 per year to the Nutrient Science Program to support receiving water monitoring, modeling, and special studies to characterize the Bay's response to current and future nutrient loads; (2) monitor their effluent to characterize nutrient discharge concentrations and loads; and (3) evaluate opportunities to reduce nutrient discharges through treatment plant optimization and upgrades.

In 2019, the Regional Water Board reissued the Nutrients Watershed Permit. The permit required the Dischargers to (1) to contribute \$2.2 million per year to continue and enhance the Nutrient Science Program; (2) continue to monitor their effluent to characterize nutrient discharge concentrations and loads; and (3) to evaluate opportunities to reduce nutrient discharges through recycling treated wastewater or using wetlands systems and other nature-based or multi-benefit systems. The resulting information, with the previously compiled information about potential opportunities to reduce nutrient discharges through treatment plant optimization and upgrades, provides a complete suite of nutrient reduction strategies from which the Dischargers can select the most cost-effective actions that provide the most benefits.

In July and August 2022, San Francisco Bay experienced a significant harmful algal bloom that resulted in nuisance odors and massive fish kills due in part to loss of dissolved oxygen in the water from decaying algae. The harmful algal bloom resulted in thousands of dead fish and made national news.² While the causes of the harmful algal bloom are unknown, high levels of nutrients in Bay waters enabled its extensive propagation by providing fuel for the algae to consume. This event provided cause for the Regional Water Board to establish requirements in this reissued Nutrients Watershed Permit for nutrient load reductions to prevent or minimize the propagation of a future harmful algal bloom that could adversely affect beneficial uses of the Bay. Modeling and observational data demonstrate that San Francisco Bay can no longer assimilate current nutrient loads during the summer months without fueling a large algal bloom and significant fish kills as occurred in July and August 2022. Nutrient load reductions are necessary to comply with the biostimulatory substances water quality

² See, e.g., <u>https://www.nytimes.com/2022/08/30/us/fish-dead-algae-bloom-</u> <u>california.html?searchResultPosition=1</u> and <u>https://www.cnn.com/2022/09/03/us/san-francisco-bay-</u> <u>area-algae-fish/index.html</u>.

objective, which provides that waters shall not contain such substances in concentrations that promote aquatic growths to the extent that they cause nuisance or adversely affect beneficial uses.

The Regional Water Board developed the requirements in this Order based on information the Dischargers submitted, information obtained through monitoring and reporting programs, and other available information. The Fact Sheet contains background information and rationales for this Order's requirements and is hereby incorporated into, and constitutes findings for, this Order. Attachments A, B, C, D, and E are also incorporated into this Order.

This Order requires the Dischargers to reduce dry season total inorganic nitrogen loads to San Francisco Bay by 40 percent regionwide compared to 2022 loads over a 10-year period, which is the maximum time allowed in an NPDES permit by the State Water Resources Control Board's (State Water Board) *Policy for Compliance Schedules in National Pollutant Discharge Elimination System Permits* (Compliance Schedule Policy; Resolution 2008-0025). The load reduction was developed using a model created by SFEI, which manages the Nutrients Science Program. The nitrogen load reductions this Order requires are the minimum necessary to protect the Bay's aquatic life from an algal bloom that could form under ambient conditions similar to those in July and August 2022 (e.g., weak tides, solar irradiance, low wind speed, low turbidity, and warm temperature) when the large algal bloom fueled by available nitrogen resulted in massive fish kills.

The cost to implement these load reductions will be significant. In response to the first Nutrients Watershed Permit requirement to evaluate opportunities to reduce nutrient discharges through treatment plant optimization and upgrades, the Dischargers prepared a report, *Bay Area Clean Water Agencies Nutrient Reduction Study: Potential Nutrient Reduction by Treatment Optimization, Sidestream Treatment, Treatment Upgrades, and Other Means*, dated June 22, 2018. The evaluation found that to implement conventional technologies to reduce total nitrogen concentrations below 15 mg/L during the dry season would cost about \$8.8 billion regionwide in 2018 dollars, which amounts to nearly \$11 billion in 2024.

This Order requires Dischargers to take steps to comply with the 40 percent load reduction requirement within 10 years, while maintaining at least current performance in the interim. If a Discharger cannot comply within 10 years, the Regional Water Board will consider regulatory mechanisms as warranted and as available to grant more time (see Fact Sheet section 6.3.5). This Order recognizes that multi-benefit solutions, such as nature-based treatment or water recycling, may take longer than 10 years to implement, and the Regional Water Board will use any available regulatory mechanisms to allow more time for these projects to be implemented.

This Order requires Dischargers to continue funding the Nutrient Science Program. For the permit reissuance scheduled for 2029, the Regional Water Board will consider any new information available (e.g., observational data, improved load response modeling, and other scientific updates generated by the Nutrient Science Program) to reassess and refine the final limits in this Order to ensure that they remain appropriate to protect San Francisco Bay beneficial uses. This may involve adjusting the magnitude of the required load reductions, the spatial scale for the load reductions (e.g., by subembayment instead of baywide), or the timeperiod used to evaluate nitrogen loading.

- **2.3.** Notification of Interested Parties. The Regional Water Board notified the Dischargers and interested agencies and persons of its intent to prescribe these WDRs and has provided an opportunity to submit written comments and recommendations. Fact Sheet section 8.1 provides details regarding the notification.
- **2.4. Consideration of Public Comment.** The Regional Water Board, in a public meeting, heard and considered all comments pertaining to the discharge. Fact Sheet section 8.4 provides details regarding the public hearing.

THEREFORE, IT IS HEREBY ORDERED that Order R2-2019-0017 (previous order) is rescinded upon the effective date of this Order, except for enforcement purposes, and, in order to meet the provisions contained in Water Code division 7 (commencing with § 13000) and regulations adopted thereunder and the provisions of the CWA and regulations and guidelines adopted thereunder, the Dischargers shall comply with the requirements in this Order. This action in no way prevents the Regional Water Board from taking enforcement action for violations of the previous order.

3. DISCHARGE PROHIBITIONS

This Order does not establish additional discharge prohibitions beyond those established in the individual NPDES permits listed in Attachment B of this Order.

4. EFFLUENT LIMITATIONS

4.1. Interim Effluent Limitations. The Dischargers shall comply with the following interim seasonal effluent limitations at the discharge points and monitoring locations specified in the Monitoring and Reporting Program (MRP) (Attachment E). Final effluent limitations shall become effective in accordance with the compliance schedule established by Provision 6.3.3 of this Order. Compliance with these interim limitations shall be determined seasonally for each Discharger based on discharges from May 1 through September 30. Mass loads shall be determined by calculating each daily average total inorganic nitrogen load from daily flows and concentrations, averaging all resulting daily loads, and rounding to two significant figures.

Discharger	Total Inorganic Nitrogen (kg/day)
American Canyon, City of	79
Benicia, City of	290
Burlingame, City of	610
Central Contra Costa Sanitary District	4,300
Central Marin Sanitation Agency	1,300
Crockett Community Services District	5.3
Delta Diablo	2,000
East Bay Dischargers Authority (EBDA)	
City of Hayward	
City of San Leandro	
Oro Loma Sanitary District and	
Linion Sanitary District	9,000
Livermore-Amador Valley Water Management Agency	
Dublin San Ramon Services District	
City of Livermore	
East Bay Municipal Utility District	11,000
Fairfield-Suisun Sewer District	1,600
Marin County (Paradise Cove), Sanitary District No. 5 of	3.7
Marin County (Tiburon), Sanitary District No. 5 of	69
Millbrae, City of	340
Mt. View Sanitary District	190
Novato Sanitary District	210
Palo Alto, City of	2,900
Pinole, City of	460
Rodeo Sanitary District	50
San Francisco (San Francisco International Airport), City and County of	560
San Francisco (Southeast Plant), City and County of	11,000
San Jose and Santa Clara, Cities of	6,400
San Mateo, City of	1,700
Sausalito-Marin City Sanitary District	180
Sewerage Agency of Southern Marin	280
Silicon Valley Clean Water	3,000
South San Francisco and San Bruno, Cities of	1,500
Sunnyvale, City of	830
Treasure Island Development Authority	29
Vallejo Flood and Wastewater District	1,000

Table 3. Interim Effluent Limitations

Discharger	Total Inorganic Nitrogen (kg/day)	
West County Agency		
West County Wastewater District	1 100	
City of Richmond and Richmond Municipal Sewer District	1,100	

4.2. Final Effluent Limitations. In accordance with the compliance schedule established by this Order in Provision 6.3.3, starting October 1, 2034, the Dischargers shall comply with the following final seasonal water quality-based effluent limitations at the discharge points and monitoring locations specified in the MRP. Compliance with these final limitations shall be determined seasonally based on discharges from May 1 through September 30. If the sum of all the individual Dischargers' total inorganic nitrogen mass loads is greater than the Aggregate Mass Load Limit set forth below, the Dischargers whose total inorganic nitrogen mass loads exceed their individual limitations shall be in violation of their individual limitations. Mass loads shall be determined by calculating each daily average total inorganic nitrogen load from daily flows and concentrations, averaging all resulting daily loads, and rounding to two significant figures. The Aggregate Mass Load shall be determined by summing each individual Dischargers' average mass load.

Discharger	Total Inorganic Nitrogen (kg/day) ^[2]
American Canyon, City of	62
Benicia, City of	120
Burlingame, City of	160
Central Contra Costa Sanitary District	2,300
Central Marin Sanitation Agency	480
Crockett Community Services District	3.7
Delta Diablo ^[1]	920
East Bay Dischargers Authority (EBDA)	
City of Hayward	
City of San Leandro	
Oro Loma Sanitary District and	4,200
Castro Valley Sanitary District	
Union Sanitary District	
Livermore-Amador Valley Water Management Agency	
Dublin San Ramon Services District	
City of Livermore	
East Bay Municipal Utility District	3,300
Fairfield-Suisun Sewer District	880
Marin County (Paradise Cove), Sanitary District No. 5 of	3.5

Table 4. Final Effluent Limitations

Discharger	Total Inorganic Nitrogen (kg/day) ^[2]
Marin County (Tiburon), Sanitary District No. 5 of	47
Millbrae, City of	100
Mt. View Sanitary District	78
Novato Sanitary District	140
Palo Alto, City of	1,200
Pinole, City of	190
Rodeo Sanitary District	38
San Francisco (San Francisco International Airport), City and County of	71
San Francisco (Southeast Plant), City and County of	3,300
San Jose and Santa Clara, Cities of	5,000
San Mateo, City of	670
Sausalito-Marin City Sanitary District	69
Sewerage Agency of Southern Marin	140
Silicon Valley Clean Water	880
South San Francisco and San Bruno, Cities of	560
Sunnyvale, City of	740
Treasure Island Development Authority	21
Vallejo Flood and Wastewater District	580
West County Agency	
West County Wastewater District	430
City of Richmond and Richmond Municipal Sewer District	+50
Aggregate Mass Load Limit (kg/day)	26,700

Footnote:

- ^[1] Delta Diablo may apply a discharge adjustment to its final discharge mass emission when determining compliance with its limit. The adjustment shall be based on measured total inorganic nitrogen levels from the reverse osmosis concentrate it receives from the City of Antioch's Brackish Water Desalination Project. Delta Diablo shall calculate the adjustment by using flow and total inorganic nitrogen concentrations in reverse osmosis concentrate that must be monitored at the same monitoring frequency as effluent in MRP Table E-4.
- ^[2] If a Discharger accepts wastewater from another agency for its recycled water supply, but then is unable to recycle it due to uncontrollable factors, the Discharger shall document such factors in its related self-monitoring reports.

5. RECEIVING WATER LIMITATIONS

The receiving water limitations for the biostimulatory substances water quality objective that are applicable to the Dischargers are established in the individual NPDES permits listed in Attachment B.

6. PROVISIONS

6.1. Standard Provisions. The Dischargers shall comply with the standard provisions in Attachment D and G of their individual NPDES permits listed in Attachment B of this Order.

6.2. Monitoring and Reporting Provisions. The Discharger shall comply with the Monitoring and Reporting Program (MRP, Attachment E) and future revisions thereto, and applicable monitoring and reporting requirements in Attachments D and G of their individual NPDES permits listed in Attachment B of this Order.

6.3. Special Provisions

- 6.3.1. **Reopener Provisions**. The Regional Water Board may modify or reopen this Order prior to its expiration date in any of the following circumstances as allowed by law or as otherwise authorized by law. Any Discharger may request a permit modification in accordance with 40 C.F.R section 122.62. With any such request, the Discharger shall include antidegradation and anti-backsliding analyses as necessary.
- 6.3.1.1. If present or future investigations demonstrate that the discharges governed by this Order have or will have a reasonable potential to cause or contribute to adverse impacts on water quality or beneficial uses of the receiving waters;
- 6.3.1.2. If new or revised water quality objectives or total maximum daily loads (TMDLs) come into effect for San Francisco Bay or contiguous water bodies (whether statewide, regional, or site-specific). In such cases, effluent limitations in this Order may be modified as necessary to reflect the updated water quality objectives or wasteload allocations. Adoption of the effluent limitations in this Order does not restrict in any way future modifications based on legally adopted water quality objectives or TMDLs or as otherwise permitted under federal regulations governing NPDES permit modifications;
- 6.3.1.3. If studies provide a basis for determining that a permit condition should be modified;
- 6.3.1.4. If a State Water Board precedential decision, new policy, new law, or new regulation is adopted;
- 6.3.1.5. If an administrative or judicial decision on a separate NPDES permit or WDRs addresses requirements similar to this discharge; or
- 6.3.1.6. If the final effluent limitations for total inorganic nitrogen do not attain and maintain applicable water quality standards.
- 6.3.2. **Monitoring, Modeling, and Subembayment Studies.** Each Discharger listed in Table 1 shall conduct, or cause to be conducted, studies to continue to address the potential adverse impacts of nutrients on San Francisco Bay beneficial uses. The studies shall include the efforts described below:
- 6.3.2.1. **Support Receiving Water Monitoring.** Individually or in collaboration with other regional stakeholders, support receiving water monitoring for nutrients

and related constituents. These efforts shall supplement the monitoring the Regional Monitoring Program and other entities already undertake, by providing the following:

- 6.3.2.1.1. A network of nutrient monitoring locations to track nutrient concentrations, dissolved oxygen, turbidity, and phytoplankton biomass in San Francisco Bay;
- 6.3.2.1.2. Adequate data to support continued modeling of nutrient fate and transport in San Francisco Bay; and
- 6.3.2.1.3. Studies furthering the understanding of harmful algae bloom development, including, at a minimum, monitoring for algae species and toxins.
- 6.3.2.2 **Increase San Francisco Bay's Resilience**. Explore opportunities to restore wetlands or to increase the resiliency of San Francisco Bay against nutrient loading (e.g., eelgrass beds to increase dissolved oxygen).
- 6.3.2.3. **Support Science Plan Development and Implementation.** Individually or in collaboration with other regional stakeholders, support further development, update, and implementation of the Nutrient Science Program to implement the San Francisco Bay Nutrient Management Strategy and support consideration of future management actions, including the development of nutrient water quality objectives. The Nutrient Science Program shall include studies necessary to assess water quality attainment scenarios for San Francisco Bay as a whole and for specific subembayments. The modeling and monitoring described in Provision 6.3.2.1, above, shall inform the Nutrient Science Program and any future management actions.

By June 1, 2025, submit, or cause to be submitted, an updated science plan and schedule for proposed studies, and annually update and revise the plan and schedule as necessary by June 1 of each subsequent year.

6.3.3. Compliance Schedule Milestones and Progress Reporting

This Order establishes compliance schedules for Dischargers in Table 4 to meet the final water quality-based effluent limitations for total inorganic nitrogen within 10 years consistent with the State Water Board's Compliance Schedule Policy, as further explained in Fact Sheet section 4.2.1. To demonstrate progress in meeting these limits, each Discharger listed in Table 4 shall submit the information required below with the Annual Nutrients Report required by MRP section 5.2.2 starting with the Group Annual Report due April 1, 2025, and each year thereafter:

6.3.3.1. Summary of progress toward meeting the total inorganic nitrogen final effluent limitations in Table 4, including actions taken to reduce total

inorganic nitrogen loads. Table 5, below, includes specific milestones that must also be completed. Early Actors defined by Provision 6.3.6 shall instead provide annual status updates on project implementation.

Milestone	Compliance Date
Identify Compliance Alternatives. Dischargers shall identify preliminary alternatives for meeting the final effluent limitations in Table 4. This may include traditional treatment infrastructure, optimization, nature-based solutions, recycled water, trading, or a combination thereof. The submittal shall note whether the identified alternatives require pilot projects. If a Discharger has already identified a compliance pathway (selected alternative or combination of alternatives), the Discharger shall instead describe the compliance pathway, begin implementation, and provide a status update.	April 1, 2025
Perform Alternatives Analysis. Dischargers shall evaluate the compliance alternatives and identify which alternative or combination of alternatives (i.e., compliance pathway) best achieves compliance with the final effluent limitations in Table 4. If a Discharger has already identified a compliance pathway, the Discharger shall provide a status update regarding implementation. If a Discharger plans to meet the final effluent limits in Table 4 solely or in part through treatment optimization, it shall include a schedule to	April 1, 2026
complete the optimization portion of the work no later than May 1, 2028, and begin implementation in accordance with its schedule.	
Submit Compliance Plan. Dischargers shall describe proposed improvements and provide an implementation schedule for major milestones for the compliance pathway identified above, including a schedule for design and construction of improvements.	April 1, 2027 ^[1]
If a Discharger chooses to implement a Multi-Benefit Solution consistent with Provision 6.3.5, it shall submit a governance plan that documents partnerships and a memorandum of understanding or agreement among parties to implement nature-based solutions (e.g., land ownership and funding partnerships) or wastewater recycling (e.g., agreement between wastewater agencies, water purification entity, water contractors).	
Submit Design Progress Report. If a Discharger intends to implement a capital project, such as sidestream, split-stream, or full-scale treatment, to comply with the final effluent limits in Table 4, it shall provide project details for each capital project, including a project description, estimated nutrient removal from the project, evidence that the planned improvements have moved into the design stage, the percent completion of the design, an updated implementation schedule, estimated capital costs, a financial assessment, and a funding strategy.	April 1, 2028 ^[1]
Submit Design Progress Report and Compliance Update. Dischargers shall summarize their progress toward meeting the final effluent limits in Table 4 and provide a status update regarding	April 1, 2029 ^[1]

Table 5. Compliance Schedule Milestones

implementation of their compliance pathway and an updated	
implementation schedule. If a Discharger is implementing a capital	
project, it shall provide a status update on its progress from the	
previous year, including, at minimum, the percent completion of the	
design, the status of contract documents used to bid projects, and an	
updated implementation schedule for the capital project.	

Footnote:

- 6.3.3.2. Summary of changes to the project plans and design and construction schedules listed in the previous year's update and rationale for the changes along with any additional plans for nitrogen reductions if current planned projects will not achieve the final effluent limits in Table 4.
- 6.3.3.3. Notification of the Discharger's compliance or noncompliance with this provision.
- 6.3.4. **Regional Planning to Reduce Total Inorganic Nitrogen Loads.** The Dischargers listed in Table 4 and designated as "major" in Table 1 shall, individually or in collaboration with other regional stakeholders, develop a report that describes regionwide planning efforts to meet the final effluent limitations required by the end of the compliance schedule established through this permit. The report will complement individual reporting required by Provision 6.3.3 and provide a regionwide perspective toward ensuring compliance is achieved as soon as possible. The report shall include the following:
 - a. Regional schedule that lays out the phasing of identified future projects;
 - b. Identification of anticipated capital, operation, and maintenance costs of proposed projects, to the extent feasible for the level of planning;
 - c. Description of anticipated financing alternatives and impacts on agency rates (i.e., the cost to the community) associated with the identified projects;
 - d. Assessment of the impact of the proposed projects on other regulations or requirements (e.g., air and biosolids regulations);
 - e. Identification of nutrient reduction projects that would occur beyond the compliance schedule established in Provision 6.3.3 (with a focus on recycled water and nature-based solution projects) with the potential to reduce baywide total inorganic nitrogen load to below 22,000 kg/day and below 17,600 kg/day (50 percent and 60 percent reduction from 2022 total inorganic nitrogen load); and

⁽¹⁾ The compliance date for this task shall be extended by one year if a Discharger experiences significant delays related to (1) the need to conduct pilot studies prior to design, (2) unsuccessful pilot studies that cause the Discharger to change course, (3) the need to develop agreements to pursue water recycling or nature-based solutions, (4) legal challenges, or (5) engineering challenges that are beyond the Discharger's control. The Discharger shall notify the Executive Officer at least 90 days before the deadline and provide documentation that it satisfies one of the conditions for an extension above.

- f. Nutrient trading program, if Dischargers seek to engage in trading³, consistent with U.S. EPA's *Water Quality Trading Policy* (January 13, 2003) to facilitate achieving total inorganic nitrogen load reductions in Table 4. The proposed trading program should evaluate baywide and subembayment trading allowances that are supported by the best available science.
- 6.3.4.1. **Scoping Plan.** By July 1, 2025, the Dischargers shall, individually or in collaboration with regional stakeholders, submit a Scoping Plan describing the work proposed to develop the Final Report required below.
- 6.3.4.2. **Status Reports.** By July 1, 2026, and again by July 1, 2027, the Dischargers shall submit, or cause to be submitted, a status report describing the tasks completed and preliminary findings.
- 6.3.4.3. **Final Report.** By March 31, 2029, the Dischargers shall submit, or cause to be submitted, a Final Report describing the results of their evaluations.
- 6.3.5. **Multi-Benefit Solutions for Load Reductions.** Dischargers that identify longterm multi-benefit solutions⁴ (e.g., water recycling or nature-based solutions) that cannot be completed by the effective date of the final effluent limitations in Table 4 shall identify such projects by, and their intent to pursue and implement them, as required by Provision 6.3.3.1, including the due dates in Table 5. If these projects result in total inorganic nitrogen loads at or below the individual final effluent limitations in Table 4, the Regional Water Board will consider available regulatory mechanisms to provide more time to comply as explained in the Fact Sheet.

Dischargers pursuing long-term multi-benefit solutions shall satisfy the requirements in Provision 6.3.3.

6.3.6. **Recognition of Early Actors**. Dischargers that have already completed or begun construction or implementation of projects to reduce total inorganic nitrogen discharges to San Francisco Bay by the effective date of this Order may qualify as early actors. These Dischargers shall provide updates with each

³ Water quality trading is a market-based approach that offers efficiency in achieving water quality improvements on a watershed basis. With more stringent limits for total inorganic nitrogen, water quality trading would allow one Discharger to control nitrogen at levels greater than required and sell "credits" to another Discharger, which would use the credits to supplement its level of treatment to comply with final effluent limitations. Trading capitalizes on economies of scale and the control cost differentials between and among sources.

⁴ Multi-benefit solutions refer to initiatives that incorporate nature-based solutions, such as horizontal levees, open water treatment wetlands, or wastewater recycling (both potable and non-potable). These projects are designed to reduce nutrient loads while also providing other benefits, such as enhancing flood control, increasing water supply, or improving habitat quality.

Annual Nutrients Report required by MRP section 5.2.2. Upon completion of these projects, if a Discharger's total inorganic nitrogen loads are above the individual final effluent limitations in Table 4, the Regional Water Board will consider available regulatory mechanisms to provide more time to comply as explained in Fact Sheet section 6.3.5.

6.3.7. **Report of Waste Discharge.** Each Discharger shall file a report of waste discharge as an application for updated WDRs in accordance with title 23, California Code of Regulations, section 2235.1 and an application for reissuance of a National Pollutant Discharge Elimination System (NPDES) permit no later than March 31, 2029. To comply with this requirement, each Discharger may reference the date its individual permit application was submitted for reissuance of its individual permit. Additionally, each Discharger's application for permit reissuance must include nutrient data required by this Order. This requirement may also be satisfied by referencing individual self-monitoring reports. Alternatively, the Dischargers may choose to submit a collective report of waste discharge by including the above information for each Discharger covered by this Order in one application.

ATTACHMENT A – DEFINITIONS AND ABBREVIATIONS

DEFINITIONS

Arithmetic Mean (µ)

Also called the average, sum of measured values divided by the number of samples. For ambient water concentrations, the arithmetic mean is calculated as follows:

Arithmetic mean = μ = $\Sigma x / n$

where: Σx is the sum of the measured ambient water concentrations, and n is the number of samples

Bioaccumulative

Taken up by an organism from its surrounding medium through gill membranes, through epithelial tissue, or from food and subsequently concentrated and retained in the body of the organism.

Calendar Month(s)

Period from the first day of a month through the last day of a month (e.g., January 1 to January 31). For toxicity monitoring, the period is from the first day of a routine monitoring test to the day before the corresponding day of the next month (e.g., from June 15 to July 14), or to the last day of the next month if there is no corresponding day (e.g., January 31 to February 28).

Carcinogenic

Known to cause cancer in living organisms.

Daily Discharge

Either: (1) the total mass of a constituent discharged over a calendar day (12:00 a.m. through 11:59 p.m.) or any 24-hour period that reasonably represents a calendar day for purposes of sampling (as specified in the permit) for a constituent with limitations expressed in units of mass; or (2) the unweighted arithmetic mean measurement of a constituent over a day for a constituent with limitations expressed in other units of measurement (e.g., concentration).

The daily discharge may be determined by the analytical results of a composite sample taken over the course of one day (a calendar day or other 24-hour period defined as a day) or by the arithmetic mean of analytical results from one or more grab samples taken over the course of the day.

For composite sampling, if 1 day is defined as a 24-hour period other than a calendar day, the analytical result for the 24-hour period is considered the result for the calendar day in which the 24-hour period ends.

Detected, but Not Quantified (DNQ)

Sample results less than the RL, but greater than or equal to the laboratory's MDL. Sample results reported as DNQ are estimated concentrations.

ATTACHMENT A — DEFINITIONS AND ABBREVIATIONS

Dilution Credit

Amount of dilution granted to a discharge in the calculation of a water quality-based effluent limitation, based on the allowance of a specified mixing zone. It is calculated from the dilution ratio or determined through conducting a mixing zone study or modeling of the discharge and receiving water.

Enclosed Bays

Indentations along the coast that enclose an area of oceanic water within distinct headlands or harbor works. Enclosed bays include all bays where the narrowest distance between the headlands or outermost harbor works is less than 75 percent of the greatest dimension of the enclosed portion of the bay. Enclosed bays include, but are not limited to, Humboldt Bay, Bodega Harbor, Tomales Bay, Drake's Estero, San Francisco Bay, Morro Bay, Los Angeles-Long Beach Harbor, Upper and Lower Newport Bay, Mission Bay, and San Diego Bay. Enclosed bays do not include inland surface waters or ocean waters.

Estimated Chemical Concentration

Concentration that results from the confirmed detection of a substance below the ML by the analytical method.

Estuaries

Waters, including coastal lagoons, located at the mouths of streams that serve as areas of mixing for fresh and ocean waters. Coastal lagoons and mouths of streams that are temporarily separated from the ocean by sandbars shall be considered estuaries. Estuarine waters are considered to extend from a bay or the open ocean to a point upstream where there is no significant mixing of fresh water and seawater. Estuarine waters included, but are not limited to, the Sacramento-San Joaquin Delta, as defined in Water Code section 12220; Suisun Bay; Carquinez Strait downstream to the Carquinez Bridge; and appropriate areas of the Smith, Mad, Eel, Noyo, Russian, Klamath, San Diego, and Otay rivers. Estuaries do not include inland surface waters or ocean waters.

Inland Surface Waters

All surface waters of the state that are not the ocean, enclosed bays, or estuaries.

Instantaneous Maximum Effluent Limitation

Highest allowable value for any single grab sample or aliquot (i.e., each grab sample or aliquot is independently compared to the instantaneous maximum limitation).

Instantaneous Minimum Effluent Limitation

Lowest allowable value for any single grab sample or aliquot (i.e., each grab sample or aliquot is independently compared to the instantaneous minimum limitation).

Median

Middle measurement in a data set. The median of a data set is found by first arranging the measurements in order of magnitude (either increasing or decreasing order). If the number of measurements (n) is odd, then the median = $X_{(n+1)/2}$. If n is even, then the median = $(X_{n/2} + X_{(n/2+1)})/2$ (i.e., the midpoint between n/2 and n/2+1).

Method Detection Limit (MDL)

Minimum concentration of a substance that can be reported with 99 percent confidence that the measured concentration is distinguishable from method blank results, as defined in 40 C.F.R. part 136, Appendix B.

Minimum Level (ML)

Concentration at which the entire analytical system must give a recognizable signal and acceptable calibration point. The ML is the concentration in a sample that is equivalent to the concentration of the lowest calibration standard analyzed by a specific analytical procedure, assuming that all the method specified sample weights, volumes, and processing steps have been followed.

Mixing Zone

Limited volume of receiving water allocated for mixing with a wastewater discharge where water quality criteria can be exceeded without causing adverse effects to the overall water body.

Not Detected (ND)

Sample results less than the laboratory's MDL.

Persistent Pollutants

Substances for which degradation or decomposition in the environment is nonexistent or very slow.

Pollutant Minimization Program

Program of waste minimization and pollution prevention actions that include, but are not limited to, product substitution, waste stream recycling, alternative waste management methods, and education of the public and businesses. The goal of a Pollutant Minimization Program is to reduce all potential sources of a priority pollutant through pollutant minimization (control) strategies, including pollution prevention measures as appropriate, to maintain the effluent concentration at or below the water quality-based effluent limitation. Pollution prevention measures may be particularly appropriate for persistent bioaccumulative priority pollutants where there is evidence that beneficial uses are being impacted. Cost effectiveness may be considered when establishing the requirements of a Pollutant Minimization Program. The completion and implementation of a Pollution Prevention Plan, if required pursuant to Water Code section 13263.3(d), is considered to fulfill the Pollutant Minimization Program requirements.

Pollution Prevention

Any action that causes a net reduction in the use or generation of a hazardous substance or other pollutant discharged into water and includes, but is not limited to, input change, operational improvement, production process change, and product reformulation (as defined in Water Code section 13263.3). Pollution prevention does not include actions that merely shift a pollutant in wastewater from one environmental medium to another environmental medium, unless clear environmental benefits of such an approach are identified to the satisfaction of the State Water Resources Control Board or Regional Water Board.

Regulatory Management Decision (RMD)

Decision that represents the maximum allowable error rates and thresholds for toxicity and non-toxicity that would result in an acceptable risk to aquatic life.

Reporting Level (RL)

ML (and its associated analytical method) chosen by the Discharger for reporting and compliance determination from the MLs included in this Order, including an additional factor if applicable as discussed herein. For priority pollutants, the MLs included in this Order correspond to approved analytical methods for reporting a sample result that are selected by the Regional Water Board either from State Implementation Plan (SIP) Appendix 4 in accordance with SIP section 2.4.2 or established in accordance with SIP section 2.4.3. The ML is based on the proper application of method-based analytical procedures for sample preparation and the absence of any matrix interferences. Other factors may be applied to the ML depending on the specific sample preparation steps employed. For example, the treatment typically applied in cases where there are matrix-effects is to dilute the sample or sample aliquot by a factor of ten. In such cases, this additional factor must be applied to the ML in the computation of the RL.

Source of Drinking Water

Any water designated as municipal or domestic supply (MUN) beneficial use.

Standard Deviation (σ)

Measure of variability calculated as follows:

Standard deviation = $\sigma = (\Sigma[(x - \mu)^2]/(n - 1))^{0.5}$

where: x is the observed value µ is the arithmetic mean of the observed values n is the number of samples

ABBREVIATIONS

°F	degrees Fahrenheit
°C	degrees Celsius
%	Percent
µg/L	Micrograms per liter
1/Discharge	Once per discharge
1/Day	Once per day
1/Month	Once per month
1/Quarter	Once per quarter
1/Week	Once per week
1/Year	Once per year
2/Month	Two times per month

ATTACHMENT A — DEFINITIONS AND ABBREVIATIONS

2/Week	Twice per week
2/Year	Twice per year
В	Background concentration
С	Water quality criterion or objective
C-24	24-hour composite
CIWQS	California Integrated Water Quality System
Continuous	Measured continuously
Continuous/D	Measured continuously, and recorded and reported daily
Continuous/H	Measured continuously, and recorded and reported hourly
CTR	California Toxics Rule
CV	Coefficient of Variation
DMR	Discharge Monitoring Report
DNQ	Detected, but not quantified
DL	Detection level
ECA	Effluent Concentration Allowance
Grab	Grab sample
MDL	Method detection limit
MEC	Maximum effluent concentration
MG	Million gallons
mg/L	Milligrams per liter
mg/L as N	Milligrams per liter as nitrogen
MGD	Million gallons per day
ML	Minimum level
MRP	Monitoring and Reporting Program (Attachment E)
ND	Not detected
NTR	National Toxics Rule
NTU	Nephelometric turbidity units
ppt	Parts per thousand
RL	Reporting level
RPA	Reasonable potential analysis
SIP	Policy for Implementation of Toxics Standards for Inland Surface Waters, Enclosed Bays, and Estuaries of California (State Implementation Policy)

San Francisco Bay Nutrients Watershed Permit Municipal Wastewater Dischargers

SMR	Self-Monitoring Report
s.u.	Standard pH units
WDRs	Waste discharge requirements
WQBEL	Water quality-based effluent limitation

ATTACHMENT B - INDIVIDUAL NPDES PERMITS AND ORDER NUMBERS

Discharger	Individual NPDES Permit	Individual Order	Effective Date	Expiration Date
American Canyon, City of	CA0038768	R2-2022-0019	8/01/2022	7/31/2027
Benicia, City of	CA0038091	R2-2019-0034	2/01/2020	1/31/2025
Burlingame, City of	CA0037788	R2-2023-0010	1/01/2024	12/31/2028
Central Contra Costa Sanitary District	CA0037648	R2-2022-0020	8/01/2022	7/31/2027
Central Marin Sanitation Agency	CA0038628	R2-2023-0006	7/01/2023	6/30/2028
Crockett Community Services District	CA0037885	R2-2024-0009	8/01/2024	7/31/2029
Delta Diablo	CA0038547	R2-2019-0035	2/01/2020	1/31/2025
East Bay Dischargers Authority (EBDA)				
City of Hayward				
City of San Leandro	CA0038769	R2-2022-0023	9/01/2022	8/31/2027
Oro Loma Sanitary District and Castro Valley Sanitary District				
Union Sanitary District				
Livermore-Amador Valley Water Management Agency	CA0038679	R2-2021-0007	7/01/2021	6/30/2026
City of San Leandro – Treatment Wetland	CA0038881	R2-2022-0006	6/01/2022	5/31/2027
Oro Loma Sanitary District and Castro Valley Sanitary District – Wet Weather	CA0037559	R2-2024-0006	6/01/2024	5/31/2029
Union Sanitary District – Wet Weather	CA0038733	R2-2020-0027	12/01/2020	11/30/2025
Dublin San Ramon Services District	CA0037613	R2-2022-0024	9/01/2022	8/31/2027
City of Livermore	CA0038008	R2-2022-0025	9/01/2022	8/31/2027
East Bay Municipal Utility District	CA0037702	R2-2020-0024	11/01/2020	10/31/2025
Fairfield-Suisun Sewer District	CA0038024	R2-2020-0012	5/01/2020	4/30/2025
Las Gallinas Valley Sanitary District	CA0037851	R2-2020-0022	9/01/2020	8/31/2025
Marin County (Paradise Cove), Sanitary District No. 5 of	CA0037427	R2-2021-0017	12/01/2021	11/30/2026
Marin County (Tiburon), Sanitary District No. 5 of	CA0037753	R2-2023-0018	12/01/2023	11/30/2028
Millbrae, City of	CA0037532	R2-2024-0005	5/01/2024	4/30/2029
Mt. View Sanitary District	CA0037770	R2-2021-0026	2/01/2022	1/31/2027
Napa Sanitation District	CA0037575	R2-2022-0003	4/01/2022	3/31/2027
Novato Sanitary District	CA0037958	R2-2020-0019	9/01/2020	8/31/2025
Palo Alto, City of	CA0037834	R2-2019-0015	6/1/2019	5/31/2024
Petaluma, City of	CA0037810	R2-2021-0008	7/01/2021	6/30/2026
Pinole, City of	CA0037796	R2-2023-0008	8/01/2023	7/31/2028
Rodeo Sanitary District	CA0037826	R2-2022-0037	2/01/2023	1/31/2028

Discharger	Individual NPDES Permit	Individual Order	Effective Date	Expiration Date
San Francisco (San Francisco International Airport), City and County of	CA0038318	R2-2018-0045	12/01/2018	11/30/2023
San Francisco (Southeast Plant), City and County of	CA0037664	R2-2013-0029	10/01/2013	9/30/2018
San Jose and Santa Clara, Cities of	CA0037842	R2-2020-0001	4/01/2020	3/31/2025
San Mateo, City of	CA0037541	R2-2023-0017	12/01/2023	11/30/2028
Sausalito-Marin City Sanitary District	CA0038067	R2-2023-0022	1/01/2024	12/31/2028
Sewerage Agency of Southern Marin	CA0037711	R2-2023-0021	1/01/2024	12/31/2028
Silicon Valley Clean Water	CA0038369	R2-2023-0003	5/01/2023	4/30/2028
Sonoma Valley County Sanitation District	CA0037800	R2-2019-0019	9/01/2019	8/31/2024
South San Francisco and San Bruno, Cities of	CA0038130	R2-2019-0021	9/01/2019	8/31/2024
Sunnyvale, City of	CA0037621	R2-2020-0002	4/01/2020	3/31/2025
Treasure Island Development Authority	CA0110116	R2-2020-0020	8/01/2020	7/31/2025
Vallejo Flood and Wastewater District	CA0037699	R2-2023-0001	4/01/2023	3/31/2028
West County Agency				
West County Wastewater District	CA0038539	R2-2024-0008	8/01/2024	7/31/2029
City of Richmond and Richmond Municipal Sewer District	070000000	112-2024-0000	0,01/2024	110112029

ATTACHMENT C - MAP OF MUNICIPAL DISCHARGE LOCATIONS



Municipal Discharger outfall locations

ATTACHMENT D – STANDARD PROVISIONS

Refer to Attachment D in the individual permits listed in Attachment B of this Order.

ATTACHMENT E – MONITORING AND REPORTING PROGRAM

CONTENTS

1.	GENERAL MONITORING PROVISIONS	E-2
2.	MONITORING LOCATIONS	E-2
3.	INFLUENT MONITORING	E-3
4.	EFFLUENT MONITORING	E-3
5.	REPORTING REQUIREMENTS	E-4

TABLES

TABLE E-1. MONITORING LOCATIONS	E-2
TABLE E-2. INFLUENT MONITORING	E-3
TABLE E-3. EFFLUENT MONITORING	E-3
TABLE E-4. MINIMUM SAMPLING FREQUENCIES	E-3
TABLE E-5. MONITORING PERIODS	E-5

ATTACHMENT E – MONITORING AND REPORTING PROGRAM

Clean Water Act (CWA) section 308 and 40 C.F.R. sections 122.41(h), (j)-(l), 122.44(i), and 122.48 require that all NPDES permits specify monitoring and reporting requirements. Water Code section 13383 also authorizes the Regional Water Board to establish monitoring, inspection, entry, reporting, and recordkeeping requirements. This MRP establishes monitoring, reporting, and recordkeeping requirements that implement the federal and state laws and regulations.

1. GENERAL MONITORING PROVISIONS

- 1.1. Dischargers shall comply with this MRP. The Executive Officer may amend this MRP pursuant to 40 C.F.R. section 122.63. If any discrepancies exist between this MRP and the "Regional Standard Provisions, and Monitoring and Reporting Requirements (Supplement to Attachment D) for NPDES Wastewater Discharge Permits" (Attachment G) in the individual permits listed in Attachment B of this Order, this MRP shall prevail.
- 1.2. Sampling is required during the entire year when discharging. Dischargers shall conduct all monitoring in accordance with Attachment D section 3, as supplemented by Attachment G of the individual permits listed in Attachment B. Equivalent test methods must be more sensitive than those specified in 40 C.F.R. section 136 and must be specified in this permit.

2. MONITORING LOCATIONS

Dischargers shall establish the following monitoring locations to demonstrate compliance with the effluent limitations, discharge specifications, and other requirements of this Order:

Discharge Point	Monitoring Location	Monitoring Location Description
Influent	Individual monitoring locations for influent wastewater (normally Monitoring Location INF-001) are specified in the MRPs of the individual NPDES permits listed in Attachment B of this Order. ^[1]	Individual monitoring location descriptions are provided in the MRPs of the individual NPDES permits listed in Attachment B of this Order.
Effluent	Individual monitoring locations for discharges of treated wastewater (normally Monitoring Location EFF-001) are specified in the MRPs of the individual NPDES permits listed in Attachment B of this Order. ^[2]	Individual monitoring location descriptions are provided in the MRPs of the individual NPDES permits listed in Attachment B of this Order.

Table E-1. Monitoring Locations

Footnotes:

^[1] For the City and County of San Francisco (Southeast Plant), influent monitoring shall occur only during dry weather (i.e., not during wet weather as defined in its individual NPDES permit as listed in Attachment B).

^[2] For the City and County of San Francisco (Southeast Plant), the monitoring location shall be Monitoring Location EFF-001A. For the Fairfield-Suisun Sewer District, the monitoring location shall be Monitoring Location EFF-001D.

3. INFLUENT MONITORING

Dischargers with a design flow \geq 10 MGD, as described in Fact Sheet Table F-1, shall monitor treatment plant influent (typically at Monitoring Location INF-001) as shown in Tables E-2 and E-4, below.

	•	
Parameter [1]	Unit	Sample Type ^[2]
Ammonia, Total	mg/L and kg/day as N	C-24
Total Kjeldahl Nitrogen (TKN)	mg/L and kg/day as N	C-24
Nitrate-Nitrite ^[3]	mg/L and kg/day as N	C-24
Phosphorus, Total	mg/L and kg/day as p	C-24

Footnotes:

- ^[1] Influent samples shall be collected concurrently with effluent samples.
- ^[2] 24-hour composites may be made up of four discrete grab samples collected over a 24-hour period and volumetrically or mathematically flow-weighed. During a 24-hour period, the samples may be collected only when the plant is staffed, if necessary.
- ^[3] If two years of monitoring data show all nitrate-nitrite concentrations a Discharger measures are below 2.0 mg/L, the Discharger may discontinue influent monitoring for this parameter.

4. EFFLUENT MONITORING

Dischargers shall monitor treatment plant effluent (typically at Monitoring Location EFF-001) as follows:

		•
Parameter	Unit	Sample Type ^[1]
Ammonia, Total	mg/L and kg/day as N	C-24
Nitrate-nitrite	mg/L and kg/day as N	C-24
Inorganic Nitrogen, Total ^[2]	mg/L and kg/day as N	Calculated
Phosphorus, Total	mg/L and kg/day as p	C-24

Table E-3. Effluent Monitoring

Footnotes:

^[1] The 24-hour composites may be made up of four discrete grab samples collected over a 24-hour period and volumetrically or mathematically flow-weighed. During a 24-hour period, the samples may be collected only when the plant is staffed, if necessary. Monitoring for total ammonia, nitrate-nitrite, and total phosphorus shall be performed on the same day.

^[2] Total Inorganic Nitrogen = Total Ammonia + Nitrate-Nitrite. Dischargers may use approved analytical techniques that require filtration for analyte measurements that comprise Total Inorganic Nitrogen. When calculating total inorganic nitrogen, the Discharger shall assume data reported below the method detection limit equal half of the detection limit.

Discharger Size	Total Ammonia, Nitrate-Nitrite, Influent TKN, Effluent Total Inorganic Nitrogen Sampling Frequencies ^[1,2,3,4]	Total Phosphorous Sampling Frequency ^[1,2,3,4]
Major Dischargers (design flow ≥ 10 MGD)	Twice per month for effluent Once per quarter for influent	Once per month for effluent Twice per year for influent
Major Dischargers (design flow < 10 MGD)	Once per month for effluent	Once per quarter for effluent

Table E-4. Minimum Sampling Frequencies

Discharger Size	Total Ammonia, Nitrate-Nitrite, Influent TKN, Effluent Total Inorganic Nitrogen Sampling Frequencies ^[1,2,3,4]	Total Phosphorous Sampling Frequency ^[1,2,3,4]	
Minor Dischargers (design flow < 1.0 MGD)	Twice per year for effluent ^[5]	Once per year for effluent	

Footnotes:

- ^[1] Samples need only to be collected when discharging (i.e., seasonal Dischargers shall collect samples only during the discharge season). For compliance monitoring (between May 1 and September 30), samples shall be representative of dry season conditions. If effluent flows are higher than normal due to unseasonal wet weather that increases flows to the treatment plant or results in reduced recycled water demand the Discharger shall exclude these results from the dry season average used for compliance determination and shall include documentation in the transmittal letter of its monthly self-monitoring report that explains effluent flows during that period were higher than normal due to wet weather.
- ^[2] Dischargers that discharge through the East Bay Dischargers Authority Common Outfall (i.e., City of Hayward, City of San Leandro, Oro Loma Sanitary District and Castro Valley Sanitary District, Union Sanitary District, City of San Leandro – Treatment Wetland, and Dublin San Ramon Services District, and City of Livermore) shall monitor their individual wastewater treatment plant influent and effluent at least once per quarter.
- ^[3] Dischargers that discharge through the West County Agency Combined Outfall (i.e., West County Wastewater District and City of Richmond and Richmond Municipal Sewer District) shall monitor their individual wastewater treatment plant influent and effluent at least once per quarter.
- ^[4] The Livermore-Amador Valley Water Management Agency is not required to monitor influent or effluent, and neither the Union Sanitary District nor the Oro Loma Sanitary District is required to monitor effluent from its wet weather outfall.
- ^[5] Monitoring shall occur during the dry season (May September).

5. REPORTING REQUIREMENTS

5.1. General Monitoring and Reporting Requirements. The Dischargers shall comply with all Standard Provisions (Attachments D and G of the individual NPDES permits) related to monitoring, reporting, and recordkeeping.

5.2. Individual Reporting in Self-Monitoring Reports (SMRs)

- 5.2.1. **Routine SMRs.** The Dischargers shall submit nutrients data collected to comply with this Order in the routine monthly or quarterly SMRs required by each Discharger's individual NPDES permit. Each SMR shall include all new nutrients monitoring results obtained since the last SMR was submitted. If a Discharger monitors nutrients more frequently than required by this Order at a monitoring location described in Table E-1, it shall include the results of such monitoring in the calculations and reporting for the relevant SMR.
- 5.2.2. **Annual Nutrients Report.** By January 1 of each year, each Discharger shall provide its nutrient information in a separate annual report or state that it is participating in a group report the Bay Area Clean Water Agencies (BACWA) will submit pursuant to Provision 5.2.2.5, below. Each Discharger shall submit the following:
- 5.2.2.1. Documentation that the Discharger is complying with Provisions 6.3.2, 6.3.3, 6.3.5, and 6.3.6 of the Order. If reporting through a group report as described below, the Discharger shall submit certification that it has provided adequate support (i.e., contributed its portion of the required contribution) in accordance with Provision 6.3.2.

- 5.2.2.2. Summary tables depicting the Discharger's annual and monthly flows, nutrient concentrations, and nutrient mass loads, calculated as described in Attachment G section 8.1 (Arithmetic Calculations) of individual NPDES permits. The summary tables shall cover October 1 before the preceding year through September 30 of the preceding year and at least the previous five years of available data. Each Discharger shall document its nutrient loads relative to other facilities covered by this Order that discharge into the same subembayment (i.e., Suisun Bay, San Pablo Bay, Central Bay, South Bay, and Lower South Bay). These subembayment delineations may be refined through Provision 6.3.2 of the Order, in which case each Discharger shall document loads relative to the most recent delineation. Nutrient data from other Dischargers may be obtained from the State Water Board's California Integrated Water Quality System (CIWQS) website (https://www.waterboards.ca.gov/ciwqs/index.html).
- 5.2.2.3. Analysis of nutrient trends and load variability, and assessment as to whether nutrient mass loads are increasing or decreasing.
- 5.2.2.4 A summary of the amount of water recycled annually by the Discharger, the corresponding decrease in the level of nutrients discharged to the Bay, and any updates to future water recycling plans.
- 5.2.2.5. Status and plans for investigation if the trend analysis shows a significant change in nutrient loading. In such cases, the Discharger shall investigate the cause. In the annual reports, the Discharger shall set forth its plans for investigation and report its results, providing necessary updates in subsequent annual reports. The investigation shall include, at a minimum, whether treatment process changes, increasing or decreasing water reclamation, or changes in total influent flow related to water conservation, population growth, transient work community, new industry, or wet weather flows have reduced or increased nutrient discharges.

As an alternative to submitting an individual Annual Nutrients Report, each Discharger may instead participate in a group report to be submitted by BACWA. By April 1 of each year, the Annual Group Nutrients Report shall include the information detailed in this provision.

5.2.3. **Monitoring Periods.** Monitoring periods for all required monitoring shall be as set forth below unless otherwise specified:

Sampling Frequency	Monitoring Period Begins On	Monitoring Period
Continuous/D	Order effective date	All times
1/Week	First Sunday following or on Order effective date	Sunday through Saturday

Table E-5. Monitoring Periods

Sampling Frequency	Monitoring Period Begins On	Monitoring Period
1/Month	First day of calendar month following or on Order effective date	First day of calendar month through last day of calendar month
1/Quarter	Closest January 1, April 1, July 1, or October 1 before or after Order effective date ^{[1][2]}	January 1 through March 31 April 1 through June 30 July 1 through September 30 October 1 through December 31
1/Year	Closest January 1 before or after Order effective date ^[1]	January 1 through December 31
2/Year	Closest January 1 before or after Order effective date ^[1]	January 1 through June 30 July 1 through December 31

Footnote:

^[1] Monitoring performed during the previous order term may be used to satisfy monitoring required by this Order.

^[2] Definitions of 1/Quarter in the individual NPDES permits listed in Attachment B of this Order supersede this definition.

- 5.2.4. **RL and MDL Reporting.** The Discharger shall report with each sample result the Reporting Level (RL) and Method Detection Limit (MDL) as determined by the procedure in 40 C.F.R. part 136. The Dischargers shall report the results of analytical determinations for the presence of chemical constituents in a sample using the following reporting protocols:
- 5.2.4.1. Sample results greater than or equal to the RL shall be reported as measured by the laboratory (i.e., the measured chemical concentration in the sample).
- 5.2.4.2. Sample results less than the RL, but greater than or equal to the laboratory's MDL, shall be reported as "Detected, but Not Quantified," or DNQ. The estimated chemical concentration of the sample shall also be reported.

For purposes of data collection, the Dischargers shall require the laboratory to write the estimated chemical concentration next to DNQ. The laboratory may, if such information is available, include numerical estimates of the data quality for the reported result. Numerical estimates of data quality may be percent accuracy (± a percentage of the reported value), numerical ranges (low to high), or any other means the laboratory considers appropriate.

- 5.2.5.3. Sample results less than the laboratory's MDL shall be reported as "Not Detected", or ND.
- 5.2.5.4. The Dischargers shall instruct laboratories to establish calibration standards so that the minimum level (ML) value (or its equivalent if there is differential treatment of samples relative to calibration standards) is the lowest calibration standard. At no time is any Discharger to use analytical data derived from extrapolation beyond the lowest point of the calibration curve.

5.2.6. **Compliance Determination.** Compliance with effluent limitations shall be determined using sample reporting protocols defined above, in the Fact Sheet, in Attachment A, and in Attachments D and G of each individual permit. For purposes of reporting and enforcement, a Discharger shall be deemed out of compliance with interim effluent limitations if the average dry season (May 1 through September 30) mass load of total inorganic nitrogen in the dry season monitoring samples is greater than its individual effluent limitation.

For purposes of reporting and enforcement, a Discharger shall be deemed out of compliance with final effluent limitations if the average dry season mass load of the total inorganic nitrogen in dry season monitoring samples is greater than its effluent limitation and if the sum of all individual Dischargers' total inorganic nitrogen mass loads is greater than the Aggregate Mass Load Limit.

5.3. Discharge Monitoring Reports (DMRs). DMRs are U.S. EPA reporting requirements. The Dischargers shall electronically certify and submit DMRs together with SMRs using Electronic Self-Monitoring Reports module eSMR 2.5 or the latest upgraded version. Electronic DMR submittal shall be in addition to electronic SMR submittal. Information about electronic DMR submittal is available at the <u>DMR website</u>

(waterboards.ca.gov/water_issues/programs/discharge_monitoring).

ATTACHMENT F – FACT SHEET

CONTENTS

1.	PERMIT INFORMATION	F-2
2.	FACILITY DESCRIPTIONS	F-9
3.	APPLICABLE PLANS, POLICIES, AND REGULATIONS	F-15
4.	RATIONALE FOR EFFLUENT LIMITATIONS AND DISCHARGE SPECIFICA	TIONS.F-17
4	 4.1. WATER QUALITY-BASED EFFLUENT LIMITATIONS	F-17 F-17 F-17 F-17 F-18 F-20 F-27 F-27 F-27 F-30 F-31
5.	RATIONALE FOR RECEIVING WATER LIMITATIONS	F-34
6.	RATIONALE FOR PROVISIONS	F-34
6	 STANDARD PROVISIONS	F-34 F-35 F-35 F-35 F-36 F-36 F-36 F-37 F-38 F-39
7.	RATIONALE FOR MONITORING AND REPORTING REQUIREMENTS	F-39
8.	PUBLIC PARTICIPATION	F-39

TABLES

TABLE F-1. FACILITY INFORMATION	F-2
TABLE F-2. ADDITIONAL FACILITY INFORMATION	F-5
TABLE F-3. CURRENT AND PROJECTED WATER RECYCLING	. F-12
TABLE F-4. AVERAGE ANNUAL DRY SEASON TOTAL INORGANIC NITROGEN	. F-14
TABLE F-5. DRY SEASON AVERAGE TOTAL INORGANIC NITROGEN	. F-18

ATTACHMENT F – FACT SHEET

This Fact Sheet includes the legal requirements and technical rationale that serve as the basis for the requirements of this Order. As described in the findings of the Order, the Regional Water Board incorporates this Fact Sheet as findings supporting the issuance of the Order.

1. PERMIT INFORMATION

The following tables summarize administrative information related to each Discharger's facility.

Discharger	Facility Contact, Title, and Phone	Mailing Address	Effluent Description	Facility Design Flow (MGD)
American Canyon, City of	Pam Phillips Environmental Services Manager (707) 647-4544	151 Mezzetta Court American Canyon, CA 94503 Napa County	Advanced Secondary	2.5
Benicia, City of	Jeff Gregory Wastewater Treatment Plant Superintendent (707) 746-4336	614 East Fifth Street Benicia, CA 94510 Solano County	Secondary	4.5
Burlingame, City of	Manuel Molina General Manager (650) 342-3727	501 Primrose Road Burlingame, CA 94010 San Mateo County	Secondary	5.5
Central Contra Costa Sanitary District	Lori Schectel Env. Compliance Manager (925) 229-7143	5019 Imhoff Place Martinez, CA 94553 Contra Costa County	Secondary	53.8
Central Marin Sanitation Agency	Chris Finton Treatment Plant Manager (415) 459-1455 x101	1301 Andersen Drive San Rafael, CA 94901 Marin County	Secondary	10
Crockett Community Services District	James Barnhill Sanitary Department Manager (510) 787-2992	P.O. Box 578 Crockett, CA 94525 Contra Costa County	Secondary	0.033
Delta Diablo	Amanda Roa Environmental Programs Manager (925) 756-1940	2500 Pittsburg-Antioch Highway Antioch, CA 94509 Contra Costa County	Secondary	19.5
East Bay Dischargers Authority (EBDA)				
City of Hayward	Jacqueline Zinkin	2651 Grant Avenue San		
City of San Leandro General Manager		Lorenzo, CA 94580	Secondary	107.8
Oro Loma Sanitary District and Castro Valley Sanitary District	(510) 278-591Ō	Alameda County		
Union Sanitary District				

Table F-1. Facility Information
Discharger	Facility Contact, Title, and Phone	Mailing Address	Effluent Description	Facility Design Flow (MGD)
Livermore-Amador Valley Water Management Agency				
Dublin San Ramon Services District				
City of Livermore				
East Bay Municipal Utility District	Donald Gray Senior EH&S Specialist (925) 640-4738	P.O. Box 24055 Oakland, CA 94623-1055 Alameda County	Secondary	120
Fairfield-Suisun Sewer District	Meg Herston Director of Environmental Services (707) 428-9109	1010 Chadbourne Road Fairfield, CA 94534 Solano County	Advanced Secondary	23.7
Las Gallinas Valley Sanitary District	Valley trictMel Liebmann Chief Plant Operator (415) 472-1734300 Smith Ranch Road San Rafael, CA 94903 Marin County		Secondary	2.92
Marin County (Paradise Cove), Sanitary District No. 5 of	County (ParadiseTony RubioP.O. Box 227a), Sanitary DistrictDistrict ManagerTiburon, CA 94920b) of(415) 435-1501Marin County		Secondary	0.04
Marin County (Tiburon), Sanitary District No. 5 of	Tony Rubio2001 Paradise DriveDistrict ManagerTiburon, CA 94920(415) 435-1501Marin County		Secondary	0.98
Millbrae, City of	City of Sam Bautista 6 Public Works Director M (650) 259-2347 5		Secondary	3.0
Mt. View Sanitary District	w Sanitary District Lilia Corona P.O. Box (925) 228-5635 ext. 18 Contra C		Advanced Secondary	3.2
Napa Sanitation District	Napa Sanitation District Andrew Damron General Manager (707) 258-6007		Secondary	15.4
Novato Sanitary District	Novato Sanitary District Sandeep Karkal 500 Da General Manager-Chief Engineer Novato (415) 892-1694 Marin (Secondary	7.0
Palo Alto, City of Plant Manager (650) 329-2243		2501 Embarcadero Way, Palo Alto, CA 94303 Santa Clara County	Advanced Secondary	39
Petaluma, City of	Matthew Pierce Operations Supervisor (707) 776-3726	202 N. McDowell Blvd. Petaluma, CA 94954 Sonoma County	Secondary	6.7
Pinole, City of	Josh Binder Plant Manager (510) 724-8964	2131 Pear Street, Pinole, CA 94564 Contra Costa County	Secondary	4.06
Rodeo Sanitary District	eo Sanitary District District Manager (510) 799-2970 ext. 100		Secondary	1.14

Discharger	Facility Contact, Title, and Phone Mailing Address		Effluent Description	Facility Design Flow (MGD)
San Francisco (San Francisco International Airport), City and County of	Jennifer Acton Env. Operations Manager (650) 455-9241	P.O. Box 8097 San Francisco, CA 94128 San Mateo County	Secondary	2.2
San Francisco (Southeast Plant), City and County of	Amy Chastain Regulatory Manager (415) 554-1683	1155 Market St., 11th Floor San Francisco, CA 94103 San Francisco County	Secondary	85.4
San Jose and Santa Clara, Cities of	Eric Dunlavey Wastewater Compliance Program Manager (408) 635-4017	700 Los Esteros Road San Jose, CA 95134 Santa Clara County	Advanced Secondary	167
San Mateo, City of	Michael Sutter Operations Superintendent (650) 522-7380	330 West 20 th Avenue San Mateo, CA 94403	Secondary	15.7
Sausalito-Marin City Sanitary District	Jeffrey Kingston General Manager (415) 332-0244	1 East Road Sausalito, CA 94965 Marin County	Secondary	1.8
Sewerage Agency of Southern Marin	Mark Grushayev26 Corte Madera Ave.General ManagerMill Valley, CA 94941(415) 388-2402Marin County		Secondary	3.6
Silicon Valley Clean Water	Monte Hamamoto Chief Operating Officer (650) 832-6266	1400 Radio Road Redwood City, CA 94065 San Mateo County	Secondary	29
Sonoma Valley County Sanitation District	onoma Valley County anitation District Frank Mello Operations Coordinator (707) 521-1843 Sonoma County Water Agency 404 Aviation Blvd. Santa Rosa, CA 95403 Sonoma County		Secondary	3.0
South San Francisco and San Bruno, Cities of	Brian Schumacker Plant Superintendent (650) 829-3844	195 Belle Air Road South San Francisco, CA 94080 San Mateo County		13
Sunnyvale, City of	Rohan Wikramanayake Water Pollution Control Plant Division Manager (781) 491-6177	Sunnyvale Water Pollution Control Plant P.O. Box 3707 Sunnyvale, CA 94088- 3707 Santa Clara County	Advanced Secondary	29.5
Treasure Island Development Authority	Island nent AuthorityAmy Chastain Regulatory Manager (415) 554-16831 Avenue of the Palme Ste 241 San Francisco, CA 94 San Francisco County		Secondary	2.0
Vallejo Flood and Wastewater District	Jennifer Harrington Environmental Services Director (707) 652-7806	450 Ryder Street Vallejo, CA 94590 Solano County	Secondary	15.5
West County Agency			Secondary	28.5

Discharger	Facility Contact, Title, and Phone	Mailing Address	Effluent Description	Facility Design Flow (MGD)
West County Wastewater District	Aaron Winer	2910 Hilltop Drive		
City of Richmond and Richmond Municipal Sewer District	Resource Recovery (510) 837-6223	Richmond, CA 94806 Contra Costa County		

Discharger	Authorized Person to Sign and Submit Reports	Billing Address
American Canyon, City of	Pam Phillips Environmental Services Manager (707) 647-4544	151 Mezzetta Court American Canyon, CA 94503 Napa County
Benicia, City of	Jeff Gregory Wastewater Treatment Plant Superintendent (707) 746-4336	614 East Fifth Street Benicia, CA 94510 Solano County
Burlingame, City of	Manuel Molina General Manager (650) 342-3727	501 Primrose Road Burlingame, CA 94010 San Mateo County
Central Contra Costa Sanitary District	Lori Schectel Env. Compliance Manager (925) 229-7143	5019 Imhoff Place Martinez, CA 94553 Contra Costa County
Central Marin Sanitation Agency	Chris Finton Treatment Plant Manager (415) 459-1455 ext. 101	1301 Andersen Drive San Rafael, CA 94901 Marin County
Crockett Community Services District	James Barnhill Sanitary Department Manager (510) 787-2992	P.O. Box 578 Crockett, CA 94525 Contra Costa County
Delta Diablo	Joaquin Gonzalez Operations Manager (925) 756-1971	2500 Pittsburg-Antioch Highway Antioch, CA 94509 Contra Costa County
East Bay Dischargers Authority (EBDA)		
City of Hayward		
City of San Leandro		
Oro Loma Sanitary District and Castro Valley Sanitary District	Jacqueline Zipkin General Manager	2651 Grant Avenue San Lorenzo, CA
Union Sanitary District	(510) 278-5910	Alameda County
Livermore-Amador Valley Water Management Agency		
Dublin San Ramon Services District		

Table F-2. Additional Facility Information

Discharger	Authorized Person to Sign and Submit Reports	Billing Address	
City of Livermore			
East Bay Municipal Utility District	Amit Mutsuddy Director of Wastewater (510) 287-1407	P.O. Box 24055, MS#59 Oakland, CA 94623- 1055 Alameda County	
Fairfield-Suisun Sewer District	Jordan Damerel Assistant General Manager/District Engineer (707) 428-9155	1010 Chadbourne Road Fairfield, CA 94534 Solano County	
Las Gallinas Valley Sanitary District	Mel Liebmann Chief Plant Operator (415) 472-1734	300 Smith Ranch Road San Rafael, CA 94903 Marin County	
Marin County (Paradise Cove), Sanitary District No. 5 of	Tony Rubio District Manager (415) 435-1501	P.O. Box 227 Tiburon, CA 94920 Marin County	
Marin County (Tiburon), Sanitary District No. 5 of	Tony Rubio District Manager (415) 435-1501	2001 Paradise Drive Tiburon, CA 94920 Marin County	
Millbrae, City of	Craig Centis Deputy Director of Public Works (650) 259-2376	621 Magnolia Avenue Millbrae, CA 94030 San Mateo County	
Mt. View Sanitary District	Stacey Ambrose Environmental Services Manager (925) 228-5635 ext. 12	P.O. Box 2757 Martinez, CA 94553 Contra Costa County	
Napa Sanitation District	Andrew Damron General Manager (707) 258-6007	1515 Soscol Ferry Road Napa, CA 94558 Napa County	
Novato Sanitary District	Sandeep Karkal General Manager-Chief Engineer (415) 892-1694	500 Davidson Street Novato, CA 94945 Marin County	
Palo Alto, City of	James Allen Plant Manager (650) 329-2243	2501 Embarcadero Way, Palo Alto, CA 94303 Santa Clara County	
Petaluma, City of	Matthew Pierce Operations Supervisor (707) 776-3726	202 N. McDowell Blvd. Petaluma, CA 94954 Sonoma County	
Pinole, City of	Josh Binder Plant Manager (510) 724-8964	2131 Pear Street, Pinole, CA 94564 Contra Costa County	
Rodeo Sanitary District	Steve Beall District Manager (510) 799-2970 ext. 100	800 San Pablo Avenue Rodeo, CA 94572 Contra Costa County	
San Francisco (San Francisco International Airport), City and County of	Leroy Sisneros Director of Facilities (650) 821-5400	P.O. Box 8097 San Francisco, CA 94128 San Mateo County	

Discharger	Authorized Person to Sign and Submit Reports	Billing Address
San Francisco (Southeast Plant), City and County of	Andrew Clark Operations Superintendent (415) 920-4944	1155 Market St., 11th Floor San Francisco, CA 94103 San Francisco County
San Jose and Santa Clara, Cities of	Eric Dunlavey Wastewater Compliance Program Manager (408) 635-4017	700 Los Esteros Road San Jose, CA 95134 Santa Clara County
San Mateo, City of	Michael Sutter Operations Superintendent (650) 522-7380	330 West 20 th Avenue San Mateo, CA 94403
Sausalito-Marin City Sanitary District	Jeffrey Kingston General Manager (415) 332-0244	1 East Road Sausalito, CA 94965 Marin County
Sewerage Agency of Southern Marin	Mark Grushayev General Manager (415) 388-2402	26 Corte Madera Ave. Mill Valley, CA 94941 Marin County
Silicon Valley Clean Water	Monte Hamamoto Chief Operating Officer (650) 832-6266	1400 Radio Road Redwood City, CA 94065 San Mateo County
Sonoma Valley County Sanitation District	Frank Mello Operations Coordinator (707) 521-1843	Sonoma County Water Agency 404 Aviation Blvd. Santa Rosa, CA 95403 Sonoma County
South San Francisco and San Bruno, Cities of	Brian Schumacker Plant Superintendent (650) 829-3844	195 Belle Air Road South San Francisco, CA 94080 San Mateo County
Sunnyvale, City of	Rohan Wikramanayake Water Pollution Control Plant Division Manager (781) 491-6177	Sunnyvale Water Pollution Control Plant P.O. Box 3707 Sunnyvale, CA 94088- 3707 Santa Clara County
Treasure Island Development Authority	Andrew Clark Operations Superintendent (415) 920-4944	1 Avenue of the Palms, Ste 161 San Francisco, CA 94130 San Francisco County
Vallejo Flood and Wastewater District	Jennifer Harrington Environmental Services Director (707) 652-7806	450 Ryder Street Vallejo, CA 94590 Solano County
West County Agency	Andrew Clough	2910 Hilltop Drive
Wastewater District	(510) 237-6603	Contra Costa County

Discharger	Authorized Person to Sign and Submit Reports	Billing Address
City of Richmond and Richmond Municipal		
Sewer District		

1.1. The Dischargers listed in Table 1 own and operate their respective wastewater treatment plants and collection systems. The Dischargers provide secondary or advanced secondary treatment of wastewater collected from their service areas. After treatment, the Dischargers discharge to San Francisco Bay¹ and its tributaries, which are waters of the United States within the San Francisco Bay watershed. Details of the wastewater treatment processes and discharges are described in the individual NPDES permits listed in Attachment B. Attachment C shows a map of the primary discharge locations subject to this Order.

For the purposes of this Order, references to the "discharger" or "permittee" in applicable federal and state laws, regulations, plans, and policies are held to be equivalent to references to the Discharger herein.

- **1.2.** The Dischargers are regulated pursuant to the individual NPDES permits listed in Attachment B and NPDES Permit CA0038873, previously Order R2-2019-0017 (previous order).
- 1.3. The Dischargers are authorized to discharge nutrients subject to waste discharge requirements (WDRs) in this Order. Clean Water Act section 402(b)(1)(B) limits the duration of NPDES permits to a fixed term not to exceed five years (33 U.S.C. §1342(b)(1)(B); see also 40 C.F.R. § 122.46). Accordingly, Table 3 of this Order limits the effective period for this discharge authorization. Pursuant to California Code of Regulations, title 23, section 2235.4, the terms and conditions of an expired permit are automatically continued pending reissuance of the permit if the Dischargers comply with all requirements for continuation of expired permits (40 C.F.R § 122.6(d)).
- **1.4.** This Order is the third phase of what the Regional Water Board expects to be a multiple-permit-term effort. It establishes new interim and final effluent limitations to limit excessive eutrophication in San Francisco Bay. The purpose of this phase is to (1) establish interim effluent limitations for total inorganic nitrogen to ensure nutrient loads do not increase at individual treatment plants, (2) track and evaluate current and future nutrient loads from municipal dischargers, (3) fund nutrient monitoring programs, (4) support load response modeling, and (5) establish final numeric water quality-based effluent limitations that modeling and data indicate

¹ San Francisco Bay, as the term is used in this Order, refers to the Sacramento/San Joaquin River Delta generally west of and including Montezuma Island, Suisun Bay, Carquinez Strait, San Pablo Bay, Central San Francisco Bay, Richardson Bay, Lower San Francisco Bay, and South San Francisco Bay.

will meet the narrative biostimulatory water quality objective to protect beneficial uses and a compliance schedule to attain these final effluent limitations.

2. FACILITY DESCRIPTIONS

2.1. Wastewater Collection and Treatment

- 2.1.1. **Location and Service Area**. The municipal wastewater treatment plants are located throughout the San Francisco Bay region and described in the individual permits listed in Attachment B.
- 2.1.2. **Wastewater Treatment**. Municipal wastewater treatment plants provide secondary treatment, which includes screening, skimming, settling, and biological treatment. Some plants provide advanced secondary treatment, which can nitrify ammonia to make nitrate nitrogen. Plants also denitrify at various levels, which removes nitrogen from wastewater. The primary source of nutrients in municipal wastewater is human waste; therefore, most Dischargers have no practical way of controlling influent nutrient concentrations.
- 2.2. Discharge Point and Receiving Waters. Municipal wastewater treatment plants discharge throughout San Francisco Bay, including the Sacramento/San Joaquin River Delta generally west of and including Montezuma Island, Suisun Bay, Carquinez Strait, San Pablo Bay, Central San Francisco Bay, Richardson Bay, Lower San Francisco Bay, South San Francisco Bay, and connected tributaries. Discharge points and receiving waters are described in the individual permits listed in Attachment B. Primary discharge points are also shown in Attachment C.
- 2.3. Previous Requirements and Monitoring Data. The previous order required the Dischargers to continue developing and supporting necessary studies to support implementation of the San Francisco Bay Nutrient Management Strategy. The Dischargers submitted a Science Plan for the San Francisco Bay Nutrient Management Strategy on January 30, 2020, and have since submitted annual updates and continue to implement the studies.

The previous order also required the Dischargers to evaluate potential nutrient reduction by natural systems and water recycling. The Dischargers submitted a Nature-Based Solution for Nutrient Removal report on June 30, 2023. The report was prepared by the San Francisco Estuary Institute (SFEI), which conducted a regional desktop analysis to identify Dischargers that have the best opportunities to implement nature-based solutions for nutrient reduction. SFEI then conducted outreach to these Dischargers to develop and identify constraints and site-scale models. The results are summarized below:

• **Central Contra Costa Sanitary District**. The district is currently reviewing strategies to reduce total inorganic nitrogen discharges. One of the potential methods would be to convert its wet weather earthen basins to water treatment wetlands. This project is in the early evaluation stages.

- **Delta Diablo**. Delta Diablo was identified to be a strong candidate for nutrient removal using nature-based solution by preliminary assessments. It is currently developing designs and cost estimates. The project has not yet been reviewed by Delta Diablo executive staff or its board of directors.
- Fairfield Suisun Sewer District. The district is considering adding treatment wetlands to its treatment process. The facility has large wet-weather equalization basins and additional land where the district is evaluating construction of a multi-benefit wetland for resiliency and nutrient removal benefits. The district is seeking funding from outside sources for implementation.
- **Novato Sanitary District**. The district could construct either a horizontal levee or a vegetated freshwater wetland to augment its treatment system. It could partner with Marin County on existing funded projects in the area while seeking other funding sources through regional, state, and federal levels.
- Sewerage Agency of Southern Marin. The agency could build horizontal levees in its surrounding tidal marsh or retrofit its equalization basins with treatment wetlands.
- San Jose/Santa Clara. San Jose maintains significant open water wetlands and has begun evaluating the feasibility of converting decommissioned sludge lagoons to nature-based treatment. A regional flood protection levee project (i.e., the South San Francisco Bay Shoreline Project) would need to be completed before any potential nature-based treatment could be pursued.
- South San Francisco/San Bruno. While South San Francisco does not have much open land near the facility, it could convert old naval piers into a horizontal levee or treatment wetland.
- Union Sanitary District. In conjunction with the South Bay Salt Pond Restoration Project, the district explored the feasibility of building a horizontal levee on adjacent land. Although the district does not own the land, it has pledged support for the concept and will assist with moving the project forward. The district plans to significantly reduce nutrient discharges with treatment plant upgrades. Construction started in 2022 and is expected to be completed by 2029.

The next phase of this process is to focus on a smaller set of facilities to develop design and cost estimates, which will be submitted to the Regional Water Board by June 30, 2024.

In addition, several other Dischargers have explored nature-based solutions not evaluated in the regional study:

- Oro Loma and Castro Valley Sanitary Districts. The districts, along with partners at East Bay Dischargers Authority and East Bay Regional Park District, are continuing to advance design of the First Mile Horizontal Levee Project just south of the Oro Loma Sanitary District/Castro Valley Sanitary District Water Pollution Control Plant at Oro Loma Marsh. The project would treat up to 1 MGD of treatment plant effluent through a subsurface treatment layer in the horizontal levee, effectively removing nitrogen and emerging contaminants, while also providing flood protection, upland refugia for endangered species, and recreational opportunities for an underserved community. Funding has been secured to develop the project through final design and permitting.
- **City of San Leandro.** To demonstrate the feasibility of implementing naturebased solutions for building shoreline resiliency, creating habitat, and improving water quality, the City of San Leandro plans to convert an existing 6.9-acre wastewater storage basin into a shallow, freshwater, open-water wetland to provide polishing treatment for flows from a newly installed nitrification system. This constructed wetland is expected to polish about 10 percent of wastewater flows from the treatment plant. The City of San Leandro plans to start construction in 2024. The Regional Water Board permitted this discharge under Order R2-2022-0006 (NPDES Permit CA0038881).
- **City of Hayward.** Under a grant from U.S. EPA's Water Quality Improvement Fund, the City of Hayward completed a feasibility study that evaluated opportunities to construct a treatment wetland and horizontal levee at its former oxidation ponds. Under a second Water Quality Improvement Fund grant, the City of Hayward is evaluating this project in more detail. The project would use a portion of the oxidation ponds to create an optimized wetland that would provide nitrogen treatment during the dry season, while maintaining the wet weather storage function in the winter. The project would also include a horizontal levee at the edge of the wetlands to provide additional wastewater treatment and polishing, as well as flood protection and upland refugia for shoreline species as sea level rises.
- **Silicon Valley Clean Water**. Silicon Valley Clean Water is considering the feasibility of using nearby wetlands or upgrading its surrounding levee system to provide nature-based treatment for nitrogen removal.

The Dischargers also submitted a Regional Evaluation of Potential Nutrient Discharge Reduction by Water Recycling report on June 28, 2023, summarizing feasible nutrient reductions through water recycling at different facilities. The table below projects water recycling through 2030 based on planned projects. The 2025 projections are more certain than those for 2030 because many of the later projects are conceptual and still require agreements between multiple agencies. Provision 6.3.4 requires Dischargers to submit a regional planning document that proposes how additional nutrient load reductions can be achieved, including through implementation of nature-based solutions and water recycling. Nutrient reductions from recycled water will depend on nutrient concentrations in recycled water, end uses, and, for projects that use reverse osmosis, how the reverse osmosis concentrate is managed.

Discharger	Average Daily Discharge Oct 2019- Sept 2020	2020 Water Recycled (MGD)	2020 Fraction Recycled	2025 Projected Water Recycled (MGD)	2030 Projected Water Recycled (MGD)
American Canyon, City of	1.22	0.313	0.26	0.619	0.619
Benicia, City of	1.8	-	-	-	-
Burlingame, City of	2.44	-	-	-	-
Central Contra Costa Sanitary District	33.3	1.6	0.05	1.95	2.24
Central Marin Sanitation Agency	9.01	0.024	0.00	0.024	0.024
Crockett Community Services District	0.0296	-	-	-	-
Delta Diablo	8.17	4.75	0.58	4.78	4.78
East Bay Dischargers Authority (EBDA)	62.1	6.0	0.10	6.5	6.8
Dublin San Ramon Services District	10	3.5	0.34	3.7	3.7
City of Hayward	11	0.8	0.07	1.1	1.2
City of Livermore	4.1	1.4	0.35	1.5	1.5
Oro Loma Sanitary District and Castro Valley Sanitary District	11	0.03	0.00	0.0	0.0
City of San Leandro	5.0	0.3	0.05	0.3	0.3
Union Sanitary District	23	0.0	-	0.0	0.0
East Bay Municipal Utility District	48.1	0.18	0.00	0.202	0.504
Fairfield-Suisun Sewer District	12.9	1.03	0.08	1.03	1.03
Las Gallinas Valley Sanitary District	1.93	0.975	0.51	0.975	0.975
Marin County (Paradise Cove), Sanitary District No. 5 of	0.0149	-	-	-	-
Marin County (Tiburon), Sanitary District No. 5 of	0.573	-	-	-	-
Millbrae, City of	1.48	-	-	-	-
Mt. View Sanitary District	1.19	1.15	0.97	1.18	1.21
Napa Sanitation District	3.54	3.3	0.93	3.4	3.4
Novato Sanitary District	2.75	1.47	0.53	1.45	5.03
Palo Alto, City of	19.5	0.705	0.04	0.752	13.7
Petaluma, City of	2.89	0.981	0.34	1.2	3.4

Table F-3. Current and Projected Water Recycling

Discharger	Average Daily Discharge Oct 2019- Sept 2020	2020 Water Recycled (MGD)	2020 Fraction Recycled	2025 Projected Water Recycled (MGD)	2030 Projected Water Recycled (MGD)
Pinole, City of	2.27	-	-	-	-
Rodeo Sanitary District	0.551	-	-	-	-
San Francisco (San Francisco International Airport), City and County of	0.943	-	-	-	-
San Francisco (Southeast Plant), City and County of	46.8	-	-	-	-
San Jose and Santa Clara, Cities of	84.4	12.6	0.15	15	17
San Mateo, City of	9.92	-	-	-	-
Sausalito-Marin City Sanitary District	1.03	-	-	-	-
Sewerage Agency of Southern Marin	2.14	0.038	0.02	0.038	0.038
Silicon Valley Clean Water	13.7	0.856	0.06	1.23	1.31
Sonoma Valley County Sanitation District	2.21	2.21	1.00	2.24	2.24
South San Francisco and San Bruno, Cities of	7.34	-	-	-	-
Sunnyvale, City of	10.1	0.443	0.04	-	-
Treasure Island Development Authority	0.285	-	-	-	-
Vallejo Flood and Wastewater District	8.51	-	-	-	-
West County Agency West County Wastewater District City of Richmond and Richmond Municipal Sewer District	7.37	3.92	0.53	1.1	1.4
Total	408	43.2	0.11	52.8	76.4

2.4. Existing Nutrient Discharge Data

The previous order required Dischargers to collect the nutrient discharge data shown below. The table includes 2022 dry season daily average loads, which was used to calculate baywide load reductions, and the maximum dry season average from 2014 through 2017, which established a 2019 baseline for performance in the previous order.

Discharger	2019-2023 Average Loads (kg/day)	2022 Loads (kg/day)	2019 Established Baseline (kg/day)	Design Flow (MGD)
American Canyon, City of	18	11	80	2.5
Benicia, City of	220	200	240	4.5
Burlingame, City of	340	250	290	5.5
Central Contra Costa Sanitary District	3,700	3,700	3,700	53.8
Central Marin Sanitation Agency	1,100	1,100	1,200	10
Crockett Community Services District	-	-	-	0.033
Delta Diablo	1,200	950	1,500	19.5
East Bay Dischargers Authority (EBDA)	7,300	6,900	8,400	107.8
East Bay Municipal Utility District	8,900	10,000	9,800	120
Fairfield-Suisun Sewer District	960	1,000	1,100	23.7
Las Gallinas Valley Sanitary District	-	-	-	2.92
Marin County (Paradise Cove), Sanitary District No. 5 of	1.5	0.88	-	0.04
Marin County (Tiburon), Sanitary District No. 5 of	41	47	-	0.98
Millbrae, City of	270	240	290	3.0
Mt. View Sanitary District	89	42	120	3.2
Napa Sanitation District	-	-	-	15.4
Novato Sanitary District	85	-	-	7.0
Palo Alto, City of	2,100	2,200	2,600	39
Petaluma, City of	-	-	-	6.7
Pinole, City of	280	370	340	4.06
Rodeo Sanitary District	41	39	31	1.14
San Francisco (San Francisco International Airport), City and County of	110	91	340	2.2
San Francisco (Southeast Plant), City and County of	7,300	7,400	11,000	85.4
San Jose and Santa Clara, Cities of	3,700	2,500	5,300	167
San Mateo, City of	1,400	1,300	1,500	15.7
Sausalito-Marin City Sanitary District	130	110	150	1.8
Sewerage Agency of Southern Marin	230	250	190	3.6

Table F-4. Average Annual Dry Season Total Inorganic Nitrogen

Discharger	2019-2023 Average Loads (kg/day)	2022 Loads (kg/day)	2019 Established Baseline (kg/day)	Design Flow (MGD)
Silicon Valley Clean Water	2,500	2,500	2,500	29
Sonoma Valley County Sanitation District	-	-	-	3.0
South San Francisco and San Bruno, Cities of	1,200	1,200	920	13
Sunnyvale, City of	530	500	630	29.5
Treasure Island Development Authority	20	20	21	2.0
Vallejo Flood and Wastewater District	810	770	900	15.5
West County Agency West County Wastewater District City of Richmond and Richmond Municipal Sewer District	750	700	1,000	28.5
Aggregate Load (kg/day)	45,200	44,400	54,100	-

3. APPLICABLE PLANS, POLICIES, AND REGULATIONS

The requirements contained in this Order are based on the requirements and authorities described in this section.

- **3.1. Legal Authorities.** This Order serves as WDRs pursuant to California Water Code article 4, chapter 4, division 7 (commencing with § 13260). This Order is also issued pursuant to federal Clean Water Act (CWA) section 402 and implementing regulations adopted by the U.S. EPA, and Water Code chapter 5.5, division 7 (commencing with § 13370). It serves as an NPDES permit for point source municipal discharges of nutrients to surface waters from the named facilities listed in Attachment B of this Order.
- **3.2. California Environmental Quality Act (CEQA).** Under Water Code section 13389, this action to adopt an NPDES permit is exempt from the provisions of the California Environmental Quality Act (CEQA), Public Resources Code division 13, chapter 3 (commencing with § 21100).

3.3. State and Federal Laws, Regulations, Policies, and Plans

3.3.1. **Water Quality Control Plan.** The Regional Water Board adopted the *Water Quality Control Plan for the San Francisco Bay Basin* (Basin Plan), which designates beneficial uses, establishes water quality objectives, and contains implementation programs and policies to achieve those objectives for all waters addressed through the plan. Requirements in this Order implement the Basin Plan. In addition, this Order implements State Water Board Resolution 88-63,

which established State policy that all waters, with certain exceptions, should be considered suitable or potentially suitable for municipal or domestic supply. The beneficial uses applicable to San Francisco Bay include Agricultural Supply (AGR), Cold Freshwater Habitat (COLD), Ocean, Commercial, and Sport Fishing (COMM), Estuarine Habitat (EST), Industrial Service Supply (IND), Marine Habitat (MAR), Fish Migration (MIGR), Municipal and Domestic Supply (MUN), Navigation (NAV), Industrial Process Supply (PROC), Preservation of Rare and Endangered Species (RARE), Water Contact Recreation (REC1), Non-Contact Water Recreation (REC2), Shellfish Harvesting (SHELL), Fish Spawning (SPWN), Warm Freshwater Habitat (WARM), and Wildlife Habitat (WILD).

- 3.3.2. **Antidegradation Policy.** Federal regulations at 40 C.F.R. section 131.12 require that state water quality standards include an antidegradation policy consistent with the federal policy. The State Water Board established California's antidegradation policy through State Water Board Resolution 68-16, *Statement of Policy with Respect to Maintaining High Quality of Waters in California*, which incorporates the federal antidegradation policy where the federal policy applies under federal law. Resolution 68-16 requires that existing water quality be maintained unless degradation is justified based on specific findings. The Basin Plan implements, and incorporates by reference, both the State and federal antidegradation policies. Permitted discharges must be consistent with the antidegradation provisions of 40 C.F.R. section 131.12 and State Water Board Resolution 68-16.
- 3.3.3. **Anti-Backsliding Requirements.** CWA sections 402(o) and 303(d)(4) and 40 C.F.R. section 122.44(I) restrict backsliding in NPDES permits. These antibacksliding provisions require that effluent limitations in a reissued permit be as stringent as those in the previous permit, with some exceptions in which limitations may be relaxed.
- 3.3.4. Endangered Species Act Requirements. This Order does not authorize any act that results in the taking of a threatened or endangered species or any act that is now prohibited, or becomes prohibited in the future, under either the California Endangered Species Act (Fish and Game Code §§ 2050 to 2097) or Federal Endangered Species Act (16 U.S.C.A. §§ 1531 to 1544). This Order requires compliance with effluent limitations, receiving water limitations, and other requirements to protect the beneficial uses of waters of the State, including protecting rare, threatened, or endangered species. The Discharger is responsible for meeting all applicable Endangered Species Act requirements.
- **3.4.** Impaired Water Bodies on CWA section 303(d) List. On May 11, 2022, U.S. EPA approved a revised list of impaired waters pursuant to CWA section 303(d), which requires identification of specific water bodies where it is expected that water quality standards will not be met after implementation of technologybased effluent limitations on point sources. Where it has not done so already, the

Regional Water Board plans to adopt Total Maximum Daily Loads (TMDLs) for pollutants on the 303(d) list. TMDLs establish wasteload allocations for point sources and load allocations for nonpoint sources and are established to achieve water quality standards. No San Francisco Bay segment is listed as impaired by nutrients.

4. RATIONALE FOR EFFLUENT LIMITATIONS AND DISCHARGE SPECIFICATIONS

The CWA requires point source dischargers to control the amount of conventional, non-conventional, and toxic pollutants discharged into waters of the United States. The control of pollutants discharged is established through effluent limitations and other requirements in NPDES permits. There are two principal bases for effluent limitations: 40 C.F.R. section 122.44(a) requires that permits include applicable technology-based limitations and standards, and 40 C.F.R. section 122.44(d) requires that permits include water quality-based effluent limitations to attain and maintain applicable numeric and narrative water quality criteria to protect the beneficial uses of receiving waters. The individual NPDES permits listed in Attachment B of this Order contain the applicable technology-based limitations for the discharges covered by this Order.

4.1. Water Quality-Based Effluent Limitations

4.1.1. Scope and Authority

CWA section 301(b) and 40 C.F.R. section 122.44(d) require permits to include limitations more stringent than federal technology-based requirements where necessary to achieve water quality standards. According to 40 C.F.R. section 122.44(d)(1)(i), permits must include effluent limitations for all pollutants that are or may be discharged at levels that have a reasonable potential to cause or contribute to an exceedance of a water guality standard, including numeric and narrative objectives within a standard. Where reasonable potential has been established for a pollutant, but there is no numeric criterion or objective, water guality-based effluent limitations (WQBELs) must be established using (1) U.S. EPA criteria guidance under CWA section 304(a), supplemented where necessary by other relevant information; (2) an indicator parameter for the pollutant of concern; or (3) a calculated numeric water quality criterion, such as a proposed state criterion or policy interpreting a narrative criterion, supplemented with relevant information. The process for determining reasonable potential and calculating WQBELs when necessary is intended to achieve applicable water quality objectives and criteria, and thereby protect designated beneficial uses of receiving waters.

4.1.2. Beneficial Uses and Water Quality Objectives

The Dischargers discharge to San Francisco Bay and its tributaries. Fact Sheet section 3.3.1 identifies the beneficial uses of San Francisco Bay and its

tributaries. Water quality objectives to protect these beneficial uses include the narrative biostimulatory substances objective in Basin Plan section 3.3.3:

Waters shall not contain biostimulatory substances in concentrations that promote aquatic growths to the extent that such growths cause nuisance or adversely affect beneficial uses. Changes in chlorophyll a and associated phytoplankton communities follow complex dynamics that are sometimes associated with a discharge of biostimulatory substances. Irregular and extreme levels of chlorophyll a or phytoplankton blooms may indicate exceedance of this objective and require investigation.

4.1.3. Reasonable Potential Analysis

Municipal wastewater treatment plants are a significant source of nutrients to San Francisco Bay and nutrients pose a threat to San Francisco Bay beneficial uses. In San Francisco Bay, nitrogen is the growth-limiting nutrient.² Total inorganic nitrogen is the bioavailable form of nitrogen. As shown in the table below, municipal wastewater treatment plants account for about 86 percent of the annual average dry season total inorganic nitrogen load to San Francisco Bay and close to 100 percent of the total inorganic nitrogen load to Lower South Bay, South Bay, and Central Bay.³ The estimates in the table do not account for dry season inorganic nitrogen loads from other sources such as creeks, urban stormwater systems, or aerial deposition, because load estimates were not available and assumed to be relatively small.

Subembayment	Municipal ^[1] (kg N/day)	Petroleum Refinery ^[2] (kg N/day)	Delta ^[3] (kg N/day)	Total (kg N/day)	Municipal (%)
Lower South Bay	6,300	-	-	6,300	100
South Bay	20,400	-	-	20,400	100
Central Bay	11,200	-	-	11,200	100
San Pablo Bay & Carquinez Strait	1,500	840	-	2,300	64
Suisun Bay	5,900	130	6,200	12,200	48
Baywide	45,200	970	6,200	52,400	86

 Table F-5. Dry Season Average Total Inorganic Nitrogen

Footnotes:

^[1] Average of data from 2018 through 2022.

^[2] Data from 2011. To gather more information on current total inorganic nitrogen loadings from refineries and assess potential treatment options, the Regional Water Board issued a 13383 order on January 26, 2024.

^[3] Data from *Nutrients in the Northern San Francisco Estuary* from SFEI in 2021.

² San Francisco Estuary Institute, Scientific Foundation for the San Francisco Bay Nutrient Management Strategy, Draft FINAL, October 2014, page 65.

³ San Francisco Estuary Institute, External Nutrient Loads to San Francisco Bay, January 2014, Table 6, page 27.

San Francisco Bay has long been recognized as nutrient-enriched. Despite this, the abundance of phytoplankton in the estuary is typically lower than what would be expected due to strong tidal mixing, which limits periods of stratification; high turbidity, which limits light penetration; and an abundant clam population, which feeds on the phytoplankton. Data from 2000 through 2020 indicated an increase in phytoplankton biomass in many areas of the estuary, suggesting that San Francisco Bay's historic resilience to the effects of nutrient enrichment was potentially weakening.⁴ The contributing factors for this decline may include (1) natural oceanic oscillations that have increased benthic predators, thus reducing South San Francisco Bay's clam population and clam grazing and (2) decreases in suspended sediment that have resulted in a less turbid environment and increased light penetration. Beginning in the late 1990s, phytoplankton growth in South San Francisco Bay increased sharply through 2010, then leveled off until 2022. The cause of this increase appears to have been a significant increase in fish, shrimp, and crab predators attributed to a change in natural oceanic oscillations bringing colder waters to San Francisco Bay.

Spring phytoplankton blooms are relatively frequent in San Francisco Bay, and fall blooms are becoming more frequent. The reasons are unknown, but the increases could be the result of a less turbid environment and less clam grazing. While San Francisco Bay experiences strong tidal mixing, there are two periods each year, between March and April and between September and October, during which there is less tidal mixing. Typically, these blooms are short-lived, lasting only 10 to 14 days and ending when tides increase and remix the water column.

While phytoplankton growth and biomass accumulation are limited much of the time by a lack of light and clam grazing, these limiting conditions were overcome in July and August 2022, when a large harmful algal bloom caused significant fish mortality. In late July 2022, an algae bloom formed in the deep channel between Alameda and Oakland. In early August, it spread from the Lower Bay to the South Bay, and by mid-to-late August, it had expanded throughout the Lower and South Bays. Researchers reported chlorophyll a values above 100 ug/L, which is about 20 times higher than typical values. There were observations of fish mortality, including sturgeon, leopard sharks, striped bass, and smaller fish throughout the Lower Bay, South Bay, Central Bay, and San Pablo Bay. Researchers recorded unusually low dissolved oxygen concentrations (below 3 mg/L) in large parts of the South Bay and Lower South Bay for several days after observing the fish mortality.

⁴ Cloern, J.E., Schraga, T.S., Nejad, E. et al. Nutrient Status of San Francisco Bay and Its Management Implications. Estuaries and Coasts 43, 1299–1317 (2020). https://doi.org/10.1007/s12237-020-00737-w.

The species associated with this bloom, *Heterosigma akashiwo*, is one of several species that can cause water to take on a reddish-brown color, commonly called a "red tide." *Heterosigma akashiwo* was able to proliferate over such a large area of San Francisco Bay because the physical factors that typically limit algal growth were not present (e.g., turbidity levels were low). Because existing nutrient concentrations in San Francisco Bay are sufficient to support large and sustained algal blooms, it was possible for large areas of San Francisco Bay to experience excessive eutrophication, low dissolved oxygen levels, and fish mortality. These conditions were not limited to Lower Bay and South Bay because *Heterosigma akashiwo* was also observed in a significant portion of San Pablo Bay in July and August 2023.

As shown in Table F-5, municipal wastewater treatment plants contribute most of the total inorganic nitrogen discharged to San Francisco Bay. During the July and August 2022 bloom, total inorganic nitrogen levels were sufficient to support excessive algal growth, which adversely affected beneficial uses. As explained above, irregular and extremely high chlorophyll-a values and thousands of dead fish were observed. Therefore, this Order finds reasonable potential for the Dischargers, except those with a dry season discharge prohibition in their individual permits (i.e., Las Gallinas Valley Sanitation District, Napa Sanitation District, City of Petaluma, and Sonoma Valley County Sanitation District), to discharge total inorganic nitrogen at levels that could cause or contribute to an exceedance of the narrative biostimulatory substances objective during the dry season (May through September). This finding is consistent with U.S. EPA's NPDES Permit Writers' Manual (Publication Number: EPA-833-K-10-001, September 2010, section 6.3.1), which indicates that a permit writer may use effluent and receiving water data and modeling techniques, or a non-quantitative approach to evaluate whether there is reasonable potential to exceed a narrative water quality objective. There is no reasonable potential during the wet season because algal blooms during the wet season have been short-lived and have not adversely affected beneficial uses.

4.1.4. Water Quality-Based Effluent Limitations

4.1.4.1. **WQBEL Expression.** NPDES regulations at 40 CFR 122.45(d) require that all permit effluent limitations, standards, and prohibitions for continuous discharges from publicly-owned treatment works be expressed as average weekly and average monthly limitations, unless impracticable. Here, it is impracticable to express the total inorganic nitrogen effluent limitations as daily maximums, weekly averages, or monthly averages because developing limitations for the nutrients affecting San Francisco Bay and its tributaries is different from setting limitations for toxic pollutants. The exposure period of concern for nutrients is longer than one month, and the average exposure rather than the maximum exposure is of concern. The statistical procedures for developing effluent limits from the State Water Board's *Policy for*

Implementation of Toxics Standards for Inland Surface Waters, Enclosed Bay, and Estuaries of California (State Implementation Policy) would result in impracticable effluent limits for total inorganic nitrogen. If based on the procedures used for aquatic life protection that have water quality objectives based on exposure durations of one hour (acute) or four days (chronic), the maximum and average monthly effluent limits would be less stringent than the seasonal limits necessary to protect beneficial uses. Even if municipal wastewater treatment plants discharged total inorganic nitrogen in compliance with these monthly effluent limits, it would be possible for these dischargers to exceed the seasonal mass limit that must be met to protect beneficial uses. Such a result would be unacceptable.

The nutrient dynamics of San Francisco Bay and its tributaries are complex and also make expressing the total inorganic nitrogen effluent limitations as daily maximums, weekly averages, or monthly averages impracticable. Unlike many conventional pollutants that have direct and somewhat immediate effects on the aquatic system, nutrients have no known direct effect. Several conditions must be met for nutrients to affect the Bay ecosystem. These conditions delay and buffer the effects nutrients have on receiving waters. San Francisco Bay and its tributaries' biological and physical processes can be viewed as integrating the various nutrient loads from all sources over time. The integration ameliorates daily and monthly load fluctuations, with the Bay responding to overall loads on a seasonal basis, showing little response to the daily and monthly variations among individual sources. SFEI models the effect of nutrient loading to San Francisco Bay. Based on the model results, the Bay and its tributaries have been shown to integrate various point source loads over time. Thus, seasonal loading requirements (specifically requirements for the dry season from May 1 through September 30) will protect the Bay under the critical conditions that led to the July and August 2022 bloom. This is consistent with U.S. EPA's Memorandum: Annual Permit Limits for Nitrogen and Phosphorus for Permits Designed to Protect Chesapeake Bay and its tidal tributaries from Excess Nutrient Loading under the National Pollutant Discharge Elimination System, dated March 3, 2004, which found that a similar finding of impracticability pursuant to 40 C.F.R. section 122.45(d) may be appropriate when implementing nutrient criteria in other watersheds if supported with data and modeling that shows it is necessary to control long-term average loadings rather than short-term maximum loadings.

4.1.4.2. **Final Effluent Limitations.** Based on the reasonable potential analysis in Provision 4.1.3, above, this Order establishes effluent limitations for total inorganic nitrogen. Pursuant to 40 C.F.R. section 122.44(d)(1)(vi), where a state has not established a water quality criterion for a specific chemical pollutant that is present in an effluent at a concentration that causes, has the reasonable potential to cause, or contribute to an excursion above a

narrative water quality objective, the permitting agency must establish effluent limits using one or more of the following options:

- (A) Establish effluent limits using a calculated numeric water quality criterion for the pollutant which the permitting authority demonstrates will attain and maintain applicable narrative water quality criteria and will fully protect the designated use. Such a criterion may be derived using a proposed State criterion, or an explicit State policy or regulation interpreting its narrative water quality criterion, supplemented with other relevant information which may include: EPA's Water Quality Standards Handbook, October 1983, risk assessment data, exposure data, information about the pollutant from the Food and Drug Administration, and current EPA criteria documents;
- (B) Establish effluent limits on a case-by-case basis, using U.S. EPA's water quality criteria under CWA section 304(a), supplemented where necessary by other relevant information; or
- (C) Establish effluent limits based on an indicator parameter for the pollutant of concern.

This Order establishes effluent limits for total inorganic nitrogen by using a calculated numeric water quality criterion for dissolved oxygen that will attain and maintain the narrative biostimulatory substances water quality objective and fully protect beneficial uses, as allowed by 40 C.F.R. section 122.44(d)(1)(vi)(A). As explained in the *Memo on Numerical Translation of Narrative Objective*,⁵ a dissolved oxygen concentration for San Francisco Bay that is protective of beneficial uses under the acute condition of an algae bloom was calculated using the dissolved oxygen criterion for Suisun Marsh and other supplemental information (e.g., South Bay slough study).

The Nutrient Science Program has developed and continues to improve a coupled physical biogeochemical model, with input and feedback from scientific advisors, that accounts for the fate and transport of nutrient loads to the Bay and how nutrients affect or may affect primary productivity, dissolved oxygen, and harmful algal blooms in the Bay. A recent review⁶ by an independent panel of experts in physical and biogeochemical modeling, observations, and use of models to support decisions to manage eutrophication and other anthropogenic effects found that the model

⁵ San Franisco Bay Regional Water Board, *Memo on Numerical Translation of Narrative Objective*, February 2024.

⁶ Findings and Recommendations of an Expert Panel Evaluating a Physical-Biogeochemical Model Supporting the San Francisco Bay Nutrient Management Strategy: February 2023 Workshop

represents important transport processes and can reproduce the seasonal and spatial patterns of nutrient concentrations in the Bay.

The panel also found that the physical portion of the model used to predict the spatial patterns of nutrient concentrations is ready for near-term application. This Order's Aggregate Mass Load was calculated based on use of the physical portion of the model. This Order used the biogeochemical portion of the model to simulate nitrogen transformation, but did not use the biogeochemical portion of the model to predict chlorophyll-a and dissolved oxygen levels due to its limitations that will be resolved with ongoing and planned model improvements.

The Nutrient Science Program scientists at SFEI evaluated different total inorganic nitrogen load reduction scenarios using the physical portion of the model to determine the loads that San Francisco Bay can assimilate without having an excessive algal bloom that would result in unprotective dissolved oxygen levels.

Studies undertaken for Suisun Marsh and South Bay sloughs were used to establish a dissolved oxygen criterion that would protect beneficial uses under the acute conditions of a large algal bloom. The Suisun Marsh study evaluated the four species most sensitive to low dissolved oxygen concentrations to calculate an acute threshold. These species, from most tolerant to least tolerant, were striped bass, Mississippi silversides, American shad, and sturgeon. The resulting dissolved oxygen criterion was a minimum concentration of 3.8 mg/L. The South Bay slough study also evaluated the four species most sensitive to low dissolved oxygen concentrations to calculate an acute threshold. These species, from most tolerant to least tolerant, were sturgeon, killifish/topminnow, molly, and herring. The resulting dissolved oxygen criterion was a minimum concentration of 3.7 mg/L.

The species used for these calculations are generally representative of the most oxygen-sensitive species living in San Francisco Bay. Therefore, a protective dissolved oxygen concentration for San Francisco Bay would likely be close to 3.8 or 3.7 mg/L. To provide a margin of safety when applying the dissolved oxygen criteria for Suisun Marsh and the South Bay sloughs to all of San Francisco Bay, a dissolved oxygen concentration of 4.0 mg/L was selected to evaluate the model results for each subembayment.

U.S. EPA recognizes that beneficial uses can be supported even if water quality objectives are not achieved 100 percent of the time. U.S. EPA guidance provides an allowable exceedance threshold of 10 percent for

conventional pollutants, like dissolved oxygen.⁷ Like many states, California uses this guidance.⁸ For example, the California Listing Policy⁹, consistent with U.S. EPA guidance, allows for an exceedance frequency of up to 10 percent for conventional pollutants like dissolved oxygen to determine whether water quality standards are met. Accordingly, for purposes of this Order, the narrative biostimulatory substances water quality objective would be met if modeling results show that no more than 10 percent of the surface area in each subembayment has dissolved oxygen levels below 4.0 mg/L. When reissuing this permit, the Regional Water Board will consider additional endpoints, such as algal toxins, to interpret the narrative biostimulatory substances water quality objective if supported by new scientific evidence.

SFEI modeled different load reduction scenarios under the critical conditions of the July and August 2022 bloom and made worst-case assumptions for phytoplankton growth and decay. SFEI assumed that all available nitrogen would be converted to phytoplankton, and that all the phytoplankton produced would be digested by bacteria, a process that consumes oxygen. The "worst case" assumptions are appropriate because they represent what occurred during the July and August 2022 bloom. To determine nitrogen levels that are protective of beneficial uses, this Order only considers acute impacts because the effect of a large algae bloom on dissolved oxygen levels in San Francisco Bay, such as the July and August 2022 bloom, will occur over a period of a few days.

The results indicate that a baywide seasonal reduction in the total inorganic nitrogen loads from municipal wastewater treatment plants would need to be 40 percent below the loads that occurred during the 2022 bloom, or about 50 percent below the 2019 baseline conditions established in the previous order. According to the modeling, these lower total inorganic nitrogen loads would be sufficient to ensure that dissolved oxygen concentrations would fall below 4.0 mg/L in no more than 10 percent of any individual subembayment under the critical conditions of the 2022 bloom, a level protective of beneficial

⁷ Consolidated assessment and listing methodology toward a compendium of best practices. First edition. Washington, D.C.: Office of Wetlands, Oceans, and Watersheds, U.S. Environmental Protection Agency. 2002.

⁸ Functional Equivalent Document: Water Quality Control Policy for Developing California's Clean Water Act Section 303(d) List. September 2004.

⁹ The State Water Board adopted the Water Quality Control Policy for Developing California's Clean Water Act Section 303(d) List (Listing Policy). The Listing Policy describes the process by which the State Water Board and the nine Regional Water Quality Control Boards comply with the listing requirements of Clean Water Action section 303(d) and establishes a standard process to develop the list. To make decisions regarding standards attainment, the Listing Policy provides guidance for interpreting data and information as they are compared to beneficial uses, existing numeric and narrative water quality objectives, and antidegradation considerations.

uses under the acute condition of a large algae bloom. This reduction corresponds to a total aggregate average total inorganic nitrogen mass load of 26,700 kg/day (the total aggregate WQBEL in the Order).

This Order uses an aggregate approach to regulating total inorganic nitrogen because, once nitrogen loads are introduced into San Francisco Bay, mixing forces distribute and circulate nitrogen over a large area. The nitrogen concentrations in various portions of San Francisco Bay include loads from other dischargers and the combined contributions from the various dischargers determine the nitrogen levels that could potentially fuel algae blooms. This is reasonable because all portions of the estuary, including the North Bay, are vulnerable to algal blooms given the high concentrations of total inorganic nitrogen prevalent throughout the Bay.

This aggregate approach does not exclude major nutrient dischargers in the North Bay, like the Central Contra Costa Sanitary District, which is one of the top five dischargers of nutrients to the Bay and contributes over 50 percent of the nutrient discharge to North Bay from municipal wastewater treatment plants. The 40 percent baywide reduction in nitrogen needed to meet the objective and protect beneficial uses includes North Bay nitrogen discharges because they are not confined to the North Bay. Because the area is tidally influenced, these nutrients flow upstream to nutrient-sensitive areas in the Sacramento-San Joaquin Delta, an area known for its own nutrients-related problems. The Central Valley Regional Water Quality Control Board required the Sacramento Regional County Sanitation District (upstream of the Central Contra Costa Sanitary District outfall) to reduce its effluent nitrogen concentrations significantly (Order R5-2010-0114). North Bay discharges also flow through San Pablo Bay and Central Bay into the Pacific Ocean, another nutrient-sensitive area, and home to the Monterey Bay National Marine Sanctuary, Greater Farallones National Marine Sanctuary, and Cordell Bank National Marine Sanctuary. A small percentage of North Bay discharges even reach the South Bay.

Suisun Bay itself has measured total inorganic nitrogen levels that are comparable to the levels in the portions of the estuary where the 2022 algal bloom occurred, as explained in the *Memo on Numerical Translation of Narrative Objective*. Scientific evidence suggests that Suisun and San Pablo Bays are increasingly vulnerable to harmful algal blooms. Researchers have observed declining turbidity in the North Bay, which suggests that this portion of the estuary is losing its resilience against high nutrient loads.¹⁰ Losing this resilience makes it more likely that algae can make efficient use of available nitrogen, which is already sufficiently concentrated to support a significant algal bloom. In fact, algal toxins from harmful freshwater and marine algae species have been routinely detected in San Pablo Bay and Suisun Bay at relatively high concentrations. Therefore, the 40 percent baywide reduction in nitrogen is needed in North Bay to meet the biostimulatory objective and protect beneficial uses.

The Regional Water Board calculated the final WQBELs for individual Dischargers based on meeting the total aggregate average load of 26,700 kg/day as follows. For the three minor Dischargers listed in Table 1 (i.e., design flow less than 1.0 MGD), the final individual WQBELs are based on 2022 loads (for Marin County [Tiburon] Sanitary District No. 5) and the maximum loading, accounting for variability, from the previous 10 years for the two smallest facilities (Crockett Community Services District and Marin County [Paradise Cove] Sanitary District No. 5). This is appropriate because previous orders did not require minor facilities to evaluate treatment upgrade options and they only contribute about 0.1 percent of the total aggregate average load to San Francisco Bay. For the remaining Dischargers, the individual WQBELs are based on the concentration that, when the various flows are considered, results in loads summing to the total aggregate average load of 26,700 kg/day, assuming 2022 dry season flows. This concentration is 20.5 mg/L total inorganic nitrogen. The resulting individual WQBELs are listed in Table 4 of the Order.

Compliance with these dry season (May 1 through September 30) WQBELs will be assessed based on dry season data because algal blooms large enough to significantly consume total inorganic nitrogen and depress oxygen concentrations have not been shown to occur in San Francisco Bay during the wet season.

Because the individual WQBELs are based on the total aggregate WQBEL, compliance with the WQBELs will be based first on the total aggregate WQBEL. Compliance with the aggregate WQBEL will be attained if the sum of all the individual Dischargers' total inorganic mass loads does not exceed the aggregate WQBEL. If the sum of the individual total inorganic nitrogen mass loads is greater than the aggregate WQBEL, only the Dischargers

¹⁰ Cloern J.E., Jassby, A.D. (2012). Drivers of change in estuarine-coastal ecosystems: Discoveries from four decades of study in San Francisco Bay. Reviews of Geophysics, October 2012.

whose total inorganic nitrogen mass loads exceed their individual WQBELs will be in violation of the WQBELs.

Provision 6.3.2 of this Order requires the Dischargers to continue supporting receiving water monitoring and modeling to better understand how San Francisco Bay assimilates nutrients. Advances in modeling and data collected over the next five years will inform the Regional Water Board on the need to reassess and refine the final WQBELs and whether subembayments should be treated differently. For the permit reissuance scheduled for 2029, the Regional Water Board will consider advances in the science related to nutrients loading and beneficial use protection and available new information (e.g., observational data and improved load response modeling) to reassess and refine the final WQBELs developed for this Order to ensure that they are appropriate to protect San Francisco Bay beneficial uses.

4.2. Compliance Schedules and Interim Effluent Limitations

4.2.1. Compliance Schedules

State Water Resources Control Board (State Water Board) Resolution 2008-0025. Policy for Compliance Schedules in National Pollutant Discharge *Elimination System Permits* (Compliance Schedule Policy), authorizes the Water Board to include a compliance schedule in a permit for an existing discharger "to implement a new, revised, or newly interpreted water quality objective or criterion in a water quality standard that results in a permit limitation more stringent than the limitation previously imposed where the Water Board determines that the discharger has complied with the application requirements [of the] Policy and has demonstrated that the discharger needs additional time to implement actions to comply with the limitation."¹¹ These actions may include designing and constructing facilities or implementing new or significantly expanded programs and securing financing, if necessary. This Order applies to existing dischargers and newly interprets the Basin Plan's narrative biostimulatory substances water quality objective to establish numeric total inorganic nitrogen WQBELs that are more stringent than the previous permit, which contained no numeric effluent limitations for total inorganic nitrogen. The Dischargers have demonstrated, and the Water Board agrees that this will require the Dischargers to design, finance, and construct facilities, as well as

¹¹ The Compliance Schedule Policy defines "newly interpreted water quality objective or criterion in a water quality standard" as "a narrative water quality objective or criterion that, when interpreted during NPDES permit development (using appropriate scientific information and consistent with state and federal law) to determine the permit limitations necessary to implement the objective, results in a numeric permit limitation more stringent than the limit in the prior NPDES permit issued to the discharger." Resolution 2008-0025, section 1.e. "Permit limitation" is further defined as a "water quality-based effluent limitation (WQBEL). *Id.*, section 1.f.

implement new or significantly expanded programs (e.g., water recycling) to comply with these effluent limitations. The new interpretation of the biostimulatory substances water quality objective is explained in the *Memo on Numerical Translation of Narrative Objective*. The more stringent effluent limitations will require a 40 percent reduction in the total inorganic nitrogen loads discharged to San Francisco Bay and its tributaries compared to 2022 levels. Therefore, it is infeasible for Dischargers to meet these limitations immediately. Except for minor facilities (explained below), significant treatment upgrades will be needed to reduce nutrient discharges. Thus, this Order establishes compliance schedules as authorized by the Compliance Schedule Policy.

Compliance schedules under the Compliance Schedule Policy must require compliance as soon as possible and may not exceed ten years. The Water Board is thus prohibited from granting a compliance schedule in a permit that is longer than ten years. In this case, ten-year schedules are needed to develop the most effective strategy (e.g., water recycling, nature-based solutions, treatment upgrades) to comply with the total inorganic nitrogen WQBELs. As explained below through representative examples, a compliance schedule of 10 years is necessary for all dischargers.

All Dischargers except the three minor Dischargers discussed below (i.e., those with total inorganic nitrogen WQBELs based on an effluent concentration of 20.5 mg/L) must implement significant treatment plant upgrades and the projects needed to comply will involve planning, design, and construction. The planning and design phases typically include many steps such as evaluating options to improve treatment; developing preliminary designs, 10 percent designs, 50 percent designs, 90 percent designs, and final designs; and completing contract documents so the projects can be publicly bid and awarded to contractors. The Dischargers must also obtain permits from multiple agencies, which can take several months or longer. The construction phase generally takes several years. Additional time will also be needed for treatment unit startup, optimization, and troubleshooting.

Some Dischargers have begun the planning phase, and their proposed projects will take an anticipated 10 years. For example, Delta Diablo is planning to reduce its effluent nitrogen concentration to around 15 to 20 mg/L. This project will undergo two phases, where the first phase addresses current infrastructure upgrades needed at the facility, and the second phase increases aeration capacity to remove nitrogen. According to its preliminary schedule for phase one, it needs six months for planning, 18 months for design and bidding, four years for construction, and one year for startup. During the construction for phase one, phase two planning will take six months, 18 months for design, four years for construction, one year for startup, and one year for optimization. The total timeline for these projects is just over ten years.

The three minor Dischargers also need 10 years to comply. This is because these facilities will need to develop, plan, and implement actions to improve the performance of their facilities to accommodate population growth in their service areas and meet their final effluent limitations. In addition, they may need to consider trading options with larger facilities implementing more significant treatment plant upgrades. Trading with larger facilities may result in a more cost-effective regionwide strategy to ensure beneficial uses are protected. A trading program does not yet exist and will take time to develop, especially considering that no trading program has been developed in this Region or approved by the Water Board. As described in Provision 6.3.4, the trading program must be consistent with U.S. EPA guidance. The Regional Water Board intends to consider a formal trading program with the next permit reissuance. Since the final aggregate load WQBEL becomes effective in 10 years, a compliance schedule that aligns with this aggregate load WQBEL is necessary for minor dischargers to reap the potential benefits of trading.

Based on the above information, this Order grants until October 1, 2034, for Dischargers to begin complying with the final effluent limits. This represents a time schedule of 10 years, which is the maximum allowed by the Compliance Schedule Policy.

The Dischargers submitted the following documentation to qualify for compliance schedules:

- Descriptions of diligent efforts the Dischargers have made to quantify pollutant levels in the discharge, sources of the pollutant in the waste stream, and the results of those efforts. The Dischargers provided total inorganic nitrogen monitoring data for the previous order term. The primary source of total inorganic nitrogen in the discharges is human waste.
- Descriptions of source control and/or pollutant minimization efforts currently underway or completed. The Dischargers implement pollution prevention programs in accordance with their individual permits, and those with influent flows above five million gallons per day implement pretreatment programs that regulate industrial discharges. The primary source of total inorganic nitrogen in municipal wastewater is human waste; therefore, Dischargers do not have a practical way of controlling influent levels.
- Proposed schedules for additional or future source control measures, pollutant minimization, or waste treatment. Because the primary source of total inorganic nitrogen in municipal wastewater is human waste, additional source control and pollution minimization is infeasible. Provisions 6.3.3 and 6.3.4 of the Order require the Dischargers to submit strategies to comply with the final effluent limitations in Table 4 of the Order, including

specific projects to reduce total inorganic nitrogen loads discharged to San Francisco Bay.

- Data demonstrating current treatment facility performance to compare against limitations. The Dischargers provided total inorganic nitrogen monitoring data. These data were used to determine that Dischargers would be unable to meet the final effluent limitations immediately. They were also used to establish the performance-based interim effluent limitations in Table 3 of the Order as described in Fact Sheet section 4.2.2 below.
- Highest discharge quality that can reasonably be achieved until final compliance is attained. Compliance with the interim effluent limitations will ensure that each Discharger maintains its discharge at the highest levels that can reasonably be achieved until compliance with the final effluent limitations are attained. The Regional Water Board will reconsider the interim effluent limitations during the permit reissuance scheduled for 2029.
- Demonstration that proposed schedules are as short as practicable. The Dischargers provided planned construction schedules for treatment plant upgrades that are being undertaken to reduce total inorganic nitrogen discharges. As explained above, a ten-year compliance schedule is as short as practicable because of the time needed to plan, design, fund, permit, construct, and optimize treatment plant upgrades regionwide.

Provision 6.3.3 of the Order includes interim requirements and dates for their achievement. The interim dates are no more than one year apart. The Order requires the Dischargers to notify the Regional Water Board, in writing, no later than 14 days following each interim date, of their compliance or noncompliance with the interim requirements due on that date. Because the compliance schedules exceed one year, the Order establishes interim numeric limitations as described below.

The benefit of the compliance schedule provided in this Order is that Dischargers do not have to immediately comply with the final WQBELs while they undertake the considerable and costly actions necessary to ultimately achieve compliance by the end of the compliance schedule in ten years. For the term of this permit, this Order requires compliance with existing performancebased interim effluent limitations and other actions to put Dischargers on a path toward compliance.

4.2.2. Interim Effluent Limitations

Because the compliance schedules extend beyond one year, the Compliance Schedule Policy requires that this Order include interim effluent limitations based on current treatment performance or existing permit limitations, whichever are more stringent. The interim effluent limitations in this Order are designed to cap total inorganic nitrogen loads at existing treatment levels. A period from 2013 through 2022 was chosen to represent current treatment capabilities, to account for variability, and to provide sufficient data for statistical analysis. Total inorganic nitrogen loads were calculated using data from days when both total ammonia and nitrate-nitrite were sampled. The sum is the total inorganic nitrogen discharged for a given day. To calculate the interim effluent limitation for each Discharger, the 95th percentile of each Discharger's total inorganic nitrogen loads from May 1 through September 30 of 2013 through 2022 were used, assuming a lognormal distribution. The resulting interim effluent limitations are listed in Table 3 of the Order. Compliance with the interim limits is based on a five-month average of daily total inorganic nitrogen loads from May through September of each year.

4.3. Discharge Requirement Considerations

- 4.3.1. **Anti-Backsliding.** This Order complies with the anti-backsliding provisions of CWA sections 402(o) and 303(d)(4), and 40 C.F.R. section 122.44(l), which generally require effluent limitations in a reissued permit to be as stringent as those in the previous order. The effluent limitations in this Order are new and are more stringent than those in the previous order.
- 4.3.2. **Antidegradation.** This Order complies with the antidegradation provisions of 40 C.F.R. section 131.12 (federal policy) and State Water Board Resolution 68-16 (state policy). Permitted discharges must be consistent with these policies. This Order does not decrease the quality nor increase the quantity of the Dischargers' nutrient discharges to San Francisco Bay and its tributaries. The Dischargers' discharges into San Francisco Bay are authorized by the individual NPDES permits listed in Attachment B. This Order does not authorize any additional discharges, but rather requires the amount of nitrogen authorized by these existing permits to be reduced. The performance-based interim limits ensure that the Dischargers will maintain existing performance and do not authorize increased nitrogen discharges, temporary or otherwise.

This Order complies with the antidegradation requirements of 40 C.F.R. section 131.12 and State Water Board Resolution 68-16, as well as the State Water Resources Control Board's Administrative Procedures Update, Antidegradation Policy Implementation for NPDES Permitting, 90 004 (APU 90-004). As explained below, this Order will not degrade San Francisco Bay water quality with respect to biostimulatory substances, including in the Lower South Bay. Instead, this Order will restore water quality to the typically high levels observed for many years and protect existing beneficial uses. For purposes of the antidegradation policies, the baseline water quality is the best water quality that has existed since 1968 (state policy) or 1975 (federal policy) unless some degradation has been authorized. No degradation for biostimulatory substances has been authorized since 1968 or 1975; therefore, the baseline for comparison

with the biostimulatory water quality objective is the best water quality since then.

Prior to passage of the Clean Water Act in 1972, San Francisco Bay water quality was often poor. Pollutant discharges from many sources, including sewage systems, contributed to eutrophication, foul smells, and low dissolved oxygen. San Francisco Bay south of the Dumbarton Bridge had alarmingly low dissolved oxygen concentrations due to excessive algal growths caused by biostimulatory substances in wastewater and the discharge of high oxygendemanding substances (Interim Water Quality Control Plan, San Francisco Bay, Basin 2, June 1971). Water quality related to biostimulatory substances greatly improved during the 1970s and 1980s as secondary treatment was installed to remove biochemical oxygen demand from municipal wastewater.¹² These improvements have been consistently maintained since then.¹³ For example, dissolved oxygen concentrations have remained relatively constant and protective of beneficial uses, as demonstrated by U.S. Geological Survey data collected along the "spine" of the bay shown in the figure below on the right. The figure on the left below shows the numbered station locations where the data are collected during every cruise. Since 1993, the U.S. Geological Survey has conducted monthly cruises along the entire Bay-Delta system as part of the Regional Monitoring Program for Water Quality in San Francisco Bay



Dissolved oxygen is a good proxy for the effects of biostimulatory substances on beneficial uses. When biostimulatory substances (i.e., nutrients) feed an algal bloom, the subsequent consumption of dissolved oxygen leads to low dissolved oxygen levels that can harm beneficial uses. Although dissolved oxygen levels throughout the bay have remained consistently high, occasional algal blooms have periodically occurred, including some toxic algal blooms. However, these algal blooms rarely lasted long enough or spread far enough to cause nuisance or adversely affect beneficial uses throughout San Francisco Bay. While sufficient nutrients have been present in San Francisco Bay to

¹² SFEI, 2007. The Pulse of the Estuary: Monitoring and Managing Water Quality in the San Francisco Estuary. SFEI Contribution No. 532.

¹³ The exception is dissolved oxygen in Guadalupe and Alviso sloughs due to dischargers from former salt ponds in the Lower South Bay.

support large algal blooms, the risk of significant algal blooms and their adverse effects to beneficial uses has been minimized by the many other factors that together diminish the potential for algal blooms. These factors include turbidity, light penetration, clam foraging, temperature, and wave and tidal action that disrupt algal growth near the water surface.

Recently, however, as demonstrated by the large algal bloom in 2022 that led to massive fish kills (and the significant but less harmful bloom in 2023), the probability that a significant algal bloom is triggered appears to have increased during the dry season. Nutrients loading has not significantly changed recently, but it appears the other factors that affect the bay's resiliency against significant algal blooms have. The increase in probability, coupled with sufficient nutrient loading to support potentially large blooms, means that the risk posed by algal blooms has also increased. This Order requires nutrient reductions to reduce this risk to a level comparable to the past (as described above). Because the factors that affect the probability of algal blooms are uncontrollable, this Order seeks to reduce the risk, not by reducing the probability of algal blooms, but by reducing their consequences. For example, since nutrients contribute to the magnitude of an algal bloom by fueling algal growth, reducing nutrients will limit the effects of a bloom event. Reduced nutrient loads are expected to offset the increased probability of large algal blooms.

The baseline water quality (the highest water quality since 1968 and 1975) met the narrative biostimulatory water quality objective. In 2022 and 2023, however, nutrients in the Bay fed algal blooms to the extent that they adversely affected beneficial uses and caused nuisance conditions. Where the baseline water quality is equal to or less than the applicable water quality objective, antidegradation policies require water quality to be maintained or improved. As explained above and elsewhere in this Order, this Order will improve water quality by requiring a significant reduction in the discharge of nitrogen to meet the narrative biostimulatory water quality objective and maintain and protect beneficial uses. Since this Order will not lower existing or baseline water quality, under APU 90-004 no further antidegradation analysis and no findings authorizing degradation are required.

4.3.3 Stringency of Requirements. This Order contains effluent limitations for total inorganic nitrogen that are no more stringent than required to implement CWA requirements. The total inorganic nitrogen effluent limitations are necessary to meet the Basin Plan's biostimulatory substances water quality objective. That objective has been approved pursuant to federal law and is an applicable federal water quality standard because U.S. EPA approved the objective prior to May 30, 2000. Beneficial uses and water quality objectives submitted to U.S. EPA prior to May 30, 2000, but not approved by U.S. EPA before that date, are "applicable water quality standards for purposes of the CWA" pursuant to 40 C.F.R. section 131.21(c)(1).

5. RATIONALE FOR RECEIVING WATER LIMITATIONS

The receiving water limitations for the biostimulatory substances water quality objective that are applicable to the Dischargers are established in the individual NPDES permits listed in Attachment B. This Order overlays nitrogen mass load reduction effluent limitations on the Dischargers that represent nitrogen reductions necessary to protect beneficial uses under limited duration, critical condition algal blooms. This Order recognizes that immediate compliance with the final effluent limitations to meet the biostimulatory substances water quality objective is impossible. Rather, it will take time, significant actions, and expenditures to comply. This Order provides a path and compliance schedules for Dischargers to comply with the biostimulatory substances water quality objective. As such, compliance with the conditions of this Order constitutes compliance with the receiving water limitations for biostimulatory substances for discharges of nitrogen.

This Order does not create new receiving water limitations. Specifically, the use of a dissolved oxygen threshold of 4.0 mg/L was an analytic step for purposes of translating the narrative biostimulatory water quality objective into numeric effluent limitations. The use of this dissolved oxygen value does not establish new receiving water limitations or promulgate any new, or amend existing, water quality objectives.

6. RATIONALE FOR PROVISIONS

6.1. Standard Provisions

Attachment D of each individual NPDES permit contains standard provisions that apply to all NPDES permits in accordance with 40 C.F.R. section 122.41 and additional conditions applicable to specific categories of permits in accordance with 40 C.F.R. section 122.42. The Discharger must comply with these provisions. The conditions set forth in 40 C.F.R. sections 122.41(a)(1) and (b) through (n) apply to all state-issued NPDES permits and must be incorporated into permits either expressly or by reference.

In accordance with 40 C.F.R. section 123.25(a)(12), states may omit or modify conditions to impose more stringent requirements. Attachment G of each individual NPDES permit contains sampling and reporting requirements and additional standard provisions that supplement the federal standard provisions in Attachment D.

Attachment D of each individual NPDES permit omits the federal conditions that address enforcement authority specified in 40 C.F.R. sections 122.41(j)(5) and (k)(2) because the State's enforcement authority under the Water Code is more stringent. In lieu of these conditions, the individual NPDES permits incorporate Water Code section 13387(e) by reference.

6.2. Monitoring and Reporting Provisions

CWA section 308 and 40 C.F.R. sections 122.41(h), 122.41(i)-(l), 122.44(i), and 122.48 require that NPDES permits specify monitoring and reporting requirements. Water Code section 13383 also authorizes the Regional Water Board to establish monitoring, inspection, entry, reporting, and recordkeeping requirements. The MRP establishes monitoring, reporting, and recordkeeping requirements that implement federal and State requirements. For more information, see Fact Sheet section 7. Consistent with the previous order, this Order requires influent monitoring for Dischargers with a design flow greater than or equal to 10 MGD for total ammonia, total Kjeldahl nitrogen, nitrate-nitrite, and total phosphorus; and effluent monitoring for all Dischargers for total ammonia, nitrate-nitrite, and total phosphorus. This Order requires influent monitoring for total Kjeldahl nitrogen (organic nitrogen plus ammonia) because untreated wastewater often contains high levels of organic nitrogen. It does not require effluent monitoring for total Kjeldhal nitrogen because treated wastewater contains very little organic nitrogen (about five percent of total nitrogen), and the remaining organic nitrogen in treated wastewater isn't as bioavailable.

6.3. Special Provisions

6.3.1. Reopener Provisions

These provisions are based on 40 C.F.R. sections 122.44(d)(1)(vi)(C), 122.62, and 122.63, and allow modification of this Order and its effluent limitations as necessary in response to updated water quality objectives, regulations, or other new and relevant information that may become available in the future, and other circumstances as allowed by law.

6.3.2. Monitoring, Modeling, and Subembayment Studies

This Order requires the Dischargers to conduct, by themselves or in collaboration with others, studies to address the potential impacts of nutrients on San Francisco Bay beneficial uses. These studies must be supported by receiving water monitoring and modeling efforts of San Francisco Bay as a whole to understand how the entire Bay assimilates nutrients and more specific studies to better understand how subembayments respond. There are efficiencies from collaborating on large-scale studies and studies led by individual dischargers when done in collaboration with the Nutrient Management Strategy Steering Committee. BACWA has identified \$2.2 million per year for five years for collective efforts, and the Regional Water Board finds this amount to be an appropriate level of funding to support further receiving water monitoring and science plan development and implementation as described in this provision. BACWA has identified that at least \$200,000 from its yearly support should be directed toward project management. To communicate findings from the science program, one of the project management deliverables will be to develop an annual report that summarizes the findings from the

monitoring, modelling, and studies and a breakdown of how the funds were spent that year. If the Dischargers and BACWA are successful in securing additional resources, such as from grants or other agencies, for nutrient monitoring or studies identified in the science plan, the additional funding will not count toward the Dischargers' level of effort under this provision.

These studies and analyses are necessary to continue to understand San Francisco Bay's interaction with nutrients and how these interactions can lead to harmful algal blooms. Support for receiving water monitoring will provide necessary data to further model San Francisco Bay nutrient loads, determine San Francisco Bay's response to nutrient loads, and inform the development and implementation of strategies to manage these nutrient loads. While total inorganic nitrogen has been identified as the limiting nutrient in San Francisco Bay, studies also need to track phosphorus levels and evaluate if phosphorus could seasonally limit algal growth in certain portions of San Francisco Bay.

These studies will be developed by the Nutrient Management Strategy Steering Committee and stakeholders, including the Dischargers, U.S. EPA, and San Francisco Baykeeper. This collaborative process will ensure that the Nutrient Science Plan is updated to ensure science-based decision making.

CWA section 1318(a) and Water Code section 13383 authorize this provision. CWA section 1318(a) authorizes the collection of information necessary to carry out the CWA's objectives, including but not limited to developing or assisting in the development of any effluent limitation, other limitation, prohibition, effluent standard, pretreatment standard, or standard of performance. Water Code section 13383 authorizes the Regional Water Board to establish monitoring, reporting, and recordkeeping requirements for NPDES dischargers. It also authorizes the Regional Water Board to require NPDES dischargers to provide other information as may be reasonably required.

6.3.3. Compliance Schedule and Reporting

The requirement to submit reports on measures each Discharger will implement to ensure compliance with the final WQBELs for total inorganic nitrogen is based on the Compliance Schedule Policy.

6.3.4. Regional Planning to Reduce Total Inorganic Nitrogen Loads

This Order requires major Dischargers to, by themselves or in collaboration with others, provide information on plans to meet the final effluent limitations in Table 4 of the Order, and evaluate the potential for nature-based systems (e.g., wetlands) and water recycling to further reduce nutrient loads to San Francisco Bay. This is necessary to encourage regional coordination so compliance with the final effluent limitations will occur as soon as possible as required by the Compliance Schedule Policy. This provision is also necessary to plan for multi-benefit options to achieve 50 and 60 percent load reductions from 2022 (60 and

68 percent from the 2019 baseline) if the next permit reissuance scheduled for 2029 finds them necessary.

As part of their regional coordination strategy, Dischargers may propose a formal nutrient trading or offset program to achieve final effluent limits for total inorganic nitrogen. If a discharger seeks to achieve compliance with final effluent limits by purchasing credits from another discharger, the Regional Planning report may propose a framework for nutrient trading to facilitate compliance with the final individual and aggregate effluent limits established in Table 4. While this Order establishes a baywide aggregate mass limit, the Dischargers may propose a baywide and subembayment trading program. As described in Fact Sheet section 6.3.2, there will be advances in our scientific understanding of how San Francisco Bay assimilates nutrient loads over this permit term.

CWA section 1318(a) and Water Code section 13383 authorize this provision. CWA section 1318(a) authorizes the collection of information necessary to carry out the CWA's objectives, including but not limited to developing or assisting in the development of any effluent limitation, other limitation, prohibition, effluent standard, pretreatment standard, or standard of performance. Water Code section 13383 authorizes the Regional Water Board to establish monitoring, reporting, and recordkeeping requirements for NPDES dischargers. It also authorizes the Regional Water Board to require NPDES dischargers to provide other information as may be reasonably required.

6.3.5. Multi-Benefit Solutions for Load Reductions

Multi-benefit projects will take longer to complete than conventional projects due to additional challenges associated with interagency agreements, multiagency permitting, and land acquisition. This provision requires Dischargers that identify long-term multi-benefit solutions (i.e., water recycling or naturebased solutions) that cannot be completed by the compliance date (October 1, 2034) for the final effluent limitations to identify such projects and their intent to pursue them. The Regional Water Board encourages Dischargers to pursue these long-term strategies when feasible because they are likely to result in a greater benefit to the community and the environment relative to treatment plant improvements alone. The Regional Water Board will consider available regulatory mechanisms to provide Dischargers that identify multi-benefit projects likely to result in total inorganic nitrogen loads at or below the final WQBELs more time to comply. Available regulatory mechanisms may include, for example, amending the Basin Plan to include a water quality attainment strategy for biostimulatory substances; finding that a new compliance schedule under the Compliance Schedule Policy is justified based on new, revised, or newly interpreted water quality objectives; or imposing a time schedule under a time schedule order or cease and desist order

Examples of multi-benefit solutions include three projects the Central Contra Costa Sanitary District has identified: (1) the Refinery Recycled Water Exchange Project would replace raw Delta water used at two Martinez refineries (PBF and Marathon), (2) the Potable Reuse Project would supplement water supplies for the East Bay Municipal Utility District, and (3) the Raw Wastewater Diversion with Dublin San Ramon Services District would produce recycled water to meet irrigation demand. These projects would provide multiple benefits and could significantly reduce Central Contra Costa Sanitary District's total inorganic nitrogen loads to San Francisco Bay. However, all three projects would require agreements among multiple agencies and will likely take longer than 10 years to implement. To move them forward, Central Contra Costa Sanitary District has identified milestones that it can report on annually over the next five years to determine each project's feasibility and, if feasible, an implementation schedule.

Another example of a multi-benefit solution is the Pure Water Peninsula project. This collaborative is made up of Silicon Valley Clean Water, the San Francisco Public Utilities Commission, the City of San Mateo, the Bay Area Water Supply and Conservation Agency, California Water Service, and the City of Redwood City, who together are developing a regional potable reuse project. The Pure Water Peninsula project would provide purified water to resolve multiple water supply and wastewater issues, while realizing the benefits of shared infrastructure, asset recovery, economies of scale, and a relatively competitive funding strategy. Source water for this potable reuse project would be recycled water from Silicon Valley Clean Water and the City of San Mateo, diverting 8.0 MGD from each facility. The current schedule projects a starting date for water delivery of 2039. The long timeline is associated with the number of agreements that need to be developed among the project partners, the need to complete CEQA and permitting efforts, and the time necessary to implement multiple construction packages. Silicon Valley Clean Water will report on the project milestones as the Pure Water Peninsula project progresses.

Water Code section 13383 authorizes the Regional Water Board to establish monitoring, reporting, and recordkeeping requirements for NPDES dischargers. It also authorizes the Regional Water Board to require NPDES dischargers to provide other information as may be reasonably required.

6.3.6. Recognition of Early Actors

The previous order encouraged Dischargers to make early investments in nutrient reductions in the absence of nutrient load limitations. Fact Sheet section II.E of the previous order identified several Dischargers that planned to take early actions to reduce total inorganic nitrogen loads to San Francisco Bay. Once complete, these projects were expected to result in effluent total inorganic nitrogen concentrations below 20 mg/L. Because of these investments, nutrient
loads from these Dischargers to San Francisco Bay will be realized well before those of other Dischargers that have yet to undertake such investments.

This provision requires Dischargers that have already completed or begun construction or implementation of their projects by the effective date of this Order and that seek to be recognized as early actors to provide updates with each Annual Nutrients Report required by MRP section 5.2.2. Because early actions to reduce total inorganic nitrogen loads to San Francisco Bay will make excessive algae blooms less likely sooner, the Regional Water Board will consider available regulatory mechanisms to provide any such Dischargers that are unable to comply with final WQBELs upon completion of their projects more time to comply.

6.3.7. Report of Waste Discharge

40 C.F.R section 122.21 requires publicly owned treatment works with a currently effective permit to submit a new application (report of waste discharge) at least 180 days before the expiration of the existing permit. Under 40 C.F.R. section 122.6 and title 23, California Code of Regulations, section 2335.4, if a discharger submits a timely and complete report of waste discharge for permit reissuance and the Regional Water Board does not reissue the permit before the expiration date, the expired permit continues in force and effect until the effective date of the reissued permit.

7. RATIONALE FOR MONITORING AND REPORTING REQUIREMENTS

The following provides the rationale for the monitoring and reporting requirements in the MRP.

7.1. Monitoring Requirements Rationale

- 7.1.1. **Influent Monitoring.** Influent monitoring is necessary to understand nutrient speciation entering treatment plants, optimize nutrient removal efficiencies, inform treatment plant upgrade designs, and evaluate trends.
- 7.1.2. **Effluent Monitoring.** Effluent monitoring is necessary to understand Facility operations, evaluate compliance with this Order's effluent limitations, and determine trends as treatment plant improvements are made over this permit term.

8. PUBLIC PARTICIPATION

The Regional Water Board considered the issuance of WDRs that will serve as an NPDES permit for point source discharges of nutrients from the Dischargers' facilities. As a step in the WDR adoption process, Regional Water Board staff developed tentative WDRs and encouraged public participation in the WDR adoption process.

8.1. Notification of Interested Parties. The Regional Water Board notified the Dischargers and interested agencies and persons of its intent to prescribe WDRs for the discharge and provided an opportunity to submit written comments and recommendations. The public had access to the agenda and any changes in dates and locations through the <u>Regional Water Board's website</u> (waterboards.ca.gov/sanfranciscobay).

Consistent with Water Code section 189.7, the Regional Water Board notified potentially affected disadvantaged communities and tribal communities of this Order and provided them with an opportunity to engage prior to the public comment period. As part of the outreach effort, the Regional Water Board held a workshop to engage with interested disadvantaged communities and tribal communities on March 5, 2024. The Regional Water Board also notified disadvantaged communities and tribal communities and tribal communities and tribal communities and tribal munities of the outreach effort.

8.2. Environmental Justice. Water Code section 13149.2 requires the Regional Water Board to make a concise programmatic finding on potential environmental justice, tribal impact, and racial equity considerations for reissued regional WDRs. The Regional Water Board has considered readily available information concerning anticipated water quality impacts in disadvantaged communities and tribal communities that may result from the changes to the permit requirements in this Order. The Regional Water Board has also considered the environmental justice concerns within its authority raised regarding those impacts.

The Discharges authorized by this Order will occur across the San Francisco Bay region. There are disadvantaged communities¹⁴ and tribal communities¹⁵ in the region. This Order imposes numeric effluent limitations for total inorganic nitrogen to reduce 2022 dry-season nitrogen loads to San Francisco Bay by 40 percent and provides a 10-year compliance schedule for Dischargers to meet final effluent limits. The reduction in nitrogen loads will reduce the risk of large algal blooms and protect the beneficial uses of waters across the San Francisco Bay region. These changes to permit requirements will improve water quality in disadvantaged communities and tribal communities and the region overall.

¹⁴ Water Code section 13149.2, subdivision (f)(1), defines "disadvantaged community" as "a community in which the median household income is less than 80 percent of the statewide annual median household income level." The statewide annual median household income in the U.S. Census Bureau 2020 Census was \$78,672.6. Based on this data, a community with a household income less than \$62,938 is a "disadvantaged community" as used in section 13149.2.

¹⁵ Water Code section 13149.2, subdivision (f)(3), defines "tribal community" as "a community within a federally recognized California Native American tribe or nonfederally recognized Native American tribe on the contact list maintained by the Native American Heritage Commission for the purposes of Chapter 905 of the Statutes of 2004."

Dischargers raised concerns about the impact compliance costs will have on disadvantaged communities. Although the cost concerns are beyond the scope of Water Code section 13149.2, the Regional Water Board has considered these concerns. The Regional Water Board recognizes the costs to implement the Order may have a greater impact on disadvantaged communities; however, not implementing the Order could result in detrimental impacts to water quality in disadvantaged communities and the region overall. Harmful algal blooms negatively affect many beneficial uses, such as water contact and non-contact recreation; fishing; shellfish harvesting; cold and warm freshwater, marine, and estuarine habitats; and preservation of rare and endangered species. Poor water quality can also lead to increased health care costs. Harmful algal bloom toxins can cause human illness through direct contact, airborne transmission, and fish and shellfish poisoning. (See also finding 2.2 of the Order.)

8.3. Written Comments. Interested persons were invited to submit written comments concerning the tentative WDRs as explained through the notification process. Comments were to be submitted either in person, by e-mail, or by mail to the Executive Office at the Regional Water Board at 1515 Clay Street, Suite 1400, Oakland, California 94612, to the attention of Robert Schlipf.

Written comments were due at the Regional Water Board office by 5:00 p.m. on May 6, 2024.

8.4. Public Hearing. The Regional Water Board held a public hearing on the tentative Order during its meeting at the following date and time:

Date: July 10, 2024 Time: 9:00 a.m.

Contact: Robert Schlipf, (510) 622-2478, robert.schlipf@waterboards.ca.gov.

Interested persons were provided notice of the hearing and information on how to participate. At the public hearing, the Regional Water Board heard testimony pertinent to the discharge and Order.

Dates and venues can change. The <u>Regional Water Board's website</u> is (waterboards.ca.gov/sanfranciscobay), where one can access the current agenda for changes.

8.5. Reconsideration of Waste Discharge Requirements. Any person aggrieved by this Regional Water Board action may petition the State Water Board to review the action in accordance with Water Code section 13320 and California Code of Regulations, title 23, sections 2050. The State Water Board must receive the petition at the following address within 30 calendar days of the date of Regional Water Board action:

State Water Resources Control Board Office of Chief Counsel P.O. Box 100, 1001 | Street Sacramento, CA 95812-0100

A petition may also be filed by email at <u>waterqualitypetitions@waterboards.ca.gov.</u>

For instructions on how to file a water quality petition for review, see the <u>Water</u> <u>Board's petition instructions</u> (waterboards.ca.gov/public_notices/petitions/water_quality/wqpetition_instr.shtml).

- 8.6. Information and Copying. Supporting documents and comments received are on file. To review these documents, please contact Melinda Wong, the Regional Water Board's custodian of records, by calling (510) 622-2300 or emailing <u>Melinda.Wong@waterboards.ca.gov</u>. Document copying may be arranged.
- **8.7. Register of Interested Persons.** Any person interested in being placed on the mailing list for information regarding the WDRs and NPDES permit should contact the Regional Water Board, reference the Facility, and provide a name, address, and phone number.
- **8.8.** Additional Information. Requests for additional information or questions regarding this Order should be directed to Robert Schlipf, (510) 622-2478, robert.schlipf@waterboards.ca.gov.