Issue Date: June 30, 2024

PMP Corporation

PMP Dual-point Hydrostatic Sensor 63303 and Mini-Hydrostatic Sensor 63304 as evaluated with the Veeder-Root TLS-350 (version 336 firmware)
INTERSTITIAL DETECTOR (LIQUID-PHASE)

Detector:

Output type: qualitative

Sampling frequency: continuous

Operating principle: float switch

Test Results:

reserves and	<u>propylene glycol</u> <u>(in water)</u>	ethylene glycol (in water)	<u>calcium chloride</u> (CaCl) (in water)	<u>wate</u> r
Dual-Point Hydrostatic Sensor 63303				
Detection time (sec)	<1	<1	<1	<1
Fall time (sec)	<1	<1	<1	<1
Precision (in)	0.00	0.00	0.00	0.01
Detection Threshold				
Low level (in)	1.48	1.48	1.40	1.52
High level (in)	14.50	14.14	13.67	13.99
Mini-Hydrostatic Sensor 63304				
Detection time (min)	<1	<1	<1	<1
Fall time (min)	<1	<1	<1	<1
Precision (in)	0.00	0.00	0.00	0.01
Detection Threshold Level				
Low level (in)	1.18	1.18	1.18	1.18

Applicability: California Code of Regulations require a written statement of compatibility for systems containing products other than petroleum-based fuels (biodiesel blends greater than 20%, ethanol blends greater than 10%, solvents, etc.).

Comments:

63303 is a tall dual-point sensor that indicates both low-level and high-level conditions.
63304 is a shorter, stainless steel body sensor that only registers low-level liquid conditions.
These sensors were third party evaluated with a Veeder Root TLS-350 console (version 336 firmware).

PMP Corporation claims that these sensors will work with these other consoles: the TLS-4 series, TLS-350 series, TLS-300 series, ILS-350, Simplicity, Gilbarco EMC series, EMC Basic series, EMC-PC, Red Jacket ProMax and ProPlus.

PMP Corporation Evaluator: Solutions Engineering Group

25 Security Drive

Avon, CT 06001-0422

Tel: (860) 677-9656

Toll Free: (800) 243-6628

E-mail: sales@pmp-corp.com

URL: www.pmp-corp.com

420 N. Main Street

Montgomery, IL 60538-1367

Tel: (630) 701-7703

Date of Evaluations: 11/1/2023



Appearance on this list is not to be construed as an endorsement by any regulatory agency nor is it any guarantee of the performance of the method or equipment.

Equipment should be installed and operated in accordance with all applicable laws and regulations. For full details, please refer to our expanded "DISCLAIMER" page.